

Specifications



Photo is representative



Eaton 171333

Eaton Moeller® series SL4 Ba15d
continuous light module, red

General specifications

PRODUCT NAME	Eaton Moeller® series SL4 Continuous light module
CATALOG NUMBER	171333
MODEL CODE	SL4-L-R
EAN	4015081678709
PRODUCT LENGTH/DEPTH	43 mm
PRODUCT HEIGHT	75 mm
PRODUCT WIDTH	43 mm
PRODUCT WEIGHT	0.037 kg
CERTIFICATIONS	UL File No.: E29184 UL Category Control No.: NKCR CSA Class No.: NKCR7 UL 508 IEC/EN 60947-5-1 CSA-C22.2 No. 14-10 CSA-C22.2 No. 94-91 UL CE Certified by UL for use in Canada IEC/EN 60529 UL report applies to both US and Canada
CATALOG NOTES	Without light elements



Powering Business Worldwide

Climatic environmental conditions

AMBIENT OPERATING TEMPERATURE - MAX	60 °C
AMBIENT OPERATING TEMPERATURE - MIN	-30 °C
CLIMATIC PROOFING	Damp heat, cyclic, to IEC 60068-2-30 Damp heat, constant, to IEC 60068-2-78

Features & functions

COLOR	Red
ENCLOSURE COLOR	Black
FUNCTIONS	Continuous light
LIGHT MODULES	Filament lamp max. 4 W
NUMBER OF MODULES	Max. 10 (with base for mounting on both sides) Max. 5 (with standard base)

Electrical rating

LEAKAGE CURRENT	0.003 A
POWER CONSUMPTION	Max. 4 W with the specified voltages
RATED INSULATION VOLTAGE (UI)	250 V
RATED OPERATIONAL VOLTAGE (UE) AT AC - MAX	250 V
RATED OPERATIONAL VOLTAGE (UE) AT AC - MIN	24 V
RATED OPERATIONAL VOLTAGE (UE) AT DC - MAX	250 V
RATED OPERATIONAL VOLTAGE (UE) AT DC - MIN	24 V

General information

CONNECTION TO SMARTWIRE-DT	No
DEGREE OF PROTECTION	IP66 NEMA 4X
LIFESPAN, ELECTRICAL	3,000 h
LIGHT TYPE	Continuous light
MATERIAL	Cap: Polycarbonate (PC) Enclosure: Polycarbonate (PC)
MOUNTING METHOD	BA15d lamp socket
MOUNTING POSITION	As required
OVERVOLTAGE CATEGORY	III
POLLUTION DEGREE	3
PRODUCT CATEGORY	SL signal towers
RADIATION ANGLE	360 °
RATED IMPULSE WITHSTAND VOLTAGE (UIMP)	4000 V AC
SHOCK RESISTANCE	15 g, Mechanical, According to IEC/EN 60068-2-27, Sinusoidal shock 11 ms Mechanical, According to IEC/EN 60068-2-27
TYPE	Continuous light module
VOLTAGE TYPE	AC/DC

Resources

BROCHURES	SL4, SL7, SLC Stack light overview brochure BR047017
CATALOGUES	eaton-rmq-titan-brochure-br047004en-en-us.pdf eaton-pushbuttons-signal-towers-sensors-assortment-overview-catalog-ca047003en-en-us.pdf
DECLARATIONS OF CONFORMITY	eaton-continuous-light-module-declaration-of-conformity-uk251039en.pdf eaton-continuous-light-module-declaration-of-conformity-eu250556en.pdf
DRAWINGS	eaton-operating-sl4-continuous-light-dimensions.eps eaton-operating-button-symbol-009.eps eaton-operating-sl7-continuous-light-symbol.eps
ECAD MODEL	ETN.171333.edz
INSTALLATION INSTRUCTIONS	IL047005ZU
INSTALLATION VIDEOS	Signal towers SL4 and SL7
MCAD MODEL	eaton-light-modules-mcad-drawings-sl4-bfl4.dwg DA-CS-sl4_bfl4

PROJECT NAME:
PROJECT NUMBER:
PREPARED BY:
DATE:



Eaton Corporation plc Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2026 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

