

# Specifications



Photo is representative



## Eaton 171340

Eaton Moeller® series SL4 Flashing light module, white, LED, 24 V

### General specifications

|                     |                                                 |
|---------------------|-------------------------------------------------|
| <b>PRODUCT NAME</b> | Eaton Moeller® series SL4 Flashing light module |
|---------------------|-------------------------------------------------|

|                       |        |
|-----------------------|--------|
| <b>CATALOG NUMBER</b> | 171340 |
|-----------------------|--------|

|                   |            |
|-------------------|------------|
| <b>MODEL CODE</b> | SL4-BL24-W |
|-------------------|------------|

|            |               |
|------------|---------------|
| <b>EAN</b> | 4015081678761 |
|------------|---------------|

|                             |       |
|-----------------------------|-------|
| <b>PRODUCT LENGTH/DEPTH</b> | 43 mm |
|-----------------------------|-------|

|                       |       |
|-----------------------|-------|
| <b>PRODUCT HEIGHT</b> | 75 mm |
|-----------------------|-------|

|                      |       |
|----------------------|-------|
| <b>PRODUCT WIDTH</b> | 43 mm |
|----------------------|-------|

|                       |          |
|-----------------------|----------|
| <b>PRODUCT WEIGHT</b> | 0.042 kg |
|-----------------------|----------|

|                       |                                                                                                                                                                                                                                                                      |
|-----------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>CERTIFICATIONS</b> | UL 508<br>UL report applies to both US and Canada<br>UL<br>UL Category Control No.: NKCR<br>UL File No.: E29184<br>Certified by UL for use in Canada<br>IEC/EN 60947-5-1<br>CSA-C22.2 No. 94-91<br>CSA Class No.: NKCR7<br>IEC/EN 60529<br>CE<br>CSA-C22.2 No. 14-10 |
|-----------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|



Powering Business Worldwide

## Climatic environmental conditions

|                                     |       |
|-------------------------------------|-------|
| AMBIENT OPERATING TEMPERATURE - MAX | 60 °C |
|-------------------------------------|-------|

|                                     |        |
|-------------------------------------|--------|
| AMBIENT OPERATING TEMPERATURE - MIN | -30 °C |
|-------------------------------------|--------|

|                   |                                                                                |
|-------------------|--------------------------------------------------------------------------------|
| CLIMATIC PROOFING | Damp heat, constant, to IEC 60068-2-78<br>Damp heat, cyclic, to IEC 60068-2-30 |
|-------------------|--------------------------------------------------------------------------------|

## Features & functions

|       |       |
|-------|-------|
| COLOR | Other |
|-------|-------|

|                 |       |
|-----------------|-------|
| ENCLOSURE COLOR | Black |
|-----------------|-------|

|           |               |
|-----------|---------------|
| FUNCTIONS | Blinker light |
|-----------|---------------|

|               |     |
|---------------|-----|
| LIGHT MODULES | LED |
|---------------|-----|

|                   |                                                                               |
|-------------------|-------------------------------------------------------------------------------|
| NUMBER OF MODULES | Max. 10 (with base for mounting on both sides)<br>Max. 5 (with standard base) |
|-------------------|-------------------------------------------------------------------------------|

## Electrical rating

|                 |         |
|-----------------|---------|
| LEAKAGE CURRENT | 0.003 A |
|-----------------|---------|

|                               |       |
|-------------------------------|-------|
| RATED INSULATION VOLTAGE (UI) | 250 V |
|-------------------------------|-------|

|                                            |      |
|--------------------------------------------|------|
| RATED OPERATIONAL VOLTAGE (UE) AT AC - MAX | 24 V |
|--------------------------------------------|------|

|                                            |      |
|--------------------------------------------|------|
| RATED OPERATIONAL VOLTAGE (UE) AT AC - MIN | 24 V |
|--------------------------------------------|------|

|                                            |      |
|--------------------------------------------|------|
| RATED OPERATIONAL VOLTAGE (UE) AT DC - MAX | 24 V |
|--------------------------------------------|------|

|                                            |      |
|--------------------------------------------|------|
| RATED OPERATIONAL VOLTAGE (UE) AT DC - MIN | 24 V |
|--------------------------------------------|------|

## General information

|                            |    |
|----------------------------|----|
| CONNECTION TO SMARTWIRE-DT | No |
|----------------------------|----|

|                     |                     |
|---------------------|---------------------|
| CURRENT CONSUMPTION | 50 mA at 24 V AC/DC |
|---------------------|---------------------|

|                      |                 |
|----------------------|-----------------|
| DEGREE OF PROTECTION | IP66<br>NEMA 4X |
|----------------------|-----------------|

|                    |      |
|--------------------|------|
| FLASHING FREQUENCY | 2 Hz |
|--------------------|------|

|                      |           |
|----------------------|-----------|
| LIFESPAN, ELECTRICAL | 100,000 h |
|----------------------|-----------|

|            |                |
|------------|----------------|
| LIGHT TYPE | Flashing light |
|------------|----------------|

|          |                                                          |
|----------|----------------------------------------------------------|
| MATERIAL | Cap: Polycarbonate (PC)<br>Enclosure: Polycarbonate (PC) |
|----------|----------------------------------------------------------|

|                   |             |
|-------------------|-------------|
| MOUNTING POSITION | As required |
|-------------------|-------------|

|                      |     |
|----------------------|-----|
| OVERVOLTAGE CATEGORY | III |
|----------------------|-----|

|                  |   |
|------------------|---|
| POLLUTION DEGREE | 3 |
|------------------|---|

|                  |                  |
|------------------|------------------|
| PRODUCT CATEGORY | SL signal towers |
|------------------|------------------|

|                 |       |
|-----------------|-------|
| RADIATION ANGLE | 360 ° |
|-----------------|-------|

|                                        |           |
|----------------------------------------|-----------|
| RATED IMPULSE WITHSTAND VOLTAGE (UIMP) | 4000 V AC |
|----------------------------------------|-----------|

|                  |                                                                                                                        |
|------------------|------------------------------------------------------------------------------------------------------------------------|
| SHOCK RESISTANCE | 15 g, Mechanical, According to IEC/EN 60068-2-27, Sinusoidal shock 11 ms<br>Mechanical, According to IEC/EN 60068-2-27 |
|------------------|------------------------------------------------------------------------------------------------------------------------|

|      |                       |
|------|-----------------------|
| TYPE | Flashing light module |
|------|-----------------------|

|              |       |
|--------------|-------|
| VOLTAGE TYPE | AC/DC |
|--------------|-------|

## Resources

|                            |                                                                                                                                                                                                                    |
|----------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| BROCHURES                  | <a href="#">SL4, SL7, SLC Stack light overview brochure BR047017</a>                                                                                                                                               |
| CATALOGUES                 | <a href="#">eaton-rmq-titan-brochure-br047004en-en-us.pdf</a><br><a href="#">eaton-pushbuttons-signal-towers-sensors-assortment-overview-catalog-ca047003en-en-us.pdf</a>                                          |
| DECLARATIONS OF CONFORMITY | <a href="#">eaton-continuous-light-module-declaration-of-conformity-eu250556en.pdf</a><br><a href="#">eaton-continuous-light-module-declaration-of-conformity-uk251039en.pdf</a>                                   |
| DRAWINGS                   | <a href="#">eaton-operating-sl4-continuous-light-dimensions.eps</a><br><a href="#">eaton-operating-sl7-flashing-light-symbol.eps</a><br><a href="#">eaton-operating-button-sl7-continuous-light-symbol-003.eps</a> |
| ECAD MODEL                 | <a href="#">ETN.171340.edz</a>                                                                                                                                                                                     |
| INSTALLATION INSTRUCTIONS  | <a href="#">IL047001ZU</a>                                                                                                                                                                                         |
| INSTALLATION VIDEOS        | <a href="#">Signal towers SL4 and SL7</a>                                                                                                                                                                          |
| MCAD MODEL                 | <a href="#">eaton-light-modules-mcad-drawings-sl4-bfl4.dwg</a><br><a href="#">DA-CS-sl4_bfl4</a>                                                                                                                   |

|                 |
|-----------------|
| PROJECT NAME:   |
| PROJECT NUMBER: |
| PREPARED BY:    |
| DATE:           |



**Eaton Corporation plc** Eaton House  
30 Pembroke Road  
Dublin 4, Ireland  
Eaton.com

© 2026 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

