

Specifications



Photo is representative



Eaton 171378

Eaton Moeller® series SL4 LED multistrobe light, orange 24V

General specifications

PRODUCT NAME	Eaton Moeller® series SL4 Multi-strobe light module
CATALOG NUMBER	171378
MODEL CODE	SL4-FL24-A-M
EAN	4015081679072
PRODUCT LENGTH/DEPTH	43 mm
PRODUCT HEIGHT	75 mm
PRODUCT WIDTH	43 mm
PRODUCT WEIGHT	0.042 kg

CERTIFICATIONS	CSA-C22.2 No. 14-10 IEC/EN 60947-5-1 UL Category Control No.: NKCR UL File No.: E29184 CE UL CSA Class No.: NKCR7 IEC/EN 60529 Certified by UL for use in Canada CSA-C22.2 No. 94-91 UL report applies to both US and Canada UL 508
-----------------------	--



Powering Business Worldwide

Climatic environmental conditions

AMBIENT OPERATING TEMPERATURE - MAX	60 °C
-------------------------------------	-------

AMBIENT OPERATING TEMPERATURE - MIN	-30 °C
-------------------------------------	--------

CLIMATIC PROOFING	Damp heat, cyclic, to IEC 60068-2-30
	Damp heat, constant, to IEC 60068-2-78

Features & functions

COLOR	Orange
-------	--------

ENCLOSURE COLOR	Black
-----------------	-------

FEATURES	Various strobe sequences
----------	--------------------------

FUNCTIONS	Flash light
-----------	-------------

LIGHT MODULES	LED
---------------	-----

NUMBER OF MODULES	Max. 5 (with standard base)
	Max. 10 (with base for mounting on both sides)

Electrical rating

LEAKAGE CURRENT	0.003 A
-----------------	---------

RATED INSULATION VOLTAGE (UI)	250 V
-------------------------------	-------

RATED OPERATIONAL VOLTAGE (UE) AT AC - MAX	24 V
--	------

RATED OPERATIONAL VOLTAGE (UE) AT AC - MIN	24 V
--	------

RATED OPERATIONAL VOLTAGE (UE) AT DC - MAX	24 V
--	------

RATED OPERATIONAL VOLTAGE (UE) AT DC - MIN	24 V
--	------

General information

CONNECTION TO SMARTWIRE-DT	No
----------------------------	----

CURRENT CONSUMPTION	max. 165 mA at 24 V AC/DC
---------------------	---------------------------

DEGREE OF PROTECTION	NEMA 13 IP66
----------------------	-----------------

FLASHING FREQUENCY	1 - 2.6 Hz
--------------------	------------

LIFESPAN, ELECTRICAL	100,000 h
----------------------	-----------

LIGHT TYPE	Multistrobe light
------------	-------------------

MATERIAL	Enclosure: Polycarbonate (PC) Cap: Polycarbonate (PC)
----------	--

MOUNTING POSITION	As required
-------------------	-------------

OVERVOLTAGE CATEGORY	III
----------------------	-----

POLLUTION DEGREE	3
------------------	---

PRODUCT CATEGORY	SL signal towers
------------------	------------------

RADIATION ANGLE	360 °
-----------------	-------

RATED IMPULSE WITHSTAND VOLTAGE (UIMP)	4000 V AC
--	-----------

SHOCK RESISTANCE	15 g, Mechanical, According to IEC/EN 60068-2-27, Sinusoidal shock 11 ms Mechanical, According to IEC/EN 60068-2-27
------------------	--

TYPE	LED for effective signaling effect
------	--

- Multi-strobe light module

VOLTAGE TYPE

AC/DC

Resources

BROCHURES

[SL4, SL7, SLC Stack light overview brochure BR047017](#)

CATALOGUES

[eaton-rmq-titan-brochure-br047004en-en-us.pdf](#)
[eaton-pushbuttons-signal-towers-sensors-assortment-overview-catalog-ca047003en-en-us.pdf](#)

DECLARATIONS OF CONFORMITY

[eaton-continuous-light-module-declaration-of-conformity-eu250556en.pdf](#)
[eaton-continuous-light-module-declaration-of-conformity-uk251039en.pdf](#)

DRAWINGS

[eaton-operating-sl4-continuous-light-dimensions.eps](#)
[eaton-operating-sl4-multi-strobe-light-module-symbol.eps](#)
[eaton-operating-button-sl7-continuous-light-symbol.eps](#)

ECAD MODEL

[ETN.171378.edz](#)

INSTALLATION INSTRUCTIONS

[IL047001ZU](#)

INSTALLATION VIDEOS

[Signal towers SL4 and SL7](#)

MCAD MODEL

[eaton-light-modules-mcad-drawings-sl4-bfl4.dwg](#)
[DA-CS-sl4_bfl4](#)

PROJECT NAME:
PROJECT NUMBER:
PREPARED BY:
DATE:



Eaton Corporation plc Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2026 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

