

Specifications



Photo is representative



Eaton 171379

Eaton Moeller® series SL4 Acoustic module,
24 V, continuous or pulsed tone

General specifications

PRODUCT NAME	Eaton Moeller® series SL4 Acoustic module
---------------------	---

CATALOG NUMBER	171379
-----------------------	--------

MODEL CODE	SL4-AP24
-------------------	----------

EAN	4015081679089
------------	---------------

PRODUCT LENGTH/DEPTH	43 mm
-----------------------------	-------

PRODUCT HEIGHT	72 mm
-----------------------	-------

PRODUCT WIDTH	43 mm
----------------------	-------

PRODUCT WEIGHT	0.043 kg
-----------------------	----------

CERTIFICATIONS

UL report applies to both
US and Canada
CSA-C22.2 No. 94-91
IEC/EN 60529
UL File No.: E29184
Certified by UL for use in
Canada
CSA Class No.: NKCR7
CSA-C22.2 No. 14-10
IEC/EN 60947-5-1
UL
UL 508
UL Category Control No.:
NKCR
CE



Powering Business Worldwide

Climatic environmental conditions

AMBIENT OPERATING TEMPERATURE - MAX	60 °C
-------------------------------------	-------

AMBIENT OPERATING TEMPERATURE - MIN	-30 °C
-------------------------------------	--------

CLIMATIC PROOFING	Damp heat, cyclic, to IEC 60068-2-30
	Damp heat, constant, to IEC 60068-2-78

Features & functions

COLOR	Black
-------	-------

FUNCTIONS	Continuous tone/pulse tone
-----------	----------------------------

Electrical rating

LEAKAGE CURRENT	0.003 A
-----------------	---------

RATED INSULATION VOLTAGE (UI)	250 V
-------------------------------	-------

RATED OPERATIONAL CURRENT (IE) - MAX	39 mA
--------------------------------------	-------

RATED OPERATIONAL VOLTAGE (UE) AT AC - MAX	24 V
--	------

RATED OPERATIONAL VOLTAGE (UE) AT AC - MIN	24 V
--	------

RATED OPERATIONAL VOLTAGE (UE) AT DC - MAX	24 V
--	------

RATED OPERATIONAL VOLTAGE (UE) AT DC - MIN	24 V
--	------

General information

ALARM TYPE	Pulsed tone Continuous tone Internal sound setting, 1 pole DIP 2 types of sound Tone adjustable
------------	---

CONNECTION TO SMARTWIRE-DT	No
----------------------------	----

CURRENT CONSUMPTION	0.039 A, at 24 V AC/DC
---------------------	------------------------

DEGREE OF PROTECTION	NEMA 13 IP66
----------------------	-----------------

FREQUENCY RATING	4000 Hz
------------------	---------

LOUDNESS	80 dB
----------	-------

MATERIAL	Enclosure: Polycarbonate (PC) Cap: Polycarbonate (PC)
----------	--

MOUNTING POSITION	As required Place only at the highest position on a pole
-------------------	---

OVERVOLTAGE CATEGORY	III
----------------------	-----

POLLUTION DEGREE	3
------------------	---

PRODUCT CATEGORY	SL signal towers
------------------	------------------

RADIATION ANGLE	360 °
-----------------	-------

RATED IMPULSE WITHSTAND VOLTAGE (UIMP)	4000 V AC
--	-----------

SHOCK RESISTANCE	Mechanical, According to IEC/EN 60068-2-27 15 g, Mechanical, According to IEC/EN 60068-2-27, Sinusoidal shock 11 ms
TYPE	Acoustic module
VOLTAGE TYPE	AC/DC

Resources

BROCHURES	SL4, SL7, SLC Stack light overview brochure BR047017
CATALOGUES	eaton-rmq-titan-brochure-br047004en-en-us.pdf eaton-pushbuttons-signal-towers-sensors-assortment-overview-catalog-ca047003en-en-us.pdf
DECLARATIONS OF CONFORMITY	eaton-continuous-light-module-declaration-of-conformity-uk251039en.pdf eaton-continuous-light-module-declaration-of-conformity-eu250556en.pdf
DRAWINGS	eaton-operating-sl4-acoustic-module-dimensions.eps eaton-operating-sl7-acoustic-module-symbol.eps eaton-operating-sl4-acoustic-module-3d-drawing.eps eaton-operating-sl7-acoustic-module-symbol-002.eps eaton-operating-button-sl7-base-module-symbol.eps
ECAD MODEL	ETN.SL4-AP24
INSTALLATION INSTRUCTIONS	IL047001ZU
INSTALLATION VIDEOS	Signal towers SL4 and SL7
MCAD MODEL	DA-CS-sl4 ap eaton-acoustic-modules-mcad-drawings-sl4-ap.dwg

PROJECT NAME:
PROJECT NUMBER:
PREPARED BY:
DATE:



Eaton Corporation plc Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2026 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

