

Specifications



Eaton 171424

Eaton Moeller® series SL7 Complete device, red-green, LED, 24 V, including base 100mm

General specifications

PRODUCT NAME	Eaton Moeller® series SL7 Signal tower
CATALOG NUMBER	171424
MODEL CODE	SL7-100-L-RG-24LED
EAN	4015081677566
PRODUCT LENGTH/DEPTH	73 mm
PRODUCT HEIGHT	311 mm
PRODUCT WIDTH	73 mm
PRODUCT WEIGHT	0.424 kg

CERTIFICATIONS	UL File No.: E29184 CE CSA Class No.: NKCR7 IEC/EN 60529 IEC/EN 60947-5-1 UL 508 UL report applies to both US and Canada CSA-C22.2 No. 14-10 CSA-C22.2 No. 94-91 UL UL Category Control No.: NKCR Certified by UL for use in Canada
-----------------------	---

CATALOG NOTES	The value specified for the leakage current shall apply per module.
----------------------	---

Climatic environmental conditions

AMBIENT OPERATING TEMPERATURE - MAX	60 °C
--	-------

AMBIENT OPERATING TEMPERATURE - MIN	-30 °C
--	--------

CLIMATIC PROOFING	Damp heat, constant, to IEC 60068-2-78 Damp heat, cyclic, to IEC 60068-2-30
--------------------------	--

Features & functions

COLOR	Green Red
--------------	--------------

FITTED WITH:	100 mm tube Foot
---------------------	---------------------

LIGHT MODULES	LED
----------------------	-----

NUMBER OF MODULES	2
--------------------------	---

Electrical rating

LEAKAGE CURRENT	0.003 A
------------------------	---------

RATED INSULATION VOLTAGE (UI)	250 V
--------------------------------------	-------

RATED OPERATIONAL VOLTAGE	24 V AC/DC
----------------------------------	------------

RATED OPERATIONAL VOLTAGE (UE) - MAX	24 V
---	------

RATED OPERATIONAL VOLTAGE (UE) - MIN	24 V
---	------

General information

CONNECTION TO SMARTWIRE-DT	No
-----------------------------------	----

CURRENT CONSUMPTION	0.049 - 0.054 A, at 24 V AC/DC The value specified for the current consumption at 24 V AC/DC applies to each module.
----------------------------	---

DEGREE OF PROTECTION	IP66 NEMA 4X, 13
-----------------------------	---------------------

LIFESPAN, ELECTRICAL	100,000 h
-----------------------------	-----------

LIGHT TYPE	Continuous light
-------------------	------------------

MATERIAL	Cap: Polycarbonate (PC) Enclosure: Polycarbonate (PC)
-----------------	--

MOUNTING METHOD	Standard stacklight base
------------------------	--------------------------

MOUNTING POSITION	As required
--------------------------	-------------

OVERVOLTAGE CATEGORY	III
-----------------------------	-----

POLLUTION DEGREE	3
-------------------------	---

PRODUCT CATEGORY	SL signal towers
-------------------------	------------------

RADIATION ANGLE	360 °
------------------------	-------

RATED IMPULSE WITHSTAND VOLTAGE (UIMP)	4000 V AC
---	-----------

SHOCK RESISTANCE	15 g, Mechanical, According to IEC/EN 60068-2-27, Sinusoidal shock 11 ms Mechanical, According to IEC/EN 60068-2-27
-------------------------	--

TYPE	Complete device
-------------	-----------------

VOLTAGE TYPE	AC/DC
---------------------	-------

Terminal capacities

TERMINAL CAPACITY

0.25 - 1.5 mm², flexible
with ferrule with plastic
collar
24 - 14 AWG
0.13 - 2.5 mm², solid or
flexible conductor

Resources

BROCHURES

[SL4, SL7, SLC Stack light
overview brochure
BR047017](#)

CATALOGUES

[eaton-rmq-titan-brochure-
br047004en-en-us.pdf](#)

[eaton-pushbuttons-signal-
towers-sensors-
assortment-overview-
catalog-ca047003en-en-
us.pdf](#)

DECLARATIONS OF CONFORMITY

[eaton-continuous-light-
module-declaration-of-
conformity-
eu250556en.pdf](#)

[eaton-continuous-light-
module-declaration-of-
conformity-
uk251039en.pdf](#)

DRAWINGS

[eaton-operating-sl7-
complete-device-
dimensions.eps](#)

[eaton-operating-sl7-
complete-device-3d-
drawing.eps](#)

[eaton-operating-module-
sl7-complete-device-
symbol-003.eps](#)

[eaton-operating-sl7-
continuous-light-symbol-
002.eps](#)

ECAD MODEL

[ETN.SL7-100-L-RG-24LED](#)

INSTALLATION INSTRUCTIONS

[IL047003ZU](#) [IL047004ZU](#)

INSTALLATION VIDEOS

[Signal towers SL4 and SL7](#)

MCAD MODEL

[eaton-assembled-units-
mcad-drawings-sl7-100-l-
rg-24led.dwg](#)

PROJECT NAME:
PROJECT NUMBER:
PREPARED BY:
DATE:



Eaton Corporation plc Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2026 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

