

Specifications



Photo is representative



Eaton 171429

Eaton Moeller® series SL7 Continuous light module, red, high power LED, 24 V

General specifications

PRODUCT NAME	Eaton Moeller® series SL7 Continuous light module
---------------------	---

CATALOG NUMBER	171429
-----------------------	--------

MODEL CODE	SL7-L24-R-HP
-------------------	--------------

EAN	4015081677610
------------	---------------

PRODUCT LENGTH/DEPTH	73 mm
-----------------------------	-------

PRODUCT HEIGHT	73 mm
-----------------------	-------

PRODUCT WIDTH	73 mm
----------------------	-------

PRODUCT WEIGHT	0.088 kg
-----------------------	----------

CERTIFICATIONS	CE UL Category Control No.: NKCR CSA Class No.: NKCR7 UL 508 UL File No.: E29184 UL report applies to both US and Canada Certified by UL for use in Canada IEC/EN 60947-5-1 CSA-C22.2 No. 14-10 CSA-C22.2 No. 94-91 UL IEC/EN 60529
-----------------------	--



Powering Business Worldwide

Climatic environmental conditions

AMBIENT OPERATING TEMPERATURE - MAX	60 °C
-------------------------------------	-------

AMBIENT OPERATING TEMPERATURE - MIN	-30 °C
-------------------------------------	--------

CLIMATIC PROOFING	Damp heat, cyclic, to IEC 60068-2-30
	Damp heat, constant, to IEC 60068-2-78

Features & functions

COLOR	Red
-------	-----

ENCLOSURE COLOR	Black
-----------------	-------

FUNCTIONS	Continuous light
-----------	------------------

LIGHT MODULES	High Performance LED
---------------	----------------------

NUMBER OF MODULES	Max. 5 (with standard base)
	Max. 10 (with base for mounting on both sides)

Electrical rating

LEAKAGE CURRENT	0.003 A
-----------------	---------

RATED INSULATION VOLTAGE (UI)	250 V
-------------------------------	-------

RATED OPERATIONAL VOLTAGE (UE) AT AC - MAX	26 V
--	------

RATED OPERATIONAL VOLTAGE (UE) AT AC - MIN	18 V
--	------

RATED OPERATIONAL VOLTAGE (UE) AT DC - MAX	30 V
--	------

RATED OPERATIONAL VOLTAGE (UE) AT DC - MIN	18 V
--	------

General information

CONNECTION TO SMARTWIRE-DT	No
----------------------------	----

CURRENT CONSUMPTION	50 mA at 24 V AC/DC
---------------------	---------------------

DEGREE OF PROTECTION	NEMA 13 IP66
----------------------	-----------------

LIFESPAN, ELECTRICAL	50,000 h
----------------------	----------

LIGHT TYPE	Continuous light
------------	------------------

MATERIAL	Cap: Polycarbonate (PC) Enclosure: Polycarbonate (PC)
----------	--

MOUNTING POSITION	As required
-------------------	-------------

OVERVOLTAGE CATEGORY	III
----------------------	-----

POLLUTION DEGREE	3
------------------	---

PRODUCT CATEGORY	SL signal towers
------------------	------------------

RADIATION ANGLE	360 °
-----------------	-------

RATED IMPULSE WITHSTAND VOLTAGE (UIMP)	4000 V AC
--	-----------

SHOCK RESISTANCE	Mechanical, According to IEC/EN 60068-2-27 15 g, Mechanical, According to IEC/EN 60068-2-27, Sinusoidal shock 11 ms
------------------	--

TYPE	• Continuous light module • High-performance
------	--

LED for maximum
signaling effect

VOLTAGE TYPE

AC/DC

Resources

BROCHURES

[SL4, SL7, SLC Stack light
overview brochure
BR047017](#)

CATALOGUES

[eaton-rmq-titan-brochure-
br047004en-en-us.pdf](#)
[eaton-pushbuttons-signal-
towers-sensors-
assortment-overview-
catalog-ca047003en-en-
us.pdf](#)

DECLARATIONS OF CONFORMITY

[eaton-continuous-light-
module-declaration-of-
conformity-
eu250556en.pdf](#)
[eaton-continuous-light-
module-declaration-of-
conformity-
uk251039en.pdf](#)

DRAWINGS

[eaton-operating-
dimensions-005.eps](#)
[eaton-operating-button-
symbol-009.eps](#)
[eaton-operating-sl7-
continuous-light-symbol-
003.eps](#)

ECAD MODEL

[ETN.171429.edz](#)

INSTALLATION INSTRUCTIONS

[IL047004ZU](#)

INSTALLATION VIDEOS

[Signal towers SL4 and SL7](#)

MCAD MODEL

[eaton-light-modules-
mcad-drawings-sl7-
bfl7.dwg](#)
[DA-CS-sl7_bfl7](#)

PROJECT NAME:
PROJECT NUMBER:
PREPARED BY:
DATE:



Eaton Corporation plc Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2026 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

