

# Specifications



## Eaton 171445

Eaton Moeller® series SL7 Base module; 400-mm aluminum tube and foot

### General specifications

|                             |                                                                                                                                                                                                                                                                      |
|-----------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>PRODUCT NAME</b>         | Eaton Moeller® series SL7 Base module                                                                                                                                                                                                                                |
| <b>CATALOG NUMBER</b>       | 171445                                                                                                                                                                                                                                                               |
| <b>MODEL CODE</b>           | SL7-CB-400                                                                                                                                                                                                                                                           |
| <b>EAN</b>                  | 4015081677757                                                                                                                                                                                                                                                        |
| <b>PRODUCT LENGTH/DEPTH</b> | 73 mm                                                                                                                                                                                                                                                                |
| <b>PRODUCT HEIGHT</b>       | 484 mm                                                                                                                                                                                                                                                               |
| <b>PRODUCT WIDTH</b>        | 73 mm                                                                                                                                                                                                                                                                |
| <b>PRODUCT WEIGHT</b>       | 0.41 kg                                                                                                                                                                                                                                                              |
| <b>CERTIFICATIONS</b>       | CSA-C22.2 No. 94-91<br>UL 508<br>IEC/EN 60529<br>UL report applies to both US and Canada<br>Certified by UL for use in Canada<br>CSA-C22.2 No. 14-10<br>UL File No.: E29184<br>IEC/EN 60947-5-1<br>UL<br>CE<br>UL Category Control No.: NKCR<br>CSA Class No.: NKCR7 |



Powering Business Worldwide

## Climatic environmental conditions

|                                            |                                                                                |
|--------------------------------------------|--------------------------------------------------------------------------------|
| <b>AMBIENT OPERATING TEMPERATURE - MAX</b> | 60 °C                                                                          |
| <b>AMBIENT OPERATING TEMPERATURE - MIN</b> | -30 °C                                                                         |
| <b>CLIMATIC PROOFING</b>                   | Damp heat, cyclic, to IEC 60068-2-30<br>Damp heat, constant, to IEC 60068-2-78 |

## Features & functions

|                          |                                                                                         |
|--------------------------|-----------------------------------------------------------------------------------------|
| <b>COLOR</b>             | Other                                                                                   |
| <b>FITTED WITH:</b>      | Plastic foot<br>Aluminum tube<br>Cover                                                  |
| <b>NUMBER OF MODULES</b> | Max. 5 (with standard base)<br>Max. 10 (with base for mounting on both sides)<br>Max. 5 |

## Terminal capacities

|                                                                     |                |
|---------------------------------------------------------------------|----------------|
| <b>TERMINAL CAPACITY (AWG)</b>                                      | 24 - 14        |
| <b>TERMINAL CAPACITY (FLEXIBLE WITH FERRULE AND PLASTIC COLLAR)</b> | 0.25 - 1.5 mm² |
| <b>TERMINAL CAPACITY (SOLID/FLEXIBLE)</b>                           | 0.13 - 2.5 mm² |

## Electrical rating

|                                      |                                                                 |
|--------------------------------------|-----------------------------------------------------------------|
| <b>RATED INSULATION VOLTAGE (UI)</b> | 250 V                                                           |
| <b>RATED OPERATIONAL VOLTAGE</b>     | 230/240 V AC ± 10 %<br>110/120 V AC ± 10 %<br>24 V AC/DC ± 10 % |

## General information

|                                               |                                                                                                                        |
|-----------------------------------------------|------------------------------------------------------------------------------------------------------------------------|
| <b>CONNECTION TO SMARTWIRE-DT</b>             | No                                                                                                                     |
| <b>DEGREE OF PROTECTION</b>                   | IP66<br>NEMA 4<br>NEMA 4X<br>NEMA 13                                                                                   |
| <b>MOUNTING METHOD</b>                        | Horizontal<br>Floor<br>Bracket                                                                                         |
| <b>MOUNTING POSITION</b>                      | As required                                                                                                            |
| <b>OVERVOLTAGE CATEGORY</b>                   | III                                                                                                                    |
| <b>POLLUTION DEGREE</b>                       | 3                                                                                                                      |
| <b>PRODUCT CATEGORY</b>                       | SL signal towers                                                                                                       |
| <b>RATED IMPULSE WITHSTAND VOLTAGE (UIMP)</b> | 4000 V AC                                                                                                              |
| <b>SHOCK RESISTANCE</b>                       | 15 g, Mechanical, According to IEC/EN 60068-2-27, Sinusoidal shock 11 ms<br>Mechanical, According to IEC/EN 60068-2-27 |
| <b>TUBE LENGTH</b>                            | 400 mm                                                                                                                 |
| <b>TYPE</b>                                   | Base module                                                                                                            |

## Resources

|            |                                                                                                                                                                           |
|------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| BROCHURES  | <a href="#">SL4, SL7, SLC Stack light overview brochure BR047017</a>                                                                                                      |
| CATALOGUES | <a href="#">eaton-rmq-titan-brochure-br047004en-en-us.pdf</a><br><a href="#">eaton-pushbuttons-signal-towers-sensors-assortment-overview-catalog-ca047003en-en-us.pdf</a> |

|                            |                                                                                        |
|----------------------------|----------------------------------------------------------------------------------------|
| DECLARATIONS OF CONFORMITY | <a href="#">eaton-continuous-light-module-declaration-of-conformity-eu250556en.pdf</a> |
|                            | <a href="#">eaton-continuous-light-module-declaration-of-conformity-uk251039en.pdf</a> |
| DRAWINGS                   | <a href="#">eaton-operating-sl7-base-module-dimensions-011.eps</a>                     |
|                            | <a href="#">eaton-operating-button-sl7-base-module-symbol.eps</a>                      |
|                            | <a href="#">eaton-operating-sl7-base-module-3d-drawing.eps</a>                         |
| ECAD MODEL                 | <a href="#">DA-CE-ETN.SL7-CB-400</a>                                                   |
| INSTALLATION INSTRUCTIONS  | <a href="#">IL047003ZU</a>                                                             |
| INSTALLATION VIDEOS        | <a href="#">Signal towers SL4 and SL7</a>                                              |
| MCAD MODEL                 | <a href="#">eaton-base-modules-mcad-drawings-sl7-cb-400.dwg</a>                        |
|                            | <a href="#">DA-CS-sl7_cb_400</a>                                                       |

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

DATE:



**Eaton Corporation plc** Eaton House  
30 Pembroke Road  
Dublin 4, Ireland  
Eaton.com

© 2026 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

