


Specifications



Photo is representative



Eaton 174604

Eaton DX EMC filter for frequency converter,
3-phase 520 V, 8 A

General specifications

PRODUCT NAME	Eaton DX Radio interference suppression filter - low
CATALOG NUMBER	174604
MODEL CODE	DX-EMC34-008-FS1-L
EAN	4015081710591
PRODUCT LENGTH/DEPTH	122 mm
PRODUCT HEIGHT	285 mm
PRODUCT WIDTH	70 mm
PRODUCT WEIGHT	1.3 kg
CERTIFICATIONS	EN 50178 IEC/EN 61800-3
CATALOG NOTES	low leakage current

Climatic environmental conditions

ALTITUDE

At higher altitudes observe
derating
Max. 2000 m

Connection

CONNECTION TYPE

Connection terminal, PE
stud, prefabricated cables

Design verification

10.10 TEMPERATURE RISE	The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.
10.11 SHORT-CIRCUIT RATING	Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.12 ELECTROMAGNETIC COMPATIBILITY	Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.13 MECHANICAL FUNCTION	The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.
10.2.2 CORROSION RESISTANCE	Meets the product standard's requirements.
10.2.3.1 VERIFICATION OF THERMAL STABILITY OF ENCLOSURES	Meets the product standard's requirements.
10.2.3.2 VERIFICATION OF RESISTANCE OF INSULATING MATERIALS TO NORMAL HEAT	Meets the product standard's requirements.
10.2.3.3 RESIST. OF INSUL. MAT. TO ABNORMAL HEAT/FIRE BY INTERNAL ELECT. EFFECTS	Meets the product standard's requirements.
10.2.4 RESISTANCE TO ULTRA-VIOLET (UV) RADIATION	Meets the product standard's requirements.
10.2.5 LIFTING	Does not apply, since the entire switchgear needs to be evaluated.
10.2.6 MECHANICAL IMPACT	Does not apply, since the entire switchgear needs to be evaluated.
10.2.7 INSCRIPTIONS	Meets the product standard's requirements.
10.3 DEGREE OF PROTECTION OF ASSEMBLIES	Does not apply, since the entire switchgear needs to be evaluated.
10.4 CLEARANCES AND CREEPAGE DISTANCES	Meets the product standard's requirements.
10.5 PROTECTION	Does not apply, since the

Electrical rating

**RATED OPERATIONAL
CURRENT (IE) - MAX**

8 A

AGAINST ELECTRIC SHOCK	entire switchgear needs to be evaluated.
10.6 INCORPORATION OF SWITCHING DEVICES AND COMPONENTS	Does not apply, since the entire switchgear needs to be evaluated.
10.7 INTERNAL ELECTRICAL CIRCUITS AND CONNECTIONS	Is the panel builder's responsibility.
10.8 CONNECTIONS FOR EXTERNAL CONDUCTORS	Is the panel builder's responsibility.
10.9.2 POWER-FREQUENCY ELECTRIC STRENGTH	Is the panel builder's responsibility.
10.9.3 IMPULSE WITHSTAND VOLTAGE	Is the panel builder's responsibility.
10.9.4 TESTING OF ENCLOSURES MADE OF INSULATING MATERIAL	Is the panel builder's responsibility.
RATED OPERATIONAL CURRENT FOR SPECIFIED HEAT DISSIPATION (IN)	8 A
STATIC HEAT DISSIPATION, NON-CURRENT-DEPENDENT PVS	0 W

Features & functions	
NUMBER OF PHASES	3

General information	
ACCESSORY/SPARE PART TYPE	Filter
DEGREE OF PROTECTION	IP20 IP00 IP20, when connected
PRODUCT CATEGORY	Accessories
USED WITH	DA1 DC1 DB1 DE1 DG1 DM1

Resources

CATALOGUES [eaton-drives-soft-starter-catalog-ca04020001zen-us.pdf](#)

[eaton-product-overview-for-machinery-catalogue-ca08103003zen-en-us.pdf](#)

DECLARATIONS OF CONFORMITY

[eaton-accessory-declaration-of-conformity-eu250588en.pdf](#)

[eaton-accessory-declaration-of-conformity-uk251071en.pdf](#)

DRAWINGS

[eaton-fc-options-emc-filter-dx-emc34-008-fs1-l-dimensions-8240dim-150.eps](#)

[eaton-regulating-equipment-options-dx-accessory-3d-drawing-009.eps](#)

ECAD MODEL

[DA-CE-ETN.DX-EMC34-008-FS1-L](#)

INSTALLATION INSTRUCTIONS

[IL04012017Z](#)

MCAD MODEL

[eaton-accessories-mcad-drawings-dx-emc34-008-fs1.dwg](#)

[dx_emc34_008_fs1.stp](#)

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

DATE:



Eaton Corporation plc Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2026 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

