

Specifications

Eaton 176469

Eaton CR Installation contactor, 20A, 24V
AC/DC, 2NC



General specifications

PRODUCT NAME	Eaton CR contactor
CATALOG NUMBER	176469
MODEL CODE	CR2002024
EAN	8711426209701
PRODUCT LENGTH/DEPTH	85 mm
PRODUCT HEIGHT	65 mm
PRODUCT WIDTH	17.5 mm
PRODUCT WEIGHT	0.137 kg
COMPLIANCES	RoHS conform

Additional information

FEATURES

Additional equipment
possible

Delivery programme

AMPERAGE RATING

20 A

Design verification to IEC/EN 61439

10.10 TEMPERATURE RISE	The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.
10.11 SHORT-CIRCUIT RATING	Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.12 ELECTROMAGNETIC COMPATIBILITY	Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.13 MECHANICAL FUNCTION	The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.
10.2.2 CORROSION RESISTANCE	Meets the product standard's requirements.
10.2.3.1 VERIFICATION OF THERMAL STABILITY OF ENCLOSURES	Meets the product standard's requirements.
10.2.3.2 VERIFICATION OF RESISTANCE OF INSULATING MATERIALS TO NORMAL HEAT	Meets the product standard's requirements.
10.2.3.3 RESIST. OF INSUL. MAT. TO ABNORMAL HEAT/FIRE BY INTERNAL ELECT. EFFECTS	Meets the product standard's requirements.
10.2.4 RESISTANCE TO ULTRA-VIOLET (UV) RADIATION	Meets the product standard's requirements.
10.2.5 LIFTING	Does not apply, since the entire switchgear needs to be evaluated.
10.2.6 MECHANICAL IMPACT	Does not apply, since the entire switchgear needs to be evaluated.
10.2.7 INSCRIPTIONS	Meets the product standard's requirements.
10.3 DEGREE OF PROTECTION OF ASSEMBLIES	Does not apply, since the entire switchgear needs to be evaluated.
10.4 CLEARANCES AND CREEPAGE DISTANCES	Meets the product standard's requirements.
10.5 PROTECTION	Does not apply, since the

Design verification to IEC/EN 61439 - technical data

EQUIPMENT HEAT DISSIPATION, CURRENT-DEPENDENT 2.1 W

HEAT DISSIPATION PER POLE, CURRENT-DEPENDENT 1.7 W

RATED OPERATIONAL CURRENT FOR SPECIFIED HEAT DISSIPATION (IN) 20 A

AGAINST ELECTRIC SHOCK	entire switchgear needs to be evaluated.
10.6 INCORPORATION OF SWITCHING DEVICES AND COMPONENTS	Does not apply, since the entire switchgear needs to be evaluated.
10.7 INTERNAL ELECTRICAL CIRCUITS AND CONNECTIONS	Is the panel builder's responsibility.
10.8 CONNECTIONS FOR EXTERNAL CONDUCTORS	Is the panel builder's responsibility.
10.9.2 POWER-FREQUENCY ELECTRIC STRENGTH	Is the panel builder's responsibility.
10.9.3 IMPULSE WITHSTAND VOLTAGE	Is the panel builder's responsibility.
10.9.4 TESTING OF ENCLOSURES MADE OF INSULATING MATERIAL	Is the panel builder's responsibility.

Technical data - electrical

INCANDESCENT LAMP LOAD - MAX	1950 W
LOAD FLUORESCENT LAMP - MAX	910 VA
LOAD FLUORESCENT LAMP (DUO CIRCUIT) - MAX	1160 VA
LOAD FLUORESCENT LAMP (PARALLEL COMPENSATED) - MAX	232 VA
RATED OPERATING VOLTAGE (UE) - MAX	400 V
RATED OPERATING VOLTAGE (UE) - MIN	400 V
VOLTAGE RATING (EXCITATION) - MAX	26.4 V
VOLTAGE RATING (EXCITATION) - MIN	20.4 V
VOLTAGE TYPE	AC

Resources

DECLARATIONS OF CONFORMITY	eaton-contactor-declaration-of-conformity-eu250193en.pdf
DRAWINGS	eaton-dimensions-mas-cr.jpg eaton-wiring-diagram-cr-2nc.jpg

Technical data - mechanical

BUILT-IN DEPTH	60 mm
DEGREE OF PROTECTION	IP20
NUMBER OF CONTACTS (NORMALLY CLOSED CONTACTS)	2
NUMBER OF CONTACTS (NORMALLY OPEN CONTACTS)	0
NUMBER OF MODULAR SPACINGS	1
UTILITY CATEGORY	1
UTILIZATION CATEGORY (ACCORDING TO EN IEC 60947-4-1)	AC-1

PROJECT NAME:
PROJECT NUMBER:
PREPARED BY:
DATE:



Eaton Corporation plc Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2026 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

