

Specifications



Eaton 177066

Eaton xComfort Micro/Mini LV systems Final Distribution Boards. Mini compact distribution board, 1-row 2 SU, IP20

General specifications

PRODUCT NAME	Eaton xComfort Micro/Mini mini series
CATALOG NUMBER	177066
MODEL CODE	MINI-2
EAN	4015081715091
PRODUCT LENGTH/DEPTH	66 mm
PRODUCT HEIGHT	140 mm
PRODUCT WIDTH	53 mm
PRODUCT WEIGHT	0.08 kg
COMPLIANCES	RoHS conform
CERTIFICATIONS	IEC/EN 62208

Additional information

FEATURES	EMC-version
FITTED WITH:	Basic device
FUNCTIONS	Basic device Sealable
PROTECTION CLASS	II (totally insulated)
RAL-NUMBER	9003
SPECIAL FEATURES	IP20 Protection Class II Plastic housing white (RAL 9003)
USED WITH	Basic device Installation distribution board MINI distribution board

Delivery programme

APPLICATION	Indoor (installation site)
COLOR	White Signal white (RAL 9003)
TYPE	Basic device Installation distribution board MINI distribution board

Design verification to IEC/EN 61439

10.10 TEMPERATURE RISE	The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.
10.11 SHORT-CIRCUIT RATING	Is the panel builder's responsibility.
10.12 ELECTROMAGNETIC COMPATIBILITY	Is the panel builder's responsibility.
10.13 MECHANICAL FUNCTION	Meets the product standard's requirements.
10.2.2 CORROSION RESISTANCE	Meets the product standard's requirements.
10.2.3.1 VERIFICATION OF THERMAL STABILITY OF ENCLOSURES	Meets the product standard's requirements.
10.2.3.2 VERIFICATION OF RESISTANCE OF INSULATING MATERIALS TO NORMAL HEAT	Meets the product standard's requirements.
10.2.3.3 RESIST. OF INSUL. MAT. TO ABNORMAL HEAT/FIRE BY INTERNAL ELECT. EFFECTS	650 °C; meets the product standard's requirements.
10.2.4 RESISTANCE TO ULTRA-VIOLET (UV) RADIATION	Not relevant to indoor installations.
10.2.5 LIFTING	Does not apply to enclosures without lifting aids.
10.2.6 MECHANICAL IMPACT	IK05
10.2.7 INSCRIPTIONS	Meets the product standard's requirements.
10.3 DEGREE OF PROTECTION OF ASSEMBLIES	IP20
10.4 CLEARANCES AND CREEPAGE DISTANCES	Is the panel builder's responsibility.
10.5 PROTECTION AGAINST ELECTRIC SHOCK	Protection class 2, therefore not applicable.
10.6 INCORPORATION OF SWITCHING DEVICES AND COMPONENTS	Is the panel builder's responsibility.
10.7 INTERNAL ELECTRICAL CIRCUITS AND CONNECTIONS	Is the panel builder's responsibility.
10.8 CONNECTIONS FOR	Is the panel builder's

Design verification to IEC/EN 61439 - technical data

AMBIENT OPERATING TEMPERATURE DETAILS	-5 °C - 40 °C
--	---------------

EXTERNAL CONDUCTORS	responsibility.
10.9.2 POWER-FREQUENCY ELECTRIC STRENGTH	U _i = 400 V AC
10.9.3 IMPULSE WITHSTAND VOLTAGE	2.8 kV
10.9.4 TESTING OF ENCLOSURES MADE OF INSULATING MATERIAL	Meets the product standard's requirements.

Technical data - electrical

FREQUENCY RATING OF CONTACTS	50 Hz
VOLTAGE RATING AT AC	400 V AC

Technical data - mechanical

BUILT-IN DEPTH	70 mm
CABLE ENTRY POSTION	Metric cable entries on top and bottom, side, back plate
CLOSURE TYPE	Other
COVER/DOOR MODEL	With notch
COVER/DOOR TYPE	None Other
DEGREE OF PROTECTION	IP20 IK05 (impact resistance)
ENCLOSURE MATERIAL	Plastic
INTERNAL DEPTH	60 mm
MATERIAL	ABS (plastic)
MODULE RACK TYPE	Single-rail
MOUNTING METHOD	DIN-rail Surface mounted (plaster) Surface mounting
NUMBER OF MODULE SPACE UNITS PER ROW	2
NUMBER OF ROWS	1
PROTECTIVE SHROUDING MATERIAL	Plastic
TERMINAL TYPE	Without terminals
WIDTH IN NUMBER OF MODULAR SPACINGS	2

Temperature-rise verification as per IEC 60890

HEAT DISS. AMBIENT 35°C DELTA T:20°C WALL MOUNT INDIVID. ENCL. TOP (IEC 60890)	10 W
HEAT DISS. AMBIENT 35°C DELTA T:35°C WALL MOUNT INDIVID. ENCL. TOP (IEC 60890)	12 W

Resources

BROCHURES	eaton-xcomfort-compact-distribution-boxes-brochure-br014015en-en-us.pdf
CERTIFICATION REPORTS	eaton-xcomfort-mini-micro-declaration-of-conformity-251017-en-us.pdf

DECLARATIONS OF CONFORMITY	eaton-mini-series-declaration-of-conformity-eu250253en.pdf eaton-mini-series-declaration-of-conformity-uk251465en.pdf
DRAWINGS	eaton-lighting-distribution-xcomfort-micro-mini-lv-systems-dimensions.eps

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

DATE:



Eaton Corporation plc Eaton House
 30 Pembroke Road
 Dublin 4, Ireland
 Eaton.com

© 2026 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

