

Specifications



Eaton 178772

Eaton XN-322 Analog input module, 4 analog inputs, Pt/Ni/KTY/R with 2-wire or 3-wire connection

General specifications

PRODUCT NAME	Eaton XN-322 Input module
CATALOG NUMBER	178772
MODEL CODE	XN-322-4AI-PTNI
EAN	7640130098367
PRODUCT LENGTH/DEPTH	104.2 mm
PRODUCT HEIGHT	16.8 mm
PRODUCT WIDTH	80.3 mm
PRODUCT WEIGHT	0.056 kg
CERTIFICATIONS	CE UL File No.: E135462 cULus EN 61131-2 EN 61000-6-2 EN 61000-6-4 UL508 CSA-C22.2 No. 142-M

Ambient conditions, mechanical

HEIGHT OF FALL (IEC/EN 60068-2-32) - MAX	1 m
MOUNTING POSITION	Horizontal
SHOCK RESISTANCE	15 g, Mechanical, Half-sinusoidal shock 11 ms, 18 Impacts
VIBRATION RESISTANCE	5 - 8.4 / 8.4 -150 Hz, 3,5 mm / 1 g

Communication

CONNECTION TYPE	2-conductor/3-conductor, Temperature and resistance measurement Push-in spring-cage terminal (plug-in connection), Connection design in TOP direction
PROTOCOL	Other bus systems

Climatic environmental conditions

AIR PRESSURE	795 - 1080 hPa (operation)
AMBIENT OPERATING TEMPERATURE - MAX	60 °C
AMBIENT STORAGE TEMPERATURE - MAX	85 °C
AMBIENT OPERATING TEMPERATURE - MIN	0 °C
AMBIENT STORAGE TEMPERATURE - MIN	-20 °C
CLIMATIC PROOFING	Dry heat to IEC 60068-2-2 Damp heat, constant, to IEC 60068-2-3
ENVIRONMENTAL CONDITIONS	Condensation: prevent with appropriate measures
RELATIVE HUMIDITY	0 - 95 % (non-condensing)

Design verification

10.10 TEMPERATURE RISE	The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.
10.11 SHORT-CIRCUIT RATING	Is the panel builder's responsibility.
10.12 ELECTROMAGNETIC COMPATIBILITY	Is the panel builder's responsibility.
10.13 MECHANICAL FUNCTION	The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.
10.2.2 CORROSION RESISTANCE	Meets the product standard's requirements.
10.2.3.1 VERIFICATION OF THERMAL STABILITY OF ENCLOSURES	Meets the product standard's requirements.
10.2.3.2 VERIFICATION OF RESISTANCE OF INSULATING MATERIALS TO NORMAL HEAT	Meets the product standard's requirements.
10.2.3.3 RESIST. OF INSUL. MAT. TO ABNORMAL HEAT/FIRE BY INTERNAL ELECT. EFFECTS	Meets the product standard's requirements.
10.2.4 RESISTANCE TO ULTRA-VIOLET (UV)	Meets the product standard's requirements.

RADIATION	
10.2.5 LIFTING	Does not apply, since the entire switchgear needs to be evaluated.
10.2.6 MECHANICAL IMPACT	Does not apply, since the entire switchgear needs to be evaluated.
10.2.7 INSCRIPTIONS	Meets the product standard's requirements.
10.3 DEGREE OF PROTECTION OF ASSEMBLIES	Meets the product standard's requirements.
10.4 CLEARANCES AND CREEPAGE DISTANCES	Meets the product standard's requirements.
10.5 PROTECTION AGAINST ELECTRIC SHOCK	Does not apply, since the entire switchgear needs to be evaluated.
10.6 INCORPORATION OF SWITCHING DEVICES AND COMPONENTS	Does not apply, since the entire switchgear needs to be evaluated.
10.7 INTERNAL ELECTRICAL CIRCUITS AND CONNECTIONS	Is the panel builder's responsibility.
10.8 CONNECTIONS FOR EXTERNAL CONDUCTORS	Is the panel builder's responsibility.
10.9.2 POWER-FREQUENCY ELECTRIC STRENGTH	Is the panel builder's responsibility.
10.9.3 IMPULSE WITHSTAND VOLTAGE	Is the panel builder's responsibility.
10.9.4 TESTING OF ENCLOSURES MADE OF INSULATING MATERIAL	Is the panel builder's responsibility.
EQUIPMENT HEAT DISSIPATION, CURRENT-DEPENDENT PVID	0 W
HEAT DISSIPATION CAPACITY PDISS	0 W
HEAT DISSIPATION PER POLE, CURRENT-DEPENDENT PVID	0.768 W
RATED OPERATIONAL CURRENT FOR SPECIFIED HEAT DISSIPATION (IN)	0 A
STATIC HEAT DISSIPATION, NON-CURRENT-DEPENDENT PVS	1.08 W

Electrical rating

RATED OPERATIONAL VOLTAGE	160 V (terminations)
----------------------------------	----------------------

SUPPLY VOLTAGE AT DC - MAX	30 VDC
-----------------------------------	--------

SUPPLY VOLTAGE AT DC - MIN	18 VDC
-----------------------------------	--------

Electro magnetic compatibility

AIR DISCHARGE	8 kV
----------------------	------

BURST IMPULSE	1 kV, Signal cable 2 kV, Supply cable
----------------------	--

CONTACT DISCHARGE	4 kV
--------------------------	------

ELECTROMAGNETIC FIELDS	1 V/m at 2 - 2.7 GHz (according to IEC EN 61000-4-3) 10 V/m at 0.08 - 1.0 GHz (according to IEC EN 61000-4-3) 3 V/m at 1.4 - 2 GHz (according to IEC EN 61000-4-3)
-------------------------------	---

EMITTED INTERFERENCE	47 dB (at 230 - 1000 MHz, Class A, radiated, high frequency) 40 dB (at 30 - 230 MHz, Class A, radiated, high frequency)
-----------------------------	--

RADIATED RFI	10 V
---------------------	------

SURGE RATING	0.5/0.5 kV, Supply cable, balanced/unbalanced), EMC 1 kV, Signal cable, unbalanced, EMC
---------------------	---

VOLTAGE DIPS	Voltage dips: 10 ms/Voltage fluctuations: Yes
---------------------	---

Features & functions

ELECTRIC CONNECTION TYPE

Plug-in connection

FEATURES

Input, resistance thermometer
Fieldbus connection over separate bus coupler possible
Analog outputs configurable
Input, resistor
Analog inputs configurable

Input signal, configurable
Fieldbus connection over separate bus coupler possible

FITTED WITH:

10 kHz, second-order low-pass input filter
Parameterizable Software input filter

MEASUREMENT RANGES

0 - 1000 (Resistance measurement)
0 - 2500 (Resistance measurement)
-40 - 300 °C (Temperature measurement, KTY84)
0 - 500 (Resistance measurement)
-50 - 150 °C (Temperature measurement, KTY11)
-200 - 850 °C (Temperature measurement, PT100/200/500/1000)
-60 - 250 °C (Temperature measurement, NI100/1000)
-60 - 150 °C (Temperature measurement, NI100/1000)
0 - 250 (Resistance measurement)
0 - 5000 (Resistance measurement)
-200 - 150 °C (Temperature measurement, PT100/200/500/1000)
-55 - 150 °C (Temperature measurement, KTY81)

VALUE REPRESENTATION

SIGNED16 (0.1 °C),
UNSIGNED16 (0.1 Ω),
Temperature and resistance measurement

General information

CURRENT CONSUMPTION	37 mA (typ.), for +24 V, Power supply - Input 0 mA (typ.), for +5 V power supply (internal), Power supply - Input
DEGREE OF PROTECTION	IP20 NEMA 1
MOUNTING METHOD	Rail mounting possible
NUMBER OF CHANNELS	4, Analog Inputs
OVERVOLTAGE CATEGORY	III
POLLUTION DEGREE	3
PRODUCT CATEGORY	XN-322 analog input module
RESOLUTION	16 Bit (Analog inputs)
TYPE	- Analog input module for four PT100/PT1000/Ni100/Ni1000KTYxx/R resistance inputs with 2-wire and 3-wire configurations. - XN300 I/O slice module
USED WITH	XN-312-... XN300
VOLTAGE TYPE	DC

Input/Output

ACCURACY	± 0.3 % of full scale, Temperature and resistance measurement
INPUT	4 Analog resistance inputs (Pt/Ni/KTY/R with 2-wire or 3-wire connection)
LOAD CURRENT	Not specified by plug manufacturer
MEASURED VARIABLES	Temperature Resistance
NUMBER OF INPUTS (ANALOG)	4
NUMBER OF OUTPUTS (ANALOG)	0
VALUE REFRESH TIME/CYCLE TIME	Min. 4 / 4 ms (per channel / all channels), Analog Inputs

Safety

EXPLOSION SAFETY CATEGORY FOR DUST	None
EXPLOSION SAFETY CATEGORY FOR GAS	None
POTENTIAL ISOLATION	Analog inputs: no

Terminal capacities

GAUGE PIN	A1 (according to IEC/EN 60947-1)
INSULATING MATERIAL GROUP	I
STRIPPING LENGTH (MAIN CABLE)	10 mm
TERMINAL CAPACITY	0.2 - 1.5 mm², flexible without ferrule, H07V-K 0.2 - 1.5 mm², solid, H07V-U 24 - 16 AWG 0.25 - 1.5 mm², with ferrules without plastic collar according to DIN 46228-1 (ferrules crimped gas-tight) 0.25 - 0.75 mm², with ferrules with plastic collar according to DIN 46228-1 (ferrules crimped gas-tight)

Resources

BROCHURES	Slice card modular I/O system for the machine building industry XN300 - brochure eaton-xc300-modular-plc-brochure-br050008en-en-us.pdf
DECLARATIONS OF CONFORMITY	eaton-input-module-declaration-of-conformity-uk251198en.pdf eaton-input-module-declaration-of-conformity-eu250715en.pdf
DRAWINGS	eaton-modular-plc-xn-input-module-dimensions.eps eaton-general-xv-touch-panel-symbol.eps eaton-modular-plc-xn-input-module-3d-drawing.eps eaton-modular-plc-xn-input-module-3d-drawing-006.eps
ECAD MODEL	DA-CE-ETN.XN-322-4AI-PTNI
INSTALLATION INSTRUCTIONS	IL050025ZU IL050017ZU
MANUALS AND USER GUIDES	eaton-xn-312-gw-ec-ethercat-gateway-mn050010-en-us.pdf eaton-xn300-slice-modules-mn050002-en-us.pdf eaton-xn-312-gw-can-canopen-gateway-mn050003-en-us.pdf
MCAD MODEL	eaton-modular-system-analog-mcad-3d-models-xn-322-4ai-ptni.stp eaton-modular-system-analog-mcad-drawings-xn-322-4ai-ptni.dwg
MULTIMEDIA	System solutions based on EtherCAT XC100, XC200, XC300 – Eaton's modular PLC ranges

PRODUCT NOTIFICATIONS

[eaton-xn-322-i-o-series-product-cybersecurity-guideline-mz050024-en-us.pdf](#)

[eaton-xn-322-i-o-series-end-user-license-agreement-mz050026-en-us.pdf](#)

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

DATE:



Eaton Corporation plc Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2026 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

