

Specifications



Eaton 178773

Eaton XN-322 Serial interface module, data from two SSI encoders via RS422, 32 bits / 125 kHz, 250kHz, 500kHz, 1MHz

General specifications

PRODUCT NAME	Eaton XN-322 Interface module
CATALOG NUMBER	178773
MODEL CODE	XN-322-2SSI
EAN	7640130098374
PRODUCT LENGTH/DEPTH	104.2 mm
PRODUCT HEIGHT	16.8 mm
PRODUCT WIDTH	80.3 mm
PRODUCT WEIGHT	0.046 kg
CERTIFICATIONS	UL File No.: E135462 cULus CE EN 61131-2 EN 61000-6-2 EN 61000-6-4 UL508 CSA-C22.2 No. 142-M

Ambient conditions, mechanical

HEIGHT OF FALL (IEC/EN 60068-2-32) - MAX	1 m
MOUNTING POSITION	Horizontal
SHOCK RESISTANCE	15 g, Mechanical, Half-sinusoidal shock 11 ms, 18 Impacts
VIBRATION RESISTANCE	5 - 8.4 / 8.4 -150 Hz, 3,5 mm / 1 g

Communication

BUS TERMINATION	Internal, Digital inputs, Absolute encoder
CONNECTION TYPE	RS422, Digital inputs, Absolute encoder Push-in spring-cage terminal (plug-in connection), Connection design in TOP direction
DATA TRANSFER RATE	Parameterizable, Digital inputs
PROTOCOL	Other bus systems

Climatic environmental conditions

AIR PRESSURE	795 - 1080 hPa (operation)
AMBIENT OPERATING TEMPERATURE - MAX	60 °C
AMBIENT STORAGE TEMPERATURE - MAX	85 °C
AMBIENT OPERATING TEMPERATURE - MIN	0 °C
AMBIENT STORAGE TEMPERATURE - MIN	-20 °C
CLIMATIC PROOFING	Damp heat, constant, to IEC 60068-2-3 Dry heat to IEC 60068-2-2
ENVIRONMENTAL CONDITIONS	Condensation: prevent with appropriate measures
RELATIVE HUMIDITY	0 - 95 % (non-condensing)

Design verification

10.10 TEMPERATURE RISE	The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.
10.11 SHORT-CIRCUIT RATING	Is the panel builder's responsibility.
10.12 ELECTROMAGNETIC COMPATIBILITY	Is the panel builder's responsibility.
10.13 MECHANICAL FUNCTION	The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.
10.2.2 CORROSION RESISTANCE	Meets the product standard's requirements.
10.2.3.1 VERIFICATION OF THERMAL STABILITY OF ENCLOSURES	Meets the product standard's requirements.
10.2.3.2 VERIFICATION OF RESISTANCE OF INSULATING MATERIALS TO NORMAL HEAT	Meets the product standard's requirements.
10.2.3.3 RESIST. OF INSUL. MAT. TO ABNORMAL HEAT/FIRE BY INTERNAL ELECT. EFFECTS	Meets the product standard's requirements.
10.2.4 RESISTANCE TO ULTRA-VIOLET (UV)	Meets the product standard's requirements.

RADIATION	
10.2.5 LIFTING	Does not apply, since the entire switchgear needs to be evaluated.
10.2.6 MECHANICAL IMPACT	Does not apply, since the entire switchgear needs to be evaluated.
10.2.7 INSCRIPTIONS	Meets the product standard's requirements.
10.3 DEGREE OF PROTECTION OF ASSEMBLIES	Meets the product standard's requirements.
10.4 CLEARANCES AND CREEPAGE DISTANCES	Meets the product standard's requirements.
10.5 PROTECTION AGAINST ELECTRIC SHOCK	Does not apply, since the entire switchgear needs to be evaluated.
10.6 INCORPORATION OF SWITCHING DEVICES AND COMPONENTS	Does not apply, since the entire switchgear needs to be evaluated.
10.7 INTERNAL ELECTRICAL CIRCUITS AND CONNECTIONS	Is the panel builder's responsibility.
10.8 CONNECTIONS FOR EXTERNAL CONDUCTORS	Is the panel builder's responsibility.
10.9.2 POWER-FREQUENCY ELECTRIC STRENGTH	Is the panel builder's responsibility.
10.9.3 IMPULSE WITHSTAND VOLTAGE	Is the panel builder's responsibility.
10.9.4 TESTING OF ENCLOSURES MADE OF INSULATING MATERIAL	Is the panel builder's responsibility.
EQUIPMENT HEAT DISSIPATION, CURRENT-DEPENDENT PVID	1 W
HEAT DISSIPATION CAPACITY PDISS	0 W
HEAT DISSIPATION PER POLE, CURRENT-DEPENDENT PVID	0 W
RATED OPERATIONAL CURRENT FOR SPECIFIED HEAT DISSIPATION (IN)	0 A
STATIC HEAT DISSIPATION, NON-CURRENT-DEPENDENT PVS	1.06 W

Electrical rating

RATED OPERATIONAL VOLTAGE	160 V (terminations)
----------------------------------	----------------------

SUPPLY VOLTAGE AT DC - MAX	30 V
-----------------------------------	------

SUPPLY VOLTAGE AT DC - MIN	18 V
-----------------------------------	------

Features & functions

FEATURES

Fieldbus connection over separate bus coupler possible
Fieldbus connection over separate bus coupler possible

FUNCTIONS

Binary/gray coding (Absolute encoder)

Electro magnetic compatibility

AIR DISCHARGE	8 kV
----------------------	------

BURST IMPULSE	2 kV, Supply cable 1 kV, Signal cable
----------------------	--

CONTACT DISCHARGE	4 kV
--------------------------	------

ELECTROMAGNETIC FIELDS	1 V/m at 2 - 2.7 GHz (according to IEC EN 61000-4-3) 10 V/m at 0.08 - 1.0 GHz (according to IEC EN 61000-4-3) 3 V/m at 1.4 - 2 GHz (according to IEC EN 61000-4-3)
-------------------------------	--

EMITTED INTERFERENCE	47 dB (at 230 - 1000 MHz, Class A, radiated, high frequency) 40 dB (at 30 - 230 MHz, Class A, radiated, high frequency)
-----------------------------	--

RADIATED RFI	10 V
---------------------	------

SURGE RATING	1 kV, Signal cable, unbalanced, EMC 0.5/0.5 kV, Supply cable, balanced/unbalanced), EMC
---------------------	--

VOLTAGE DIPS	Voltage dips: 10 ms/Voltage fluctuations: Yes
---------------------	---

General information

CHANNELS	2, Transmission channel CL, D, Digital inputs, Absolute encoder
-----------------	---

CURRENT CONSUMPTION	27 mA (typ.), for +24 V, Power supply - Input
----------------------------	---

DEGREE OF PROTECTION	IP20
-----------------------------	------

MOUNTING METHOD	Rail mounting possible
------------------------	------------------------

OVERVOLTAGE CATEGORY	III
-----------------------------	-----

POLLUTION DEGREE	3
-------------------------	---

RESOLUTION	32 Bit
-------------------	--------

TYPE	• XN-322 serial interface module for XN300 • XN300 technology module
-------------	--

USED WITH	XN-312-... XN300
------------------	---------------------

Input/Output

LOAD CURRENT	Not specified by plug manufacturer
---------------------	------------------------------------

Terminal capacities

GAUGE PIN	A1 (according to IEC/EN 60947-1)
------------------	----------------------------------

INSULATING MATERIAL GROUP	I
----------------------------------	---

STRIPPING LENGTH (MAIN CABLE)	10 mm
--------------------------------------	-------

TERMINAL CAPACITY	0.2 - 1.5 mm ² , flexible without ferrule, H07V-K 0.2 - 1.5 mm ² , solid, H07V-U 24 - 16 AWG 0.25 - 1.5 mm ² , with ferrules without plastic collar according to DIN 46228-1 (ferrules crimped gas-tight) 0.25 - 0.75 mm ² , with ferrules with plastic collar according to DIN 46228-1 (ferrules crimped gas-tight)
--------------------------	--

VOLTAGE TYPE

DC

Safety

EXPLOSION SAFETY CATEGORY FOR DUST	None
---	------

EXPLOSION SAFETY CATEGORY FOR GAS	None
--	------

POTENTIAL ISOLATION	Digital inputs, Absolute encoder: no
----------------------------	--------------------------------------

Resources

	eaton-xc300-modular-plc-brochure-br050008en-en-us.pdf
--	---

BROCHURES	Slice card modular I/O system for the machine building industry XN300 - brochure
-----------	--

DECLARATIONS OF CONFORMITY	eaton-interface-module-declaration-of-conformity-uk251201en.pdf eaton-interface-module-declaration-of-conformity-eu250718en.pdf
----------------------------	--

DRAWINGS	eaton-modular-plc-xn-input-module-dimensions.eps eaton-general-xv-touch-panel-symbol.eps eaton-modular-plc-xn-input-module-3d-drawing-006.eps eaton-modular-plc-xn-interface-module-3d-drawing.eps
----------	---

ECAD MODEL	DA-CE-ETN.XN-322-2SSI
------------	---------------------------------------

INSTALLATION INSTRUCTIONS	IL050025ZU IL050017ZU
---------------------------	---

MANUALS AND USER GUIDES	eaton-xn300-slice-modules-mn050002-en-us.pdf eaton-xn-312-gw-canopen-gateway-mn050003-en-us.pdf eaton-xn-312-gw-ethercat-gateway-mn050010-en-us.pdf
-------------------------	---

MCAD MODEL	eaton-communication-modules-mcad-3d-models-xn-322-2ssi.stp
	eaton-communication-modules-mcad-drawings-xn-322-2ssi.dwg
MULTIMEDIA	XC100, XC200, XC300 – Eaton's modular PLC ranges
	System solutions based on EtherCAT
PRODUCT NOTIFICATIONS	eaton-xn-322-i-o-series-product-cybersecurity-guideline-mz050024-en-us.pdf
	eaton-xn-322-i-o-series-end-user-license-agreement-mz050026-en-us.pdf

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

DATE:



Eaton Corporation plc Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2026 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

