

Specifications



Eaton 178779

Eaton XN-322 Digital relay module, 4 digital relay outputs, N/O

General specifications

PRODUCT NAME	Eaton XN-322 Relay module
CATALOG NUMBER	178779
MODEL CODE	XN-322-4DO-RNO
EAN	7640130098411
PRODUCT LENGTH/DEPTH	104.2 mm
PRODUCT HEIGHT	29.3 mm
PRODUCT WIDTH	80.3 mm
PRODUCT WEIGHT	0.118 kg
CERTIFICATIONS	UL File No.: E135462 CE cULus EN 61131-2 EN 61000-6-2 EN 61000-6-4 UL508 CSA-C22.2 No. 142-M
CATALOG NOTES	The max. heat dissipation is specified as the maximum power produced inside the device's housing.

Ambient conditions, mechanical

HEIGHT OF FALL (IEC/EN 60068-2-32) - MAX	1 m
MOUNTING POSITION	Horizontal
SHOCK RESISTANCE	15 g, Mechanical, Half-sinusoidal shock 11 ms, 18 Impacts
VIBRATION RESISTANCE	5 - 8.4 / 8.4 -150 Hz, 3,5 mm / 1 g

Communication

CONNECTION TYPE	Push-in spring-cage terminal (plug-in connection), Connection design in TOP direction
PROTOCOL	Other bus systems

Climatic environmental conditions

AIR PRESSURE	795 - 1080 hPa (operation)
AMBIENT OPERATING TEMPERATURE - MAX	60 °C
AMBIENT STORAGE TEMPERATURE - MAX	85 °C
AMBIENT OPERATING TEMPERATURE - MIN	-25 °C
AMBIENT STORAGE TEMPERATURE - MIN	-20 °C
CLIMATIC PROOFING	Dry heat to IEC 60068-2-2 Damp heat, constant, to IEC 60068-2-3
ENVIRONMENTAL CONDITIONS	Condensation: prevent with appropriate measures
RELATIVE HUMIDITY	0 - 95 % (non-condensing)

Design verification

10.10 TEMPERATURE RISE	The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.
10.11 SHORT-CIRCUIT RATING	Is the panel builder's responsibility.
10.12 ELECTROMAGNETIC COMPATIBILITY	Is the panel builder's responsibility.
10.13 MECHANICAL FUNCTION	The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.
10.2.2 CORROSION RESISTANCE	Meets the product standard's requirements.
10.2.3.1 VERIFICATION OF THERMAL STABILITY OF ENCLOSURES	Meets the product standard's requirements.
10.2.3.2 VERIFICATION OF RESISTANCE OF INSULATING MATERIALS TO NORMAL HEAT	Meets the product standard's requirements.
10.2.3.3 RESIST. OF INSUL. MAT. TO ABNORMAL HEAT/FIRE BY INTERNAL ELECT. EFFECTS	Meets the product standard's requirements.
10.2.4 RESISTANCE TO ULTRA-VIOLET (UV)	Meets the product standard's requirements.

RADIATION	
10.2.5 LIFTING	Does not apply, since the entire switchgear needs to be evaluated.
10.2.6 MECHANICAL IMPACT	Does not apply, since the entire switchgear needs to be evaluated.
10.2.7 INSCRIPTIONS	Meets the product standard's requirements.
10.3 DEGREE OF PROTECTION OF ASSEMBLIES	Meets the product standard's requirements.
10.4 CLEARANCES AND CREEPAGE DISTANCES	Meets the product standard's requirements.
10.5 PROTECTION AGAINST ELECTRIC SHOCK	Does not apply, since the entire switchgear needs to be evaluated.
10.6 INCORPORATION OF SWITCHING DEVICES AND COMPONENTS	Does not apply, since the entire switchgear needs to be evaluated.
10.7 INTERNAL ELECTRICAL CIRCUITS AND CONNECTIONS	Is the panel builder's responsibility.
10.8 CONNECTIONS FOR EXTERNAL CONDUCTORS	Is the panel builder's responsibility.
10.9.2 POWER-FREQUENCY ELECTRIC STRENGTH	Is the panel builder's responsibility.
10.9.3 IMPULSE WITHSTAND VOLTAGE	Is the panel builder's responsibility.
10.9.4 TESTING OF ENCLOSURES MADE OF INSULATING MATERIAL	Is the panel builder's responsibility.
EQUIPMENT HEAT DISSIPATION, CURRENT-DEPENDENT PVID	1.188 W
HEAT DISSIPATION CAPACITY PDISS	0 W
HEAT DISSIPATION PER POLE, CURRENT-DEPENDENT PVID	0 W
RATED OPERATIONAL CURRENT FOR SPECIFIED HEAT DISSIPATION (IN)	0 A
STATIC HEAT DISSIPATION, NON-CURRENT-DEPENDENT PVS	4.016 W

Electrical rating

RATED OPERATIONAL VOLTAGE	160 V (terminations)
----------------------------------	----------------------

SHORT-CIRCUIT PROTECTION	Yes, Short-circuit rating, Digital outputs
---------------------------------	--

SUPPLY VOLTAGE AT DC - MAX	30 VDC
-----------------------------------	--------

SUPPLY VOLTAGE AT DC - MIN	18 VDC
-----------------------------------	--------

Electro magnetic compatibility

AIR DISCHARGE	8 kV
----------------------	------

BURST IMPULSE	2 kV, Supply cable 1 kV, Signal cable
----------------------	--

CONTACT DISCHARGE	4 kV
--------------------------	------

ELECTROMAGNETIC FIELDS	10 V/m at 0.08 - 1.0 GHz (according to IEC EN 61000-4-3) 1 V/m at 2 - 2.7 GHz (according to IEC EN 61000-4-3) 3 V/m at 1.4 - 2 GHz (according to IEC EN 61000-4-3)
-------------------------------	--

EMITTED INTERFERENCE	40 dB (at 30 - 230 MHz, Class A, radiated, high frequency) 47 dB (at 230 - 1000 MHz, Class A, radiated, high frequency)
-----------------------------	--

RADIATED RFI	10 V
---------------------	------

SURGE RATING	1 kV, Signal cable, unbalanced, EMC 0.5/0.5 kV, Supply cable, balanced/unbalanced), EMC
---------------------	--

VOLTAGE DIPS	Voltage dips: 10 ms/Voltage fluctuations: Yes
---------------------	---

Features & functions

ELECTRIC CONNECTION TYPE	Plug-in connection
---------------------------------	--------------------

FEATURES	Fieldbus connection over separate bus coupler possible Fieldbus connection over separate bus coupler possible
-----------------	--

General information

CURRENT CONSUMPTION	50 mA (typ.), for +24 V, Power supply - Input 35 mA (typ.), for +5 V power supply (internal), Power supply - Input
----------------------------	---

DEGREE OF PROTECTION	IP20
-----------------------------	------

MOUNTING METHOD	Rail mounting possible
------------------------	------------------------

NUMBER OF CHANNELS	4, Digital Outputs
---------------------------	--------------------

OVERVOLTAGE CATEGORY	III
-----------------------------	-----

POLLUTION DEGREE	3
-------------------------	---

PRODUCT CATEGORY	XN-322 digital relay module
-------------------------	-----------------------------

TYPE	Digital I/O module with four relay outputs, each with an N/O for 230 V AC / 6 A or 24 V DC
-------------	--

Input/Output	
DELAY TIME	$\leq 10000 \mu s$, Digital outputs, Delay on signal change and resistive load, from Low to High signal $\leq 10000 \mu s$, Digital outputs, Delay on signal change and resistive load, from High to Low signal
LOAD CURRENT	Not specified by plug manufacturer
LOAD RESISTANCE	$> 38.3 \Omega$ (at 230 V DC) $> 4 \Omega$ (at 24 V DC)
NUMBER OF INPUTS (DIGITAL)	0
NUMBER OF OUTPUTS (DIGITAL)	4
OUTPUT	4 Digital Relay Outputs (N/O) Protective devices must be installed directly at the inductive load in order to prevent interference.
OUTPUT CURRENT	6 A
OUTPUT VOLTAGE	$< 24 V$ DC (High level, digital outputs) 24 V DC / 230V AC (digital outputs) Low level = load dependent
UTILIZATION FACTOR	100 %

	/ 6 A. • XN300 I/O slice module
USED WITH	XN300 XN-312-...
VOLTAGE TYPE	AC/DC
Safety	
EXPLOSION SAFETY CATEGORY FOR DUST	None
EXPLOSION SAFETY CATEGORY FOR GAS	None
POTENTIAL ISOLATION	Between Digital outputs: yes Power supply, Input: yes, to Relay outputs

Terminal capacities

GAUGE PIN	A1 (according to IEC/EN 60947-1)
INSULATING MATERIAL GROUP	I
STRIPPING LENGTH (MAIN CABLE)	10 mm
TERMINAL CAPACITY	0.25 - 2.5 mm², with ferrules without plastic collar according to DIN 46228-1 (ferrules crimped gas-tight) 0.25 - 2.5 mm², with ferrules with plastic collar according to DIN 46228-1 (ferrules crimped gas-tight) 24 - 12 AWG 0.2 - 2.5 mm², solid, H07V-U 0.2 - 2.5 mm², flexible without ferrule, H07V-K

Resources

BROCHURES	Slice card modular I/O system for the machine building industry XN300 - brochure eaton-xc300-modular-plc-brochure-br050008en-en-us.pdf
DECLARATIONS OF CONFORMITY	eaton-relay-module-declaration-of-conformity-uk251199en.pdf eaton-relay-module-declaration-of-conformity-eu250716en.pdf
DRAWINGS	eaton-modular-plc-xn-relay-module-dimensions.eps eaton-general-xv-touch-panel-symbol.eps
ECAD MODEL	DA-CE-ETN.XN-322-4DO-RNO
INSTALLATION INSTRUCTIONS	IL050017ZU IL050025ZU
MANUALS AND USER GUIDES	eaton-xn-312-gw-can-canopen-gateway-mn050003-en-us.pdf eaton-xn300-slice-modules-mn050002-en-us.pdf eaton-xn-312-gw-ec-ethercat-gateway-mn050010-en-us.pdf
MCAD MODEL	eaton-modular-system-digital-mcad-3d-models-xn-322-4do-rno.stp eaton-modular-system-digital-mcad-drawings-xn-322-4do-rno.dwg
MULTIMEDIA	System solutions based on EtherCAT XC100, XC200, XC300 – Eaton's modular PLC ranges
PRODUCT NOTIFICATIONS	eaton-xn-322-i-o-series-product-cybersecurity-guideline-mz050024-en-us.pdf

[eaton-xn-322-i-o-series-
end-user-license-
agreement-mz050026-en-
us.pdf](#)

SELLING POLICY AND
T&CS

[Hydraulic Warranty](#)

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

DATE:



Eaton Corporation plc Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2026 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

