

Specifications



Eaton 180792

Eaton Moeller® series M22 Contact element, Cage Clamp, Push-in, Front fixing, 1 N/O, 24 V 1.5 A, 230 V 1.5 A

General specifications

PRODUCT NAME	Eaton Moeller® series M22 contact element
CATALOG NUMBER	180792
MODEL CODE	M22-FK10
EAN	4015081759613
PRODUCT LENGTH/DEPTH	40.2 mm
PRODUCT HEIGHT	10 mm
PRODUCT WIDTH	14 mm
PRODUCT WEIGHT	0.004 kg
CERTIFICATIONS	UL UL 508 UL Category Control No.: NKCR CSA-C22.2 No. 94-91 CSA Class No.: 3211-03 CSA CSA-C22.2 No. 14-05 UL File No.: E29184 CE CSA File No.: 012528 IEC 60947-5-1 IEC/EN 60947-5

Actuator

ACTUATING FORCE - MAX	4.5 N
------------------------------	-------

Communication

CONNECTION TO SMARTWIRE-DT	No
---------------------------------------	----

Climatic environmental conditions

AMBIENT OPERATING TEMPERATURE - MAX	70 °C
--	-------

AMBIENT STORAGE TEMPERATURE - MAX	85 °C
--	-------

AMBIENT OPERATING TEMPERATURE - MIN	-25 °C
--	--------

AMBIENT STORAGE TEMPERATURE - MIN	-40 °C
--	--------

CLIMATIC PROOFING	Damp heat, cyclic, to IEC 60068-2-30 Damp heat, constant, to IEC 60068-2-78 Dry heat to IEC 60068-2-2
--------------------------	---

Contacts

FORCE FOR POSITIVE OPENING - MIN	0 N
---	-----

NUMBER OF CONTACTS (CHANGE-OVER CONTACTS)	0
--	---

NUMBER OF CONTACTS (NORMALLY CLOSED CONTACTS)	0
--	---

NUMBER OF CONTACTS (NORMALLY OPEN CONTACTS)	1
--	---

Electrical rating

RATED INSULATION VOLTAGE (UI)	250 V
--------------------------------------	-------

RATED OPERATIONAL CURRENT (IE)	2 A at AC-15, 110 V 4 A at AC-15, 60 V
---------------------------------------	---

RATED OPERATIONAL CURRENT (IE) AT AC-15, 220 V, 230 V, 240 V	1.5 A
---	-------

RATED OPERATIONAL CURRENT (IE) AT AC-15, 24 V	4 A
--	-----

RATED OPERATIONAL CURRENT (IE) AT DC-13, 110 V	0.4 A
---	-------

RATED OPERATIONAL CURRENT (IE) AT DC-13, 220 V, 230 V	0.2 A
--	-------

RATED OPERATIONAL CURRENT (IE) AT DC-13, 24 V	1.5 A
--	-------

RATED OPERATIONAL CURRENT (IE) AT DC-13, 60 V	0.8 A
--	-------

General information

DEGREE OF PROTECTION	IP20
-----------------------------	------

LIFESPAN, MECHANICAL	1,000,000 Operations (AC operated)
-----------------------------	------------------------------------

MODEL	Top mounting
--------------	--------------

OPERATING FREQUENCY	3600 Operations/h
----------------------------	-------------------

OVERVOLTAGE CATEGORY	III
-----------------------------	-----

POLLUTION DEGREE	3
-------------------------	---

RATED IMPULSE WITHSTAND VOLTAGE (UIMP)	4000 V AC
---	-----------

Short-circuit rating

SHORT-CIRCUIT PROTECTION	FAZ-B4, Contacts, Max. short-circuit protective device, Fuseless
---------------------------------	--

SHORT-CIRCUIT PROTECTION RATING	Max. 4 A gG/gL, Fuse, Contacts
--	--------------------------------

Features & functions

ELECTRIC CONNECTION TYPE	Spring clamp connection
---------------------------------	-------------------------

Mounting details

CONNECTION TYPE	Front fixing Cage Clamp Push-in clamp
------------------------	---

MOUNTING METHOD	Front fastening
------------------------	-----------------

Terminal capacities

TERMINAL CAPACITY (FLEXIBLE WITH FERRULE)	Use WAGO Variocrimp 4 crimping tool; please enquire for others 2 x (0.25 - 1) mm ²
--	--

TERMINAL CAPACITY (SOLID)	2 x (0.2 - 1.5) mm ² 2 x 1 (0.75 - 1.5) mm ² , Can be plugged without tools
----------------------------------	--

TERMINAL CAPACITY (SOLID/STRANDED AWG)	2 x (24 - 16)
---	---------------

Resources

CATALOGUES	eaton-pushbuttons-signal-towers-sensors-assortment-overview-catalog-ca047003en-en-us.pdf
CONTROL TRAVEL DIAGRAM	eaton-operating-diagram-m22-contact-element-contact-travel-diagram-002.eps
DECLARATIONS OF CONFORMITY	eaton-contact-element-declaration-of-conformity-uk260062en.pdf eaton-assembled-contact-element-and-mounting-adapter-declaration-of-conformity-eu260061en.pdf
DRAWINGS	eaton-operating-m22-contact-element-dimensions.eps eaton-operating-m22-contact-element-dimensions-003.eps eaton-operating-m22-contact-element-3d-drawing-004.eps eaton-general-standards-000Z425.jpg
ECAD MODEL	ETN.180792.edz
INSTALLATION INSTRUCTIONS	IL04716002Z
MCAD MODEL	eaton-contact-blocks-mcad-drawings-m22-fk01.dwg eaton-contact-blocks-mcad-3d-models-m22-fk10.stp DA-CS-m22_fk10
WIRING DIAGRAMS	eaton-operating-contact-m22-contact-element-wiring-diagram-002.eps

PROJECT NAME:
PROJECT NUMBER:
PREPARED BY:
DATE:



Eaton Corporation plc Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2026 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

