


Specifications



Eaton 183047

Eaton xEffect - XNH circuit protection. NH fuse-switch 3p flange connection M10 max. 150 mm², mounting plate, electronic fuse monitoring, NH1

General specifications

PRODUCT NAME	Eaton xEffect XNH device for mounting plate
CATALOG NUMBER	183047
MODEL CODE	XNH1-FCE-A250
EAN	4015081779741
PRODUCT LENGTH/DEPTH	306 mm
PRODUCT HEIGHT	148 mm
PRODUCT WIDTH	184 mm
PRODUCT WEIGHT	2.174 kg
COMPLIANCES	RoHS conform
CERTIFICATIONS	IEC/EN 60947-3



Powering Business Worldwide

Additional information

FEATURES

Electronic fuse monitoring and EMC (Electromagnetic compatibility) as of IEC 61000-4-5
Standard sealable
Electronic fuse monitoring and EMC (Electromagnetic compatibility) as of IEC 61000-4-4
Halogen free

FITTED WITH:

Connectors
Error protection

FLAMMABILITY CHARACTERISTICS (UL)

Self-extinguishing (UL 94)

SPECIAL FEATURES

- Permanent operation (rated operating mode)
- Current paths of electrolytic copper, silver-plated
- With electronic monitoring of fuse-links

SUITABLE FOR

Ground mounting
Front mounting

Delivery programme

ACTUATOR TYPE

Cover grip

COLOR

Gray

NUMBER OF POLES

Three-pole

TYPE

Fuse control - electronic

Design verification to IEC/EN 61439

10.10 TEMPERATURE RISE	The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.
10.11 SHORT-CIRCUIT RATING	Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.12 ELECTROMAGNETIC COMPATIBILITY	Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.13 MECHANICAL FUNCTION	The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.
10.2.2 CORROSION RESISTANCE	Meets the product standard's requirements.
10.2.3.1 VERIFICATION OF THERMAL STABILITY OF ENCLOSURES	Meets the product standard's requirements.
10.2.3.2 VERIFICATION OF RESISTANCE OF INSULATING MATERIALS TO NORMAL HEAT	Meets the product standard's requirements.
10.2.3.3 RESIST. OF INSUL. MAT. TO ABNORMAL HEAT/FIRE BY INTERNAL ELECT. EFFECTS	Meets the product standard's requirements.
10.2.4 RESISTANCE TO ULTRA-VIOLET (UV) RADIATION	Meets the product standard's requirements.
10.2.5 LIFTING	Does not apply, since the entire switchgear needs to be evaluated.
10.2.6 MECHANICAL IMPACT	Does not apply, since the entire switchgear needs to be evaluated.
10.2.7 INSCRIPTIONS	Meets the product standard's requirements.
10.3 DEGREE OF PROTECTION OF ASSEMBLIES	Does not apply, since the entire switchgear needs to be evaluated.
10.4 CLEARANCES AND CREEPAGE DISTANCES	Is the panel builder's responsibility.
10.5 PROTECTION	Does not apply, since the

Design verification to IEC/EN 61439 - technical data

AMBIENT OPERATING TEMPERATURE DETAILS

- Ambient temperature range: -25 °C - 70 °C
- Operating temperature range: -5 °C - 55 °C

EQUIPMENT HEAT DISSIPATION, CURRENT-DEPENDENT	16 W
HEAT DEFLECTION TEMPERATURE	125 °C
HEAT DISSIPATION AT 80% WITHOUT FUSES	10.2 W
HEAT DISSIPATION PER POLE, CURRENT-DEPENDENT	5.3 W
RATED OPERATIONAL CURRENT FOR SPECIFIED HEAT DISSIPATION (IN)	250 A
TOTAL HEAT DISSIPATION WITHOUT FUSES AT ITH	16 W

AGAINST ELECTRIC SHOCK	entire switchgear needs to be evaluated.
10.6 INCORPORATION OF SWITCHING DEVICES AND COMPONENTS	Does not apply, since the entire switchgear needs to be evaluated.
10.7 INTERNAL ELECTRICAL CIRCUITS AND CONNECTIONS	Is the panel builder's responsibility.
10.8 CONNECTIONS FOR EXTERNAL CONDUCTORS	Is the panel builder's responsibility.
10.9.2 POWER-FREQUENCY ELECTRIC STRENGTH	$U_i = 800 \text{ V AC}$
10.9.3 IMPULSE WITHSTAND VOLTAGE	Is the panel builder's responsibility.
10.9.4 TESTING OF ENCLOSURES MADE OF INSULATING MATERIAL	Is the panel builder's responsibility.

Technical data - electrical

CREEPAGE RESISTANCE	CTI 600
DIRECTION OF INCOMING SUPPLY	As required
ELECTRICAL CONNECTION TYPE OF MAIN CIRCUIT	Screw connection
ELECTRONIC FUSE MONITORING	Test button for relay + LEDs NH with live handle straps 1 NO 1 NC Self-supplied 1.5 VA 3 LEDs (F1, F2, F3) red 1 LED green > 1 kOhm/V
FREQUENCY RATING	40 Hz - 60 Hz
FREQUENCY RATING (ELECTRONIC FUSE MONITORING)	50 - 60 Hz
FREQUENCY RATING OF CONTACTS	40 Hz - 60 Hz
LIFESPAN, ELECTRICAL	200 operations
OPERATING ALTITUDE WITHOUT DERATING - MAX	2000 mm
OVERVOLTAGE CATEGORY	III II (500 V) III (230/400 V)
PERMITTED POWER LOSS PER FUSE LINK - MAX	23 W
POLLUTION DEGREE	3
POWER RATING AT AC-23, 400 V	0 kW
RATED CONDITIONAL SHORT-CIRCUIT RATING	100 kA (690 V) 120 kA (500 V)
RATED IMPULSE WITHSTAND VOLTAGE (UIMP)	8 kV
RATED INSULATION VOLTAGE (UI)	800 VAC
RATED OPERATING VOLTAGE (UE) AT AC - MAX	500 V
RATED OPERATION CURRENT (IE)	250 A
RATED OPERATIONAL CURRENT	250 A (DC-21B) 250 A (DC-22B) 250 A (AC-22B) 250 A (AC-21B)

Technical data - mechanical

ACTIVATION TYPE	Dependent manual activation
ACTUATOR POSITION	Front side
CABLE ENTRY TYPE	Other
DEGREE OF PROTECTION (FRONT SIDE)	Other
LIFESPAN, MECHANICAL	1400 operations
LOCKING FACILITY	Yes, optional
MATERIAL	Polyamide
MOUNTING METHOD	Mounting plate DIN rail
MOUNTING POSITION	Vertical or horizontal
SIZE	NH1 fuse
SUITABLE FOR FUSES	NH1
TERMINAL CAPACITY (COPPER BAND)	6 mm x 16 mm x 0.8 mm (6x) at box terminal
TERMINAL CAPACITY (COPPER BUSBAR)	Bolt diameter at flange connection: M10 Max. 37 mm cable lug width at flange connection 30 mm x 10 mm
TERMINAL CAPACITY (COPPER STRIP)	16 mm x 0.8 mm (10x) at box terminal
TERMINAL CAPACITY (STRANDED CABLE)	35 mm ² - 150 mm ² at box terminal 25 mm ² - 150 mm ² at box terminal 70 mm ² - 95 mm ² (2x) at double clamp-type terminal 10 mm ² - 150 mm ² at clamp-type terminal
CONNECTION TYPE	Flat connection
DEGREE OF PROTECTION	IP20 (operating status, XNH installed) IP2XC (contact protection, XNH installed) IP10 (handle cover open, XNH installed) IP3X

	250 A (AC-23B)
RATED SHORT-TIME WITHSTAND CURRENT (ICW)	6 kA
RATED UNINTERRUPTED CURRENT (IU)	250 A
SWITCHING CURRENT OF ELECTRONIC FUSE MONITORING - MAX	1 A
VOLTAGE INPUTS	400 V AC - 500 V AC (+/- 10%)
VOLTAGE RATING AT AC	• 400 V (AC-23B) • 500 V (AC-22B) • 690 V (AC-21B)
VOLTAGE RATING AT AC - MAX	250 VAC
VOLTAGE RATING AT DC	• 250 V (DC-22B) • 440 V (DC-21B)
VOLTAGE RATING AT DC - MAX	24 VDC
VOLTAGE TEST	Yes, sliding inspection windows
CONDITIONED RATED SHORT-CIRCUIT CURRENT IQ	120 kA
RATED CONDITIONAL SHORT-CIRCUIT CURRENT (IQ)	120 kA

Resources

BROCHURES	eaton-xeffect-xnh-fuse-switch-disconnector-brochure-br019002en-en-us.pdf
CATALOGUES	eaton-panel-building-accessories-catalog-ca008008en-en-us.pdf
CERTIFICATION REPORTS	eaton-xeffect-xnh-fuse-switch-disconnector-declaration-of-conformity-en-us.pdf
DECLARATIONS OF CONFORMITY	eaton-xnh-device-for-mounting-plate-declaration-of-conformity-eu250264en.pdf
DRAWINGS	eaton-circuit-breaker-xeffect-xeffect-xnh-circuit-protection-dimensions-006.eps
ECAD MODEL	ETN.XNH1-FCE-A250.edz
INSTALLATION INSTRUCTIONS	eaton-xeffect-xnh-fuse-switch-disconnector-il0131110z.pdf
MCAD MODEL	eaton-switch-fuse-mcad-drawings-xnh1-fce-a250.dwg eaton-XNH1-FCE-A250-3d-model.stp
WIRING DIAGRAMS	eaton-switch-xeffect-xeffect-xnh-circuit-protection-wiring-diagram.eps eaton-switch-xeffect-xeffect-xnh-circuit-protection-wiring-diagram-002.eps

PROJECT NAME:
PROJECT NUMBER:
PREPARED BY:
DATE:



Eaton Corporation plc Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2026 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

