

Specifications



Eaton 183172

Eaton XN-322 Digital input module, 8 digital inputs 24 V DC each, pulse-switching, 5.0 ms

General specifications

PRODUCT NAME	Eaton XN-322 Input module
CATALOG NUMBER	183172
MODEL CODE	XN-322-8DI-PD
EAN	4015081781058
PRODUCT LENGTH/DEPTH	104.2 mm
PRODUCT HEIGHT	16.8 mm
PRODUCT WIDTH	80.3 mm
PRODUCT WEIGHT	0.055 kg
CERTIFICATIONS	cULus CE UL File No.: E135462 EN 61131-2 EN 61000-6-2 EN 61000-6-4 UL508 CSA-C22.2 No. 142-M
CATALOG NOTES	The max. heat dissipation is specified as the maximum power produced inside the device's housing.

Ambient conditions, mechanical

HEIGHT OF FALL (IEC/EN 60068-2-32) - MAX	1 m
MOUNTING POSITION	Horizontal
SHOCK RESISTANCE	15 g, Mechanical, Half-sinusoidal shock 11 ms, 18 Impacts
VIBRATION RESISTANCE	5 - 8.4 / 8.4 -150 Hz, 3,5 mm / 1 g

Communication

CONNECTION TYPE	Push-in spring-cage terminal (plug-in connection), Connection design in TOP direction
PROTOCOL	Other bus systems

Climatic environmental conditions

AIR PRESSURE	795 - 1080 hPa (operation)
AMBIENT OPERATING TEMPERATURE - MAX	60 °C
AMBIENT STORAGE TEMPERATURE - MAX	85 °C
AMBIENT OPERATING TEMPERATURE - MIN	0 °C
AMBIENT STORAGE TEMPERATURE - MIN	-20 °C
CLIMATIC PROOFING	Damp heat, constant, to IEC 60068-2-3 Dry heat to IEC 60068-2-2
ENVIRONMENTAL CONDITIONS	Condensation: prevent with appropriate measures
RELATIVE HUMIDITY	0 - 95 % (non-condensing)

Design verification

10.10 TEMPERATURE RISE	The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.
10.11 SHORT-CIRCUIT RATING	Is the panel builder's responsibility.
10.12 ELECTROMAGNETIC COMPATIBILITY	Is the panel builder's responsibility.
10.13 MECHANICAL FUNCTION	The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.
10.2.2 CORROSION RESISTANCE	Meets the product standard's requirements.
10.2.3.1 VERIFICATION OF THERMAL STABILITY OF ENCLOSURES	Meets the product standard's requirements.
10.2.3.2 VERIFICATION OF RESISTANCE OF INSULATING MATERIALS TO NORMAL HEAT	Meets the product standard's requirements.
10.2.3.3 RESIST. OF INSUL. MAT. TO ABNORMAL HEAT/FIRE BY INTERNAL ELECT. EFFECTS	Meets the product standard's requirements.
10.2.4 RESISTANCE TO ULTRA-VIOLET (UV)	Meets the product standard's requirements.

RADIATION	
10.2.5 LIFTING	Does not apply, since the entire switchgear needs to be evaluated.
10.2.6 MECHANICAL IMPACT	Does not apply, since the entire switchgear needs to be evaluated.
10.2.7 INSCRIPTIONS	Meets the product standard's requirements.
10.3 DEGREE OF PROTECTION OF ASSEMBLIES	Meets the product standard's requirements.
10.4 CLEARANCES AND CREEPAGE DISTANCES	Meets the product standard's requirements.
10.5 PROTECTION AGAINST ELECTRIC SHOCK	Does not apply, since the entire switchgear needs to be evaluated.
10.6 INCORPORATION OF SWITCHING DEVICES AND COMPONENTS	Does not apply, since the entire switchgear needs to be evaluated.
10.7 INTERNAL ELECTRICAL CIRCUITS AND CONNECTIONS	Is the panel builder's responsibility.
10.8 CONNECTIONS FOR EXTERNAL CONDUCTORS	Is the panel builder's responsibility.
10.9.2 POWER-FREQUENCY ELECTRIC STRENGTH	Is the panel builder's responsibility.
10.9.3 IMPULSE WITHSTAND VOLTAGE	Is the panel builder's responsibility.
10.9.4 TESTING OF ENCLOSURES MADE OF INSULATING MATERIAL	Is the panel builder's responsibility.
EQUIPMENT HEAT DISSIPATION, CURRENT-DEPENDENT PVID	0.2 W
HEAT DISSIPATION CAPACITY PDISS	0 W
HEAT DISSIPATION PER POLE, CURRENT-DEPENDENT PVID	0 W
RATED OPERATIONAL CURRENT FOR SPECIFIED HEAT DISSIPATION (IN)	0 A
STATIC HEAT DISSIPATION, NON-CURRENT-DEPENDENT PVS	1.318 W

Electrical rating

RATED OPERATIONAL VOLTAGE 160 V (terminations)

SUPPLY VOLTAGE AT DC - MAX 30 VDC

SUPPLY VOLTAGE AT DC - MIN 18 VDC

Electro magnetic compatibility

AIR DISCHARGE 8 kV

BURST IMPULSE 2 kV, Supply cable
1 kV, Signal cable

CONTACT DISCHARGE 4 kV

ELECTROMAGNETIC FIELDS
1 V/m at 2 - 2.7 GHz
(according to IEC EN 61000-4-3)
10 V/m at 0.08 - 1.0 GHz
(according to IEC EN 61000-4-3)
3 V/m at 1.4 - 2 GHz
(according to IEC EN 61000-4-3)

EMITTED INTERFERENCE
47 dB (at 230 - 1000 MHz,
Class A, radiated, high
frequency)
40 dB (at 30 - 230 MHz,
Class A, radiated, high
frequency)

RADIATED RFI 10 V

SURGE RATING
1 kV, Signal cable,
unbalanced, EMC
0.5/0.5 kV, Supply cable,
balanced/unbalanced),
EMC

VOLTAGE DIPS
Voltage dips: 10
ms/Voltage fluctuations:
Yes

Features & functions

ELECTRIC CONNECTION TYPE Plug-in connection

FEATURES
Fieldbus connection over
separate bus coupler
possible
Fieldbus connection over
separate bus coupler
possible

General information

CURRENT CONSUMPTION
None mA (typ.), for +24 V,
Power supply - Input
35 mA (typ.), for +5 V
power supply (internal),
Power supply - Input

DEGREE OF PROTECTION IP20

MOUNTING METHOD Rail mounting possible

NUMBER OF CHANNELS 8

OVERVOLTAGE CATEGORY III

POLLUTION DEGREE 3

PRODUCT CATEGORY XN-322 digital input
module

TYPE
• Digital I/O module
with eight 24 V DC /
3.7 mA (EN61131-2
type 1) inputs with
a 0.5 ms input

Input/Output	
INPUT	Digital inputs (according to EN61131-2 Type 1)
INPUT CURRENT	3.7 mA (Digital inputs) ≥ 2.3 mA (Digital inputs, high level) ≤ 1.1 mA (Digital inputs, low level)
INPUT CURRENT AT SIGNAL 1	3.7 mA
INPUT DELAY	5000 μ s (falling edge) 5000 μ s (rising edge)
INPUT VOLTAGE	24 V DC (Digital inputs) 0 - 8 V (Digital inputs, low level) 14 - 30 V (Digital inputs, high level)
LOAD CURRENT	Not specified by plug manufacturer
NUMBER OF INPUTS (DIGITAL)	8
NUMBER OF OUTPUTS (DIGITAL)	0

	filter. • XN300 I/O slice module
USED WITH	XN300 XN-312-...
VOLTAGE TYPE	DC
Safety	
EXPLOSION SAFETY CATEGORY FOR DUST	None
EXPLOSION SAFETY CATEGORY FOR GAS	None
POTENTIAL ISOLATION	Between Digital inputs: no

Terminal capacities

GAUGE PIN	A1 (according to IEC/EN 60947-1)
INSULATING MATERIAL GROUP	I
STRIPPING LENGTH (MAIN CABLE)	10 mm
TERMINAL CAPACITY	24 - 16 AWG 0.2 - 1.5 mm ² , solid, H07V-U 0.2 - 1.5 mm ² , flexible without ferrule, H07V-K 0.25 - 1.5 mm ² , with ferrules without plastic collar according to DIN 46228-1 (ferrules crimped gas-tight) 0.25 - 0.75 mm ² , with ferrules with plastic collar according to DIN 46228-1 (ferrules crimped gas-tight)

Resources

BROCHURES	Slice card modular I/O system for the machine building industry XN300 - brochure eaton-xc300-modular-plc-brochure-br050008en-en-us.pdf
DECLARATIONS OF CONFORMITY	eaton-input-module-declaration-of-conformity-eu250715en.pdf eaton-input-module-declaration-of-conformity-uk251198en.pdf
DRAWINGS	eaton-modular-plc-xn-input-module-dimensions.eps eaton-modular-plc-xn-input-module-3d-drawing-006.eps eaton-general-xv-touch-panel-symbol.eps
ECAD MODEL	DA-CE-ETN.XN-322-8DI-PD
INSTALLATION INSTRUCTIONS	IL050025ZU IL050017ZU
MANUALS AND USER GUIDES	eaton-xn300-slice-modules-mn050002-en-us.pdf eaton-xn-312-gw-can-canopen-gateway-mn050003-en-us.pdf eaton-xn-312-gw-ec-ethernet-gateway-mn050010-en-us.pdf
MCAD MODEL	eaton-communication-modules-mcad-3d-models-xn-322-2ssi.stp eaton-communication-modules-mcad-drawings-xn-322-2ssi.dwg
MULTIMEDIA	System solutions based on EtherCAT XC100, XC200, XC300 – Eaton's modular PLC ranges
PRODUCT NOTIFICATIONS	eaton-xn-322-i-o-series-product-cybersecurity-guideline-mz050024-en-us.pdf

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

DATE:



Eaton Corporation plc Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2026 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

