

Specifications



Eaton 183182

Eaton XN-322 Analog I/O module, 2 analog inputs and 2 analog outputs, 0/4 to 20 mA

General specifications

PRODUCT NAME	Eaton XN-322 I/O module
CATALOG NUMBER	183182
MODEL CODE	XN-322-4AIO-I
EAN	4015081781157
PRODUCT LENGTH/DEPTH	104.2 mm
PRODUCT HEIGHT	16.8 mm
PRODUCT WIDTH	80.3 mm
PRODUCT WEIGHT	0.055 kg
CERTIFICATIONS	cULus UL File No.: E135462 CE EN 61131-2 EN 61000-6-2 EN 61000-6-4 UL508 CSA-C22.2 No. 142-M
CATALOG NOTES	The max. heat dissipation is specified as the maximum power produced inside the device's housing.

Ambient conditions, mechanical

HEIGHT OF FALL (IEC/EN 60068-2-32) - MAX	1 m
MOUNTING POSITION	Horizontal
SHOCK RESISTANCE	15 g, Mechanical, Half-sinusoidal shock 11 ms, 18 Impacts
VIBRATION RESISTANCE	5 - 8.4 / 8.4 -150 Hz, 3,5 mm / 1 g

Communication

CONNECTION TYPE	Push-in spring-cage terminal (plug-in connection), Connection design in TOP direction 2 conductors, Analog outputs, Output current 2 conductors, Current measurement
PROTOCOL	Other bus systems

Climatic environmental conditions

AIR PRESSURE	795 - 1080 hPa (operation)
AMBIENT OPERATING TEMPERATURE - MAX	60 °C
AMBIENT STORAGE TEMPERATURE - MAX	85 °C
AMBIENT OPERATING TEMPERATURE - MIN	0 °C
AMBIENT STORAGE TEMPERATURE - MIN	-20 °C
CLIMATIC PROOFING	Dry heat to IEC 60068-2-2 Damp heat, constant, to IEC 60068-2-3
ENVIRONMENTAL CONDITIONS	Condensation: prevent with appropriate measures
RELATIVE HUMIDITY	0 - 95 % (non-condensing)

Design verification

10.10 TEMPERATURE RISE	The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.
10.11 SHORT-CIRCUIT RATING	Is the panel builder's responsibility.
10.12 ELECTROMAGNETIC COMPATIBILITY	Is the panel builder's responsibility.
10.13 MECHANICAL FUNCTION	The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.
10.2.2 CORROSION RESISTANCE	Meets the product standard's requirements.
10.2.3.1 VERIFICATION OF THERMAL STABILITY OF ENCLOSURES	Meets the product standard's requirements.
10.2.3.2 VERIFICATION OF RESISTANCE OF INSULATING MATERIALS TO NORMAL HEAT	Meets the product standard's requirements.
10.2.3.3 RESIST. OF INSUL. MAT. TO ABNORMAL HEAT/FIRE BY INTERNAL ELECT. EFFECTS	Meets the product standard's requirements.
10.2.4 RESISTANCE TO ULTRA-VIOLET (UV)	Meets the product standard's requirements.

RADIATION	
10.2.5 LIFTING	Does not apply, since the entire switchgear needs to be evaluated.
10.2.6 MECHANICAL IMPACT	Does not apply, since the entire switchgear needs to be evaluated.
10.2.7 INSCRIPTIONS	Meets the product standard's requirements.
10.3 DEGREE OF PROTECTION OF ASSEMBLIES	Meets the product standard's requirements.
10.4 CLEARANCES AND CREEPAGE DISTANCES	Meets the product standard's requirements.
10.5 PROTECTION AGAINST ELECTRIC SHOCK	Does not apply, since the entire switchgear needs to be evaluated.
10.6 INCORPORATION OF SWITCHING DEVICES AND COMPONENTS	Does not apply, since the entire switchgear needs to be evaluated.
10.7 INTERNAL ELECTRICAL CIRCUITS AND CONNECTIONS	Is the panel builder's responsibility.
10.8 CONNECTIONS FOR EXTERNAL CONDUCTORS	Is the panel builder's responsibility.
10.9.2 POWER-FREQUENCY ELECTRIC STRENGTH	Is the panel builder's responsibility.
10.9.3 IMPULSE WITHSTAND VOLTAGE	Is the panel builder's responsibility.
10.9.4 TESTING OF ENCLOSURES MADE OF INSULATING MATERIAL	Is the panel builder's responsibility.
EQUIPMENT HEAT DISSIPATION, CURRENT-DEPENDENT PVID	0 W
HEAT DISSIPATION CAPACITY PDISS	0 W
HEAT DISSIPATION PER POLE, CURRENT-DEPENDENT PVID	0.851 W
RATED OPERATIONAL CURRENT FOR SPECIFIED HEAT DISSIPATION (IN)	0 A
STATIC HEAT DISSIPATION, NON-CURRENT-DEPENDENT PVS	1.85 W

Electrical rating

RATED OPERATIONAL CURRENT (IE)	0.051 A (supply input)
RATED OPERATIONAL VOLTAGE	160 V (terminations) 24 V (X5)
SHORT-CIRCUIT PROTECTION	Yes, Short-circuit strength, Analog outputs
SUPPLY VOLTAGE AT DC - MAX	30 VDC
SUPPLY VOLTAGE AT DC - MIN	18 VDC

Electro magnetic compatibility

AIR DISCHARGE	8 kV
BURST IMPULSE	2 kV, Supply cable 1 kV, Signal cable
CONTACT DISCHARGE	4 kV
ELECTROMAGNETIC FIELDS	1 V/m at 2 - 2.7 GHz (according to IEC EN 61000-4-3) 10 V/m at 0.08 - 1.0 GHz (according to IEC EN 61000-4-3) 3 V/m at 1.4 - 2 GHz (according to IEC EN 61000-4-3)
EMITTED INTERFERENCE	40 dB (at 30 - 230 MHz, Class A, radiated, high frequency) 47 dB (at 230 - 1000 MHz, Class A, radiated, high frequency)
RADIATED RFI	10 V
SURGE RATING	0.5/0.5 kV, Supply cable, balanced/unbalanced), EMC 1 kV, Signal cable, unbalanced, EMC
VOLTAGE DIPS	Voltage dips: 10 ms/Voltage fluctuations: Yes

Features & functions

CURRENT MEASUREMENT 50 Ω typ., input resistance
0 - 20 mA

ELECTRIC CONNECTION TYPE Plug-in connection

FEATURES Input, current
Analog outputs configurable
Output, current
Analog inputs configurable

Fieldbus connection over separate bus coupler possible
Input signal, configurable
Fieldbus connection over separate bus coupler possible

FITTED WITH: 1 kHz, third-order low-pass input filter
Parameterizable Software input filter

VALUE REPRESENTATION SIGNED16, Current measurement

General information

CURRENT CONSUMPTION 55 mA (typ.), for +5 V power supply (internal), Power supply - Input
None mA (typ.), for +24 V, Power supply - Input

DEGREE OF PROTECTION IP20
NEMA 1

LIMIT FREQUENCY 1 kHz (third-order low-pass filter)

MOUNTING METHOD Rail mounting possible

NUMBER OF CHANNELS 2, Analog Inputs

OVERVOLTAGE CATEGORY III

POLLUTION DEGREE 3

PRODUCT CATEGORY XN-322 analog input and output module

RESOLUTION

- 12 Bit (Analog outputs)
- 16 Bit (Analog inputs)

TYPE

- Analog mixed module with 2 analog outputs 0/4 to 20 mA (12 bit) and 2 analog inputs 0/4 to 20 mA (16 bit).
- XN300 I/O slice module

USED WITH XN300
XN-312-...

VOLTAGE TYPE DC

Input/Output

ACCURACY	± 0.5 % of full scale, Analog outputs ± 0.5 % of full scale, Current measurement
INPUT	2 Analog inputs (0/4 - 20 mA)
INPUT CURRENT	Max. 100 mA
LOAD CURRENT	Not specified by plug manufacturer
MEASURED VARIABLES	Current
NUMBER OF INPUTS (ANALOG)	2
NUMBER OF OUTPUTS (ANALOG)	2
OUTPUT	2 Analog Outputs (0/4 - 20 mA)
OUTPUT CURRENT	0 - 20 mA, Analog outputs
REFRESH TIME	1 ms (analog inputs, all channels)
RESISTIVE LOAD	≤ 500 Ω, analog outputs
VALUE REFRESH TIME/CYCLE TIME	Min. 1 / 1 ms (per channel / all channels), Analog Inputs

Terminal capacities

GAUGE PIN	A1 (according to IEC/EN 60947-1)
INSULATING MATERIAL GROUP	I
STRIPPING LENGTH (MAIN CABLE)	10 mm
TERMINAL CAPACITY	0.25 - 1.5 mm², with ferrules without plastic collar according to DIN 46228-1 (ferrules crimped gas-tight) 0.2 - 1.5 mm², solid, H07V-U 24 - 16 AWG 0.2 - 1.5 mm², flexible without ferrule, H07V-K 0.25 - 0.75 mm², with ferrules with plastic collar according to DIN 46228-1 (ferrules crimped gas-tight)

Safety

EXPLOSION SAFETY CATEGORY FOR DUST	None
EXPLOSION SAFETY CATEGORY FOR GAS	None
POTENTIAL ISOLATION	Analog inputs: no Power supply, Input: no

Resources

BROCHURES	eaton-xc300-modular-plc-brochure-br050008en-en-us.pdf Slice card modular I/O system for the machine building industry XN300 - brochure
DECLARATIONS OF CONFORMITY	eaton-input-module-declaration-of-conformity-eu250715en.pdf eaton-input-module-declaration-of-conformity-uk251198en.pdf
DRAWINGS	eaton-modular-plc-xn-input-module-dimensions.eps eaton-modular-plc-xn-input-module-3d-drawing-006.eps eaton-general-xv-touch-panel-symbol.eps
ECAD MODEL	DA-CE-ETN.XN-322-4AIO-I

INSTALLATION INSTRUCTIONS	IL050025ZU IL050017ZU
MANUALS AND USER GUIDES	eaton-xn-312-gw-can-canopen-gateway-mn050003-en-us.pdf eaton-xn-312-gw-ec-ethercat-gateway-mn050010-en-us.pdf eaton-xn300-slice-modules-mn050002-en-us.pdf
MCAD MODEL	eaton-modular-system-analog-mcad-3d-models-xn-322-1dcd-b35.stp eaton-modular-system-analog-mcad-drawings-xn-322-1dcd-b35.dwg
MULTIMEDIA	XC100, XC200, XC300 – Eaton's modular PLC ranges System solutions based on EtherCAT
PRODUCT NOTIFICATIONS	eaton-xn-322-i-o-series-end-user-license-agreement-mz050026-en-us.pdf eaton-xn-322-i-o-series-product-cybersecurity-guideline-mz050024-en-us.pdf

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

DATE:



Eaton Corporation plc Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2026 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

