

Specifications



Eaton 183283

Eaton Moeller® series M30 Indicator light, RMQ-Titan, Flat, green, Metal bezel

General specifications

PRODUCT NAME	Eaton Moeller® series M30 indicator light
CATALOG NUMBER	183283
MODEL CODE	M30C-FL-G
EAN	4015081782246
PRODUCT LENGTH/DEPTH	36 mm
PRODUCT HEIGHT	32 mm
PRODUCT WIDTH	46 mm
PRODUCT WEIGHT	0.035 kg
CERTIFICATIONS	IEC/EN 60947 VDE 0660

Actuator

BEZEL COLOR	Chrome
-------------	--------

BEZEL MATERIAL	Metal
----------------	-------

DESIGN	Flat
--------	------

FITTED WITH:	Front ring
--------------	------------

LENS COLOR	Green
------------	-------

LENS TYPE	Flat Round
-----------	---------------

Communication

CONNECTION TO SMARTWIRE-DT	Yes With SWD-RMQ connections
-------------------------------	------------------------------------

General information

DEGREE OF PROTECTION	NEMA 4X, 13
----------------------	-------------

DEGREE OF PROTECTION (FRONT SIDE)	IP67/IP69K
--------------------------------------	------------

MOUNTING POSITION	As required
-------------------	-------------

OPENING DIAMETER	30 mm
------------------	-------

OVERVOLTAGE CATEGORY	III
-------------------------	-----

POLLUTION DEGREE	3
------------------	---

PRODUCT CATEGORY	RMQ-Titan
------------------	-----------

RATED IMPULSE WITHSTAND VOLTAGE (UIMP)	4000 V AC
--	-----------

SIZE	Front dimensions: Ø 36 mm
------	------------------------------

TYPE	Indicator lights
------	------------------

Climatic environmental conditions

AMBIENT OPERATING TEMPERATURE - MAX	70 °C
--	-------

AMBIENT OPERATING TEMPERATURE - MIN	-25 °C
--	--------

CLIMATIC PROOFING	Damp heat, constant, to IEC 60068-2-78 Damp heat, cyclic, to IEC 60068-2-30
-------------------	--

Electrical rating

RATED INSULATION VOLTAGE (UI)	250 V
----------------------------------	-------

Terminal capacities

TERMINAL CAPACITY	0.5 - 1.5 mm ² , stranded 0.5 - 1.5 mm ² , solid
-------------------	---

Resources

CATALOGUES	eaton-pushbuttons-signal-towers-sensors-assortment-overview-catalog-ca047003en-en-us.pdf
DECLARATIONS OF CONFORMITY	eaton-illuminated-pushbutton-declaration-of-conformity-eu251546en.pdf
DRAWINGS	eaton-operating-m30-dimensions-004.eps
	eaton-operating-m30-dimensions-005.eps
	eaton-operating-m30-indicator-light-dimensions.eps
	eaton-operating-m30-dimensions-006.eps
	eaton-operating-m30-indicator-light-3d-drawing.eps
	eaton-general-m22-symbol.eps
ECAD MODEL	eaton-general-approval-m22-symbol.eps
	eaton-operating-button-symbol-004.eps
	ETN.183283.edz
INSTALLATION INSTRUCTIONS	eaton-operating-devices-m30-rmq-titan-flat-front-instruction-leaflet-il047019zu.pdf
MCAD MODEL	DA-CS-leuchtmelder flach flatfront
	eaton-indicating-lights-mcad-drawings-flach-flatfront.dwg

PROJECT NAME:
PROJECT NUMBER:
PREPARED BY:
DATE:



Eaton Corporation plc Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2026 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

