

Specifications



Photo is representative

Eaton 187133

Eaton Moeller® series M30 Illuminated selector switch actuator, RMQ-Titan, With thumb-grip, maintained, 3 positions, red, Metal bezel

General specifications

PRODUCT NAME	Eaton Moeller® series M30 illuminated selector switch
---------------------	---

CATALOG NUMBER	187133
-----------------------	--------

MODEL CODE	M30C-FWRLK3-R
-------------------	---------------

EAN	4015081821815
------------	---------------

PRODUCT LENGTH/DEPTH	36 mm
-----------------------------	-------

PRODUCT HEIGHT	47 mm
-----------------------	-------

PRODUCT WIDTH	46 mm
----------------------	-------

PRODUCT WEIGHT	0.042 kg
-----------------------	----------

CERTIFICATIONS	VDE 0660 IEC/EN 60947 CSA file No. 012528 CSA Class No.: 3211-03 DNV UL File No.: E29184 GL IEC/EN 60947-5 UL 508 CSA-C22.2 No. 14-05 CSA-C22.2 No. 94-91 CE marking UL Category Control No.: NKCR UL Listed CSA certified
-----------------------	--



Powering Business Worldwide

Actuator

ACTUATOR COLOR	Red
ACTUATOR FUNCTION	Switching function latching Maintained
ACTUATOR TYPE	Toggle
BEZEL COLOR	Titanium
BEZEL MATERIAL	Metal
DESIGN	With thumb-grip Flat front
FITTED WITH:	Front ring
FUNCTIONS	Stay-put/spring-return function, can be changed with coding parts M22-XC- Y
INDICATOR COLOR	Red
LENS TYPE	Round
NUMBER OF SWITCH POSITIONS	3

Communication

CONNECTION TO SMARTWIRE-DT	With SWD-RMQ connections Yes
---------------------------------------	------------------------------------

Climatic environmental conditions

AMBIENT OPERATING TEMPERATURE - MAX	70 °C
AMBIENT OPERATING TEMPERATURE - MIN	-25 °C
CLIMATIC PROOFING	Damp heat, cyclic, to IEC 60068-2-30 Damp heat, constant, to IEC 60068-2-78

Design verification

10.10 TEMPERATURE RISE	Not applicable.
10.11 SHORT-CIRCUIT RATING	Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.12 ELECTROMAGNETIC COMPATIBILITY	Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.13 MECHANICAL FUNCTION	The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.
10.2.2 CORROSION RESISTANCE	Meets the product standard's requirements.
10.2.3.1 VERIFICATION OF THERMAL STABILITY OF ENCLOSURES	Meets the product standard's requirements.
10.2.3.2 VERIFICATION OF RESISTANCE OF INSULATING MATERIALS TO NORMAL HEAT	Meets the product standard's requirements.
10.2.3.3 RESIST. OF INSUL. MAT. TO ABNORMAL HEAT/FIRE	Meets the product standard's requirements.

BY INTERNAL ELECT. EFFECTS	
10.2.4 RESISTANCE TO ULTRA-VIOLET (UV) RADIATION	Please enquire
10.2.5 LIFTING	Does not apply, since the entire switchgear needs to be evaluated.
10.2.6 MECHANICAL IMPACT	Does not apply, since the entire switchgear needs to be evaluated.
10.2.7 INSCRIPTIONS	Meets the product standard's requirements.
10.3 DEGREE OF PROTECTION OF ASSEMBLIES	Does not apply, since the entire switchgear needs to be evaluated.
10.4 CLEARANCES AND CREEPAGE DISTANCES	Meets the product standard's requirements.
10.5 PROTECTION AGAINST ELECTRIC SHOCK	Does not apply, since the entire switchgear needs to be evaluated.
10.6 INCORPORATION OF SWITCHING DEVICES AND COMPONENTS	Does not apply, since the entire switchgear needs to be evaluated.
10.7 INTERNAL ELECTRICAL CIRCUITS AND CONNECTIONS	Is the panel builder's responsibility.
10.8 CONNECTIONS FOR EXTERNAL CONDUCTORS	Is the panel builder's responsibility.
10.9.2 POWER-FREQUENCY ELECTRIC STRENGTH	Is the panel builder's responsibility.
10.9.3 IMPULSE WITHSTAND VOLTAGE	Is the panel builder's responsibility.
10.9.4 TESTING OF ENCLOSURES MADE OF INSULATING MATERIAL	Is the panel builder's responsibility.
EQUIPMENT HEAT DISSIPATION, CURRENT-DEPENDENT PVID	0 W
HEAT DISSIPATION CAPACITY PDISS	0 W
HEAT DISSIPATION PER POLE, CURRENT-DEPENDENT PVID	0 W
RATED OPERATIONAL CURRENT FOR SPECIFIED HEAT DISSIPATION (IN)	0 A
STATIC HEAT DISSIPATION, NON-CURRENT-DEPENDENT PVS	0 W

General information

DEGREE OF PROTECTION	NEMA 4X, 13
DEGREE OF PROTECTION (FRONT SIDE)	IP66
LIFESPAN, MECHANICAL	100,000 Operations
MOUNTING POSITION	As required
OPENING DIAMETER	30 mm
OPERATING FREQUENCY	2000 Operations/h
OPERATING TORQUE	0.3 Nm
OVERVOLTAGE CATEGORY	III
POLLUTION DEGREE	3
PRODUCT CATEGORY	RMQ-Titan
SIZE	Front dimensions: Ø 36 mm
SUITABLE FOR	Illumination
SWITCHING ANGLE	60 °
TYPE	Illuminated selector switch actuator

Resources

CATALOGUES	eaton-pushbuttons-signal-towers-sensors-assortment-overview-catalog-ca047003en-en-us.pdf
DECLARATIONS OF CONFORMITY	eaton-illuminated-pushbutton-declaration-of-conformity-eu251546en.pdf
	eaton-operating-m30-dimensions-005.eps
	eaton-operating-m30-dimensions-004.eps
	eaton-operating-m30-dimensions-006.eps
	eaton-operating-m30-dimensions-002.eps
DRAWINGS	eaton-general-m22-symbol.eps
	eaton-operating-3d-drawing-008.eps
	eaton-operating-button-symbol-006.eps
	eaton-general-approval-m22-symbol.eps
ECAD MODEL	ETN.187133.edz
INSTALLATION INSTRUCTIONS	eaton-operating-devices-m30-rmq-titan-flat-front-instruction-leaflet-il047019zu.pdf
MCAD MODEL	DA-CS-wahltaste knebel flatfront eaton-switches-mcad-drawings-wahltaste-knebel-flatfront.dwg

PROJECT NAME:
PROJECT NUMBER:
PREPARED BY:
DATE:



Eaton Corporation plc Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2026 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

