

# Specifications

## Eaton 187873



Eaton xEnergy Basic LV systems Low voltage switchgear. Terminal support rail incl. 2x KL29, for housing width 600mm

### General specifications

|                             |                                     |
|-----------------------------|-------------------------------------|
| <b>PRODUCT NAME</b>         | Eaton xEnergy Basic other accessory |
| <b>CATALOG NUMBER</b>       | 187873                              |
| <b>MODEL CODE</b>           | BPZ-TSB-600/2KL29                   |
| <b>EAN</b>                  | 4015081855582                       |
| <b>PRODUCT LENGTH/DEPTH</b> | 60 mm                               |
| <b>PRODUCT HEIGHT</b>       | 51 mm                               |
| <b>PRODUCT WIDTH</b>        | 530 mm                              |
| <b>PRODUCT WEIGHT</b>       | 0.7 kg                              |
| <b>COMPLIANCES</b>          | RoHS conform                        |

## Additional information

|                  |                      |
|------------------|----------------------|
| <b>FUNCTIONS</b> | Additional equipment |
|------------------|----------------------|

## Technical data - mechanical

|                                  |       |
|----------------------------------|-------|
| <b>CLEARANCE FROM BACK PLATE</b> | 50 mm |
|----------------------------------|-------|

|                                             |       |
|---------------------------------------------|-------|
| <b>CONNECTION SIZE, CONNECTION FACILITY</b> | Other |
|---------------------------------------------|-------|

|                         |                      |
|-------------------------|----------------------|
| <b>HOUSING MATERIAL</b> | Brass<br>Sheet steel |
|-------------------------|----------------------|

|                 |       |
|-----------------|-------|
| <b>MATERIAL</b> | Brass |
|-----------------|-------|

|                        |                                                                                        |
|------------------------|----------------------------------------------------------------------------------------|
| <b>MOUNTING METHOD</b> | Direct mounting<br>Floor standing distribution board<br>Surface mounting<br>Horizontal |
|------------------------|----------------------------------------------------------------------------------------|

|                          |            |
|--------------------------|------------|
| <b>MOUNTING POSITION</b> | Horizontal |
|--------------------------|------------|

|                              |    |
|------------------------------|----|
| <b>NUMBER OF CONNECTIONS</b> | 58 |
|------------------------------|----|

|                    |        |
|--------------------|--------|
| <b>RAIL LENGTH</b> | 436 mm |
|--------------------|--------|

|                           |        |
|---------------------------|--------|
| <b>SUITABLE FOR WIDTH</b> | 600 mm |
|---------------------------|--------|

|                          |            |
|--------------------------|------------|
| <b>SURFACE FINISHING</b> | Galvanized |
|--------------------------|------------|

|                                    |           |
|------------------------------------|-----------|
| <b>SURFACE OF THE CONTACT RAIL</b> | Untreated |
|------------------------------------|-----------|

|                  |      |
|------------------|------|
| <b>THICKNESS</b> | 8 mm |
|------------------|------|

## Delivery programme

|                        |      |
|------------------------|------|
| <b>AMPERAGE RATING</b> | 63 A |
|------------------------|------|

|                        |             |
|------------------------|-------------|
| <b>NUMBER OF POLES</b> | Single-pole |
|------------------------|-------------|

|             |                      |
|-------------|----------------------|
| <b>TYPE</b> | Additional equipment |
|-------------|----------------------|

## Resources

|           |                                                                       |
|-----------|-----------------------------------------------------------------------|
| BROCHURES | <a href="#">eaton-xenergy-basic-light-brochure-br014024-en-us.pdf</a> |
|-----------|-----------------------------------------------------------------------|

|            |                                                                                      |
|------------|--------------------------------------------------------------------------------------|
| CATALOGUES | <a href="#">eaton-distribution-boards-xenergy-basic-catalog-ca014010en-en-us.pdf</a> |
|------------|--------------------------------------------------------------------------------------|

|        |                                                                          |
|--------|--------------------------------------------------------------------------|
| FLYERS | <a href="#">eaton-xenergy-basic-profisnap-flyer-fl019008en-en-us.pdf</a> |
|--------|--------------------------------------------------------------------------|

|             |                                                             |
|-------------|-------------------------------------------------------------|
| SALES NOTES | <a href="#">eaton-f3a-flange-flyer-fl019005en-en-us.pdf</a> |
|-------------|-------------------------------------------------------------|

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

DATE:



**Eaton Corporation plc** Eaton House  
30 Pembroke Road  
Dublin 4, Ireland  
Eaton.com

© 2026 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

