

Specifications



Photo is representative



Eaton 189822

Eaton Moeller series NZM Power supply module for NZM2, 24 VDC

General specifications

PRODUCT NAME	Eaton Moeller series NZM electronic accessory
CATALOG NUMBER	189822
MODEL CODE	NZM2-XPS24DC
EAN	4015081878178
PRODUCT LENGTH/DEPTH	76 mm
PRODUCT HEIGHT	65 mm
PRODUCT WIDTH	68 mm
PRODUCT WEIGHT	0.021 kg
COMPLIANCES	IEC UL/CSA RoHS conform



Powering Business Worldwide

Delivery programme

ACCESSORY/SPARE PART TYPE	Other Power supply module Accessory
FRAME	NZM2
SPECIAL FEATURES	• 24 V DC supply to the electronic trip. • Mechanical pass-through of the switch's status (I, O) for use by the remote operator.
TYPE	Power supply module
USED WITH	NZM2(-4)-VX(MX)...

Design verification to IEC/EN 61439

10.10 TEMPERATURE RISE	The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.
10.11 SHORT-CIRCUIT RATING	Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.12 ELECTROMAGNETIC COMPATIBILITY	Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.13 MECHANICAL FUNCTION	The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.
10.2.2 CORROSION RESISTANCE	Meets the product standard's requirements.
10.2.3.1 VERIFICATION OF THERMAL STABILITY OF ENCLOSURES	Meets the product standard's requirements.
10.2.3.2 VERIFICATION OF RESISTANCE OF INSULATING MATERIALS TO NORMAL HEAT	Meets the product standard's requirements.
10.2.3.3 RESIST. OF INSUL. MAT. TO ABNORMAL HEAT/FIRE BY INTERNAL ELECT. EFFECTS	Meets the product standard's requirements.
10.2.4 RESISTANCE TO ULTRA-VIOLET (UV) RADIATION	Meets the product standard's requirements.
10.2.5 LIFTING	Does not apply, since the entire switchgear needs to be evaluated.
10.2.6 MECHANICAL IMPACT	Does not apply, since the entire switchgear needs to be evaluated.
10.2.7 INSCRIPTIONS	Meets the product standard's requirements.
10.3 DEGREE OF PROTECTION OF ASSEMBLIES	Does not apply, since the entire switchgear needs to be evaluated.
10.4 CLEARANCES AND CREEPAGE DISTANCES	Meets the product standard's requirements.
10.5 PROTECTION	Does not apply, since the

AGAINST ELECTRIC SHOCK	entire switchgear needs to be evaluated.
10.6 INCORPORATION OF SWITCHING DEVICES AND COMPONENTS	Does not apply, since the entire switchgear needs to be evaluated.
10.7 INTERNAL ELECTRICAL CIRCUITS AND CONNECTIONS	Is the panel builder's responsibility.
10.8 CONNECTIONS FOR EXTERNAL CONDUCTORS	Is the panel builder's responsibility.
10.9.2 POWER-FREQUENCY ELECTRIC STRENGTH	Is the panel builder's responsibility.
10.9.3 IMPULSE WITHSTAND VOLTAGE	Is the panel builder's responsibility.
10.9.4 TESTING OF ENCLOSURES MADE OF INSULATING MATERIAL	Is the panel builder's responsibility.

Technical data - electrical

CONTROL VOLTAGE TOLERANCE	+/- 20%
CURRENT CONSUMPTION - MAX	100 mA
VOLTAGE RATING	24 V DC

Technical data - mechanical

CONNECTION TYPE	Screw terminal (supply connection, rated control voltage) With push in terminal With bolt connection
DEGREE OF PROTECTION	Installation in the switch
SPECIAL FEATURES	• 24 V DC supply to the electronic trip. • Mechanical pass-through of the switch's status (I, O) for use by the remote operator.
STRIP LENGTH	5 mm (supply connection)

Technical data - mechanical - terminals

TERMINAL CAPACITY (SOLID CABLE)	0.2 mm ² - 1.5 mm ² (1x) at supply connection
TERMINAL CAPACITY (STRANDED CABLE)	0.25 mm ² - 0.75 mm ² (1x) at supply connection (insulated ferrule according to DIN46224 / 4) 24 - 16 AWG (1x) at supply connection 0.2 mm ² - 1.5 mm ² (1x) at supply connection 0.25 mm ² - 0.75 mm ² (1x) at supply connection (uninsulated ferrule according to DIN46224 / 1)
TIGHTENING TORQUE	≥ 0.22 Nm ≤ 0.25 Nm

Resources

BROCHURES	eaton-feerum-the-whole-grain-solution-success-story-en-us.pdf eaton-digital-nzm-brochure-br013003en-en-us.pdf
CATALOGUES	eaton-digital-nzm-catalog-ca013003en-en-us.pdf
INSTALLATION INSTRUCTIONS	eaton-circuit-breaker-interface-module-nzm-xbsm-il012102zu.pdf
INSTALLATION VIDEOS	The new digital NZM Range Introduction of the new digital circuit breaker NZM
TECHNICAL DATA SHEETS	eaton-nzm-technical-information-sheet

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

DATE:



Eaton Corporation plc Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2026 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

