

Specifications



Photo is representative



Eaton 189826

Eaton Moeller series NZM Interface module for NZM3 PXR20, connection for communication

General specifications

PRODUCT NAME	Eaton Moeller series NZM electronic accessory
CATALOG NUMBER	189826
MODEL CODE	NZM3-XBSM
EAN	4015081878215
PRODUCT LENGTH/DEPTH	50 mm
PRODUCT HEIGHT	22 mm
PRODUCT WIDTH	35 mm
PRODUCT WEIGHT	0.021 kg
COMPLIANCES	IEC UL/CSA RoHS conform



Powering Business Worldwide

Delivery programme

ACCESSORY/SPARE PART TYPE	Interface module Communication and measuring function Accessory
FRAME	NZM3
SPECIAL FEATURES	• For universal connection of optional circuit breaker functions. • Required for communication • The connection types depend on the design of the interface module. • Circuit breaker status detection (I, +, 0) for the electronic trip unit. • The switch's status can be communicated. • 24 V DC auxiliary power connection. • Connection for Communications Adapter Module (CAM). • Optional CAM available for various Fieldbus communication systems (Profibus DP, SmartWire-DT, Ethernet-based Fieldbus). • Connection to optional, internal Modbus RTU module. • Mechanical pass-through of the switch's status (I, O) for use by the remote operator.
TYPE	Interface module
USED WITH	NZM3(-4)- VX(MX)(PX)(PMX)...

Design verification to IEC/EN 61439

10.10 TEMPERATURE RISE	The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.
10.11 SHORT-CIRCUIT RATING	Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.12 ELECTROMAGNETIC COMPATIBILITY	Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.13 MECHANICAL FUNCTION	The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.
10.2.2 CORROSION RESISTANCE	Meets the product standard's requirements.
10.2.3.1 VERIFICATION OF THERMAL STABILITY OF ENCLOSURES	Meets the product standard's requirements.
10.2.3.2 VERIFICATION OF RESISTANCE OF INSULATING MATERIALS TO NORMAL HEAT	Meets the product standard's requirements.
10.2.3.3 RESIST. OF INSUL. MAT. TO ABNORMAL HEAT/FIRE BY INTERNAL ELECT. EFFECTS	Meets the product standard's requirements.
10.2.4 RESISTANCE TO ULTRA-VIOLET (UV) RADIATION	Meets the product standard's requirements.
10.2.5 LIFTING	Does not apply, since the entire switchgear needs to be evaluated.
10.2.6 MECHANICAL IMPACT	Does not apply, since the entire switchgear needs to be evaluated.
10.2.7 INSCRIPTIONS	Meets the product standard's requirements.
10.3 DEGREE OF PROTECTION OF ASSEMBLIES	Does not apply, since the entire switchgear needs to be evaluated.
10.4 CLEARANCES AND CREEPAGE DISTANCES	Meets the product standard's requirements.
10.5 PROTECTION	Does not apply, since the

AGAINST ELECTRIC SHOCK	entire switchgear needs to be evaluated.
10.6 INCORPORATION OF SWITCHING DEVICES AND COMPONENTS	Does not apply, since the entire switchgear needs to be evaluated.
10.7 INTERNAL ELECTRICAL CIRCUITS AND CONNECTIONS	Is the panel builder's responsibility.
10.8 CONNECTIONS FOR EXTERNAL CONDUCTORS	Is the panel builder's responsibility.
10.9.2 POWER-FREQUENCY ELECTRIC STRENGTH	Is the panel builder's responsibility.
10.9.3 IMPULSE WITHSTAND VOLTAGE	Is the panel builder's responsibility.
10.9.4 TESTING OF ENCLOSURES MADE OF INSULATING MATERIAL	Is the panel builder's responsibility.

Technical data - electrical

CONTROL VOLTAGE TOLERANCE +/- 20%

CURRENT CONSUMPTION - MAX 100 mA

VOLTAGE RATING 24 V DC

Technical data - mechanical

10-pin plug connector (internal COM connection)
5-pin plug connector (CAM connection)
Assembled CAM cable (Supply connection, Digital-input)
With push in terminal
Pre-wired cable to the Modbus module (internal COM connection)
Screw terminal (supply connection, rated control voltage)
With bolt connection

DEGREE OF PROTECTION Installation in the switch

SPECIAL FEATURES

- For universal connection of optional circuit breaker functions.
- Required for communication
- The connection types depend on the design of the interface module.
- Circuit breaker status detection (I, +, 0) for the electronic trip unit.
- The switch's status can be communicated.

Technical data - mechanical - terminals

TERMINAL CAPACITY (SOLID CABLE)	0.2 mm ² - 1.5 mm ² (1x) at supply connection
TERMINAL CAPACITY (STRANDED CABLE)	0.2 mm ² - 1.5 mm ² (1x) at supply connection 0.25 mm ² - 0.75 mm ² (1x) at supply connection (insulated ferrule according to DIN46224 / 4) 0.25 mm ² - 0.75 mm ² (1x) at supply connection (uninsulated ferrule according to DIN46224 / 1) 24 - 16 AWG (1x) at supply connection
TIGHTENING TORQUE	≥ 0.22 Nm ≤ 0.25 Nm

- 24 V DC auxiliary power connection.
- Connection for Communications Adapter Module (CAM).
- Optional CAM available for various Fieldbus communication systems (Profibus DP, SmartWire-DT, Ethernet-based Fieldbus).
- Connection to optional, internal Modbus RTU module.
- Mechanical pass-through of the switch's status (I, O) for use by the remote operator.

STRIP LENGTH	5 mm (supply connection)
Resources	
BROCHURES	eaton-digital-nzm-brochure-br013003en-en-us.pdf eaton-feerum-the-whole-grain-solution-success-story-en-us.pdf
CATALOGUES	eaton-digital-nzm-catalog-ca013003en-en-us.pdf
INSTALLATION INSTRUCTIONS	eaton-circuit-breaker-interface-module-nzm-xbsm-il012102zu.pdf
INSTALLATION VIDEOS	Introduction of the new digital circuit breaker NZM The new digital NZM Range
TECHNICAL DATA SHEETS	eaton-nzm-technical-information-sheet

PROJECT NAME:
PROJECT NUMBER:
PREPARED BY:
DATE:



Eaton Corporation plc Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2026 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

