

Specifications



Eaton 190974

Eaton Moeller® series DILMT Auxiliary contact module, 2 pole, Ith= 10 A, 1 N/O, 1 NC, Side mounted, Screw terminals, DILMT40 - DILMT95

General specifications

PRODUCT NAME	Eaton Moeller® series DILMT Accessory Auxiliary contact module
CATALOG NUMBER	190974
MODEL CODE	DILMT95-XHI11-SR
EAN	4015081911974
PRODUCT LENGTH/DEPTH	76.5 mm
PRODUCT HEIGHT	15 mm
PRODUCT WIDTH	76.5 mm
PRODUCT WEIGHT	0.055 kg
CERTIFICATIONS	IEC/EN 60947

Climatic environmental conditions

AMBIENT OPERATING TEMPERATURE - MAX	55 °C
-------------------------------------	-------

AMBIENT STORAGE TEMPERATURE - MAX	80 °C
-----------------------------------	-------

AMBIENT OPERATING TEMPERATURE - MIN	-25 °C
-------------------------------------	--------

AMBIENT STORAGE TEMPERATURE - MIN	-40 °C
-----------------------------------	--------

CLIMATIC PROOFING	Damp heat, constant, to IEC 60068-2-78 Damp heat, cyclic, to IEC 60068-2-30
-------------------	--

Electrical rating

RATED OPERATIONAL CURRENT (IE) AT AC-15, 220 V, 230 V, 240 V	4 A
--	-----

RATED OPERATIONAL CURRENT (IE) AT AC-15, 380 V, 400 V, 415 V	1.9 A
--	-------

General information

MODEL	Top mounting
-------	--------------

MOUNTING METHOD	Side mounting
-----------------	---------------

USED WITH	DILMT
-----------	-------

Contacts

NUMBER OF CONTACTS (CHANGE-OVER CONTACTS)	0
---	---

NUMBER OF CONTACTS (NORMALLY CLOSED CONTACTS)	1
---	---

NUMBER OF CONTACTS (NORMALLY OPEN CONTACTS)	1
---	---

Features & functions

ELECTRIC CONNECTION TYPE	Screw connection
--------------------------	------------------

FUNCTIONS	For standard applications
-----------	---------------------------

NUMBER OF POLES	Two-pole
-----------------	----------

Terminal capacities

SCREWDRIVER SIZE	2, Terminal screw, Pozidriv screwdriver
------------------	---

TERMINAL CAPACITY (FLEXIBLE WITH FERRULE)	1 x (0.75 - 2.5) mm ²
---	----------------------------------

TERMINAL CAPACITY (SOLID)	1 x (0.75 - 2.5) mm ² , Screw terminals
---------------------------	--

TIGHTENING TORQUE	1.2 Nm, Screw terminals
-------------------	-------------------------

Resources

BROCHURES

[eaton-powerxl-variable-frequency-drives-hvac-brochure-br040012en-en-us.pdf](#)

[eaton-dilat-dilmt-contactors-zbt-motor-protection-relay-brochure-br034003en-en-us.pdf](#)

DRAWINGS

[eaton-contactors-dimensions-005.eps](#)

[eaton-contactors-3d-drawing-010.eps](#)

ECAD MODEL

[DA-CE-ETN.DILMT95-XHI11-SR](#)

INSTALLATION INSTRUCTIONS

[IL034052ZU](#)

WIRING DIAGRAMS

[eaton-contactors-mounting-wiring-diagram.eps](#)

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

DATE:



Eaton Corporation plc Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2026 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

