

Specifications



Eaton 190987

Eaton Moeller® series DILMT Contactor, 3 pole, 380 V 400 V: 45 kW, 24 V DC, DC operation, Screw terminals

General specifications

PRODUCT NAME	Eaton Moeller® series DILMT Contactor
CATALOG NUMBER	190987
MODEL CODE	DILMT95(RDC24)
EAN	4015081912100
PRODUCT LENGTH/DEPTH	124.5 mm
PRODUCT HEIGHT	111.5 mm
PRODUCT WIDTH	72 mm
PRODUCT WEIGHT	1.26 kg
CERTIFICATIONS	EN 60335-1 GB14048 IEC/EN 60947
CATALOG NOTES	Not suitable for motors with efficiency class IE3.



Powering Business Worldwide

Climatic environmental conditions

AMBIENT OPERATING TEMPERATURE - MAX	55 °C
-------------------------------------	-------

AMBIENT STORAGE TEMPERATURE - MAX	80 °C
-----------------------------------	-------

AMBIENT OPERATING TEMPERATURE - MIN	-25 °C
-------------------------------------	--------

AMBIENT STORAGE TEMPERATURE - MIN	-40 °C
-----------------------------------	--------

CLIMATIC PROOFING	Damp heat, constant, to IEC 60068-2-78 Damp heat, cyclic, to IEC 60068-2-30
-------------------	--

Electrical rating

RATED BREAKING CAPACITY AT 380/400 V	760 A
--------------------------------------	-------

RATED INSULATION VOLTAGE (UI)	690 V
-------------------------------	-------

RATED OPERATIONAL CURRENT (IE) AT AC-1, 380 V, 400 V, 415 V	120 A
---	-------

RATED OPERATIONAL CURRENT (IE) AT AC-3, 220 V, 230 V, 240 V	95 A
---	------

RATED OPERATIONAL CURRENT (IE) AT AC-3, 380 V, 400 V, 415 V	95 A
---	------

RATED OPERATIONAL POWER AT AC-3, 380/400 V, 50 HZ	45 kW
---	-------

RATED OPERATIONAL POWER AT AC-3, 690 V, 50 HZ	45 kW
---	-------

RATED OPERATIONAL VOLTAGE (UE) AT AC - MAX	690 V
--	-------

Contacts

NUMBER OF AUXILIARY CONTACTS (NORMALLY CLOSED CONTACTS)	0
---	---

NUMBER OF AUXILIARY CONTACTS (NORMALLY OPEN CONTACTS)	0
---	---

Features & functions

FITTED WITH:	Varistor suppressor circuit
--------------	-----------------------------

NUMBER OF POLES	Three-pole
-----------------	------------

General information

APPLICATION	Contactors for Motors
CONNECTION TO SMARTWIRE-DT	No
DEGREE OF PROTECTION	IP20
FRAME SIZE	FS4
LIFESPAN, MECHANICAL	5,000,000 Operations (DC operated)
OPERATING FREQUENCY	3600 mechanical Operations/h (DC operated)
OVERVOLTAGE CATEGORY	III
POLLUTION DEGREE	3
PRODUCT CATEGORY	Contactors
RATED IMPULSE WITHSTAND VOLTAGE (UIMP)	6000 V AC
USED WITH	DILMT95-XHI11-SR and DILT-XHI01(10)
UTILIZATION CATEGORY	AC-1: Non-inductive or slightly inductive loads, resistance furnaces AC-4: Normal AC induction motors: starting, plugging, reversing, inching
VOLTAGE TYPE	DC

Terminal capacities

SCREW SIZE	M8, Terminal screw M3.5, Terminal screw 4 mm AF, Hexagon socket-head spanner, Terminal screw
SCREWDRIVER SIZE	2, Terminal screw, Pozidriv screwdriver
STRIPPING LENGTH (MAIN CABLE)	16 mm
TERMINAL CAPACITY (SOLID)	2 x (0.75 - 2.5) mm ² 1 x (0.75 - 2.5) mm ² 1 x (6 - 50) mm ² , Main cables 2 x (6 - 25) mm ² , Main cables
TERMINAL CAPACITY (STRANDED)	1 x (6 - 50) mm ² 2 x (6 - 25) mm ² , Main cables
TIGHTENING TORQUE	1.2 Nm, Screw terminals

Magnet system

RATED CONTROL SUPPLY VOLTAGE (US) AT DC - MAX 24 V

RATED CONTROL SUPPLY VOLTAGE (US) AT DC - MIN 24 V

Resources

BROCHURES	eaton-dilat-dilmt-contactors-zbt-motor-protection-relay-brochure-br034003en-en-us.pdf
	eaton-powerxl-variable-frequency-drives-hvac-brochure-br040012en-en-us.pdf
DRAWINGS	eaton-contactors-contactor-dimensions-006.eps
	eaton-contactors-contactor-dimensions-004.eps
	eaton-general-mounting-contactor-3d-drawing.eps
	eaton-contactors-contactor-3d-drawing-003.eps

ECAD MODEL	DA-CE-ETN.DILMT95(RDC24)
INSTALLATION INSTRUCTIONS	IL034052ZU
WIRING DIAGRAMS	eaton-contactors-contact-dilm-wiring-diagram-003.eps

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

DATE:



Eaton Corporation plc Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2026 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

