

Specifications



Eaton 196845

Eaton Distribution board accessory,
Analogue Light intensity switch, DIN rail 1
TE, 1 NO contact, external light sensor
Surface-mounted, 2-2000 Lux

General specifications

PRODUCT NAME	Eaton distribution board accessory
CATALOG NUMBER	196845
MODEL CODE	SRSD1NOW
EAN	9008790990410
PRODUCT LENGTH/DEPTH	65.5 mm
PRODUCT HEIGHT	85.5 mm
PRODUCT WIDTH	17.5 mm
PRODUCT WEIGHT	0.121 kg
COMPLIANCES	RoHS conform

Product specifications

MOUNTING METHOD	DIN rail
ADJUSTMENT RANGE BRIGHTNESS VALUE - MAX	2000 lx
ADJUSTMENT RANGE BRIGHTNESS VALUE - MIN	2 lx
CONDUCTOR LENGTH LIGHT SENSOR - MAX	50 m
FREQUENCY RATING - MAX	60 Hz
FREQUENCY RATING - MIN	50 Hz
HEAT DISSIPATION CAPACITY	0.8 W
INCANDESCENT LAMP LOAD - MAX	2600 W
LOAD FLUORESCENT LAMP - MAX	2300 VA
LOAD FLUORESCENT LAMP (DUO CIRCUIT) - MAX	2300 VA
LOAD FLUORESCENT LAMP (PARALLEL COMPENSATED) - MAX	730 VA
RATED OPERATIONAL VOLTAGE (UE) - MAX	230 V
DEGREE OF PROTECTION	IP55
RATED SWITCH CURRENT	16 A
STATIC HEAT DISSIPATION, NON-CURRENT-DEPENDENT	0.3 W
SWITCHING CURRENT (COS PHI = 0.6) - MAX	10 A
SWITCHING POWER LED - MAX	350 W
WIDTH IN NUMBER OF MODULAR SPACINGS	1
BUILT-IN DEPTH	65.5 mm
DEGREE OF PROTECTION (LIGHT SENSOR)	IP54
MOUNTING METHOD (LIGHT SENSOR)	Wall surface mounted
PROTECTION CLASS (LIGHT SENSOR)	II

Resources

DECLARATIONS OF CONFORMITY	eaton-distribution-parts-declaration-of-conformity-eu250239en.pdf
DRAWINGS	eaton-3d-drawing-srsd1no-anschl.jpg eaton-dimensions-mas-ds-ta-1s.jpg

PROJECT NAME:
PROJECT NUMBER:
PREPARED BY:
DATE:



Eaton Corporation plc Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2026 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

