

Specifications



Eaton 196847

Eaton Distribution board accessory, Digital Light intensity time switch, DIN rail 2 TE, weekly program, 1 channel, changeover contact, external light sensor Surface-mounted, 1-99000 Lux, push terminals

General specifications

PRODUCT NAME	Eaton distribution board accessory
CATALOG NUMBER	196847
MODEL CODE	SRCD1COD
EAN	9008790990434
PRODUCT LENGTH/DEPTH	69.2 mm
PRODUCT HEIGHT	90.1 mm
PRODUCT WIDTH	35.8 mm
PRODUCT WEIGHT	0.179 kg
COMPLIANCES	RoHS conform

Product specifications

MOUNTING METHOD	DIN rail
FEATURES	Push button input With programmable overnight shutoff
ADJUSTMENT RANGE BRIGHTNESS VALUE - MAX	99000 lx
ADJUSTMENT RANGE BRIGHTNESS VALUE - MIN	1 lx
CONDUCTOR LENGTH LIGHT SENSOR - MAX	100 m
FREQUENCY RATING - MAX	60 Hz
FREQUENCY RATING - MIN	50 Hz
HEAT DISSIPATION CAPACITY	1.5 W
INCANDESCENT LAMP LOAD - MAX	2600 W
LOAD FLUORESCENT LAMP - MAX	2600 VA
LOAD FLUORESCENT LAMP (DUO CIRCUIT) - MAX	2600 VA
LOAD FLUORESCENT LAMP (PARALLEL COMPENSATED) - MAX	1300 VA
RATED OPERATIONAL VOLTAGE (UE) - MAX	230 V
DEGREE OF PROTECTION	IP20
RATED SWITCH CURRENT	16 A
STATIC HEAT DISSIPATION, NON- CURRENT-DEPENDENT	0.8 W
SWITCHING CURRENT (COS PHI = 0.6) - MAX	10 A
SWITCHING POWER LED - MAX	600 W
WIDTH IN NUMBER OF MODULAR SPACINGS	2
BUILT-IN DEPTH	69.2 mm
DEGREE OF PROTECTION (LIGHT SENSOR)	IP55
MOUNTING METHOD (LIGHT SENSOR)	Wall surface mounted
PROTECTION CLASS (LIGHT SENSOR)	III

Resources

DECLARATIONS OF CONFORMITY	eaton-distribution-parts-declaration-of-conformity-eu250239en.pdf
DRAWINGS	eaton-3d-drawing-srcd1cod-anschl.jpg eaton-dimensions-mas- tsdw.jpg
MATERIAL SAFETY DATA SHEET (MSDS)	MSDS Varta Primary Lithium Cylindrical (Series CR).pdf
TEST REPORT	UN38.3 Varta CR1 2 AA.pdf

PROJECT NAME:
PROJECT NUMBER:
PREPARED BY:
DATE:



Eaton Corporation plc Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2026 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

