

Specifications



Eaton 197211

Eaton Moeller® series EASY Control relays easyE4 with display (expandable, Ethernet), 12/24 V DC, 24 V AC, Inputs Digital: 8, of which can be used as analog: 4, screw terminal

General specifications

PRODUCT NAME	Eaton Moeller® series EASY Control relay
CATALOG NUMBER	197211
MODEL CODE	EASY-E4-UC-12RC1
EAN	4015081939480
PRODUCT LENGTH/DEPTH	58 mm
PRODUCT HEIGHT	90 mm
PRODUCT WIDTH	72 mm
PRODUCT WEIGHT	0.25 kg
COMPLIANCES	Eaton supports the product until its end of life
CERTIFICATIONS	IEC 60068-2-30 IEC 60068-2-6 IEC/EN 61000-4-2 CSA-C22.2 No. 61010 CULus per UL 61010 EN 61010 IEC/EN 61000-6-3 IEC/EN 61131-2 IEC/EN 61000-6-2 EN 50178 IEC 60068-2-27 UL Listed UL Category Control No.: NRAQ, NRAQ7 UL File No.: E205091 DNV GL CE UL hazardous location group B (hydrogen) UL hazardous location group C (ethylene) UL hazardous location division 2 UL hazardous location group A (acetylene) UL hazardous location



Powering Business Worldwide

	class I UL hazardous location group D (propane)
CATALOG NOTES	Accuracy of the real-time clock depending on ambient air temperature - fluctuations of up to ± 5 s/day (± 0.5 h/year) are possible

Ambient conditions, mechanical	
DROP AND TOPPLE	50 mm Drop height, Drop to IEC/EN 60068-2-31
HEIGHT OF FALL (IEC/EN 60068-2-32) - MAX	0.3 m
MOUNTING POSITION	Vertical Horizontal
SHOCK RESISTANCE	15 g, Mechanical, according to IEC/EN 60068-2-27, Half- sinusoidal shock 11 ms, 18 Impacts
VIBRATION RESISTANCE	10 - 57 Hz, 0.15 mm constant amplitude According to IEC/EN 60068-2-6 57 - 150 Hz, 2 g constant acceleration

Climatic environmental conditions	
AIR PRESSURE	795 - 1080 hPa (operation)
AMBIENT OPERATING TEMPERATURE - MAX	55 °C
AMBIENT STORAGE TEMPERATURE - MAX	70 °C
AMBIENT OPERATING TEMPERATURE - MIN	-25 °C
AMBIENT STORAGE TEMPERATURE - MIN	-40 °C
ENVIRONMENTAL CONDITIONS	Clearance in air and creepage distances according to EN 50178, EN 61010-2-201, UL61010-2- 201, CSA-C22.2 NO. 61010- 2-201 Condensation: prevent with appropriate measures
RELATIVE HUMIDITY	5 - 95 % (IEC 60068-2-30, IEC 60068-2-78)

Cable	
CABLE LENGTH	100 m, unscreened, Digital inputs 24 V DC 100 m, unscreened, Digital inputs 24 V AC ≤ 30 m, screened, Analog inputs 100 m, unscreened, Digital inputs 12 V DC 40 m (max. per input), Digital inputs 24 V DC
CABLE TYPE	Ethernet: CAT5

Communication	
CONNECTION TYPE	Screw terminal Ethernet: RJ45 plug, 8-pole
DATA TRANSFER RATE	10/100 MBit/s

Design verification

10.10 TEMPERATURE RISE	The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.
10.11 SHORT-CIRCUIT RATING	Is the panel builder's responsibility.
10.12 ELECTROMAGNETIC COMPATIBILITY	Is the panel builder's responsibility.
10.13 MECHANICAL FUNCTION	The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.
10.2.2 CORROSION RESISTANCE	Meets the product standard's requirements.
10.2.3.1 VERIFICATION OF THERMAL STABILITY OF ENCLOSURES	Meets the product standard's requirements.
10.2.3.2 VERIFICATION OF RESISTANCE OF INSULATING MATERIALS TO NORMAL HEAT	Meets the product standard's requirements.
10.2.3.3 RESIST. OF INSUL. MAT. TO ABNORMAL HEAT/FIRE BY INTERNAL ELECT. EFFECTS	Meets the product standard's requirements.
10.2.4 RESISTANCE TO ULTRA-VIOLET (UV) RADIATION	Meets the product standard's requirements.
10.2.5 LIFTING	Does not apply, since the entire switchgear needs to be evaluated.
10.2.6 MECHANICAL IMPACT	Does not apply, since the entire switchgear needs to be evaluated.
10.2.7 INSCRIPTIONS	Meets the product standard's requirements.
10.3 DEGREE OF PROTECTION OF ASSEMBLIES	Meets the product standard's requirements.
10.4 CLEARANCES AND CREEPAGE DISTANCES	Meets the product standard's requirements.
10.5 PROTECTION AGAINST ELECTRIC SHOCK	Does not apply, since the entire switchgear needs to be evaluated.
10.6 INCORPORATION OF SWITCHING DEVICES AND COMPONENTS	Does not apply, since the entire switchgear needs to be evaluated.

Electrical rating

CONVENTIONAL THERMAL CURRENT ITH OF AUXILIARY CONTACTS (1-POLE, OPEN)	8 A
POWER CONSUMPTION	3 W
RATED BREAKING CAPACITY	300000 Operations at AC-15, 250 V AC, 3 A (600 Ops./h) 200000 Operations at DC-13, 24 V DC, 1 A (500 Ops./h)
RATED INSULATION VOLTAGE (UI)	240 V
RATED OPERATIONAL VOLTAGE	Max. 300 V DC 12 V DC (digital inputs) Max. 300 V AC 240 V AC 24 V AC (-15 %/+10 % - power supply) 24 V DC (digital inputs) 12/24 V DC (-15 %/+ 20 % - power supply) 10.2 - 28.8 V DC 24 V AC (digital inputs) 20.4 - 26.4 V AC
SUPPLY FREQUENCY	50/60 Hz (± 5%)
SUPPLY VOLTAGE AT AC, 50 HZ - MAX	26.4 VAC
SUPPLY VOLTAGE AT AC, 50 HZ - MIN	20.4 VAC
SUPPLY VOLTAGE AT DC - MAX	28.8 VDC
SUPPLY VOLTAGE AT DC - MIN	10.2 VDC
UNINTERRUPTED CURRENT	1 A DC, at R 300 (UL/CSA) 8 A DC, at 24 V DC (UL/CSA) 5 A AC, max. thermal continuous current $\cos \phi = 1$ at B 300 (UL/CSA) 10 A AC, at 240 V AC (UL/CSA)

10.7 INTERNAL ELECTRICAL CIRCUITS AND CONNECTIONS	Is the panel builder's responsibility.
10.8 CONNECTIONS FOR EXTERNAL CONDUCTORS	Is the panel builder's responsibility.
10.9.2 POWER-FREQUENCY ELECTRIC STRENGTH	Is the panel builder's responsibility.
10.9.3 IMPULSE WITHSTAND VOLTAGE	Is the panel builder's responsibility.
10.9.4 TESTING OF ENCLOSURES MADE OF INSULATING MATERIAL	Is the panel builder's responsibility.
EQUIPMENT HEAT DISSIPATION, CURRENT-DEPENDENT PVID	4 W
HEAT DISSIPATION CAPACITY PDISS	0 W
HEAT DISSIPATION PER POLE, CURRENT-DEPENDENT PVID	0 W
RATED OPERATIONAL CURRENT FOR SPECIFIED HEAT DISSIPATION (IN)	0 A
STATIC HEAT DISSIPATION, NON-CURRENT-DEPENDENT PVS	3 W

Electro magnetic compatibility

AIR DISCHARGE	8 kV
BURST IMPULSE	2 kV, Supply cable 2 kV, Signal cable According to IEC/EN 61000-4-4
CONTACT DISCHARGE	6 kV
ELECTROMAGNETIC FIELDS	10 V/m at 0.8 - 1.0 GHz (according to IEC EN 61000-4-3) 1 V/m at 2.0 - 2.7 GHz (according to IEC EN 61000-4-3) 3 V/m at 1.4 - 2 GHz (according to IEC EN 61000-4-3)
IMMUNITY TO LINE-CONDUCTED INTERFERENCE	10 V (according to IEC/EN 61000-4-6)
RADIO INTERFERENCE CLASS	Class B (EN 61000-6-3)
SURGE RATING	1 kV, Supply cables, symmetrical, power pulses (Surge), EMC According to IEC/EN 61000-4-5, power pulses (Surge), EMC 2 kV, Supply cables, asymmetrical, power pulses (Surge), EMC
VOLTAGE DIPS	≤ 1 ms from rated voltage (12 V DC) 10 ms

Features & functions

FEATURES	Expandable Display indication of 6 lines x 16 characters Networkable (Ethernet)
FITTED WITH:	Display Real time clock Relay output Keypad Timer
INDICATION	LCD-display used as status indication of Digital inputs 24 V DC LCD-display used as status indication of Digital inputs 12 V DC

General information

DEGREE OF PROTECTION	IP20
DISPLAY TEMPERATURE - MAX	55 °C
DISPLAY TEMPERATURE - MIN	0 °C
DISPLAY TYPE	Monochrome
FREQUENCY COUNTER	Pulse shape: Square (digital inputs 24 V DC) Cable length: ≤ 20 m (screened, Digital inputs 24 V DC) Number: 4 (I1, I2, I3, I4 - Digital inputs 24 V DC) Pulse pause ratio: 1:1 (Digital inputs 24 V DC) Counter frequency: 5 kHz (Digital inputs 24 V DC)
INPUT FREQUENCY	50/60 Hz (Digital inputs, at 24 V DC)
INSULATION RESISTANCE	According to EN 50178, EN 61010-2-201, UL61010-2-201, CSA-C22.2 NO. 61010-2-201
LIFESPAN, ELECTRICAL	25,000 Operations (Filament bulb load at 1000 W, 230/240 V AC) 25,000 Operations (Fluorescent lamp load 10 x 58 W at 230/240 V AC, uncompensated) 25,000 Operations (Fluorescent lamp load 10 x 58 W at 230/240 V AC, with upstream electrical device) 25,000 Operations (Filament bulb load at 500 W, 115/120 V AC) 25,000 Operations (Fluorescent lamp load 1 x 58 W at 230/240 V AC, conventional, compensated)
LIFESPAN, MECHANICAL	10,000,000 Operations
MOUNTING METHOD	Screw fixing using fixing brackets ZB4-101-GF1 (accessories) Front build in possible Rail mounting possible Top-hat rail fixing (according to IEC/EN 60715, 35 mm) Wall mounting/direct mounting

Input/Output

ACCURACY	± 2 s/day, Real-time clock to inputs (± 0.2 h/Year) ± 2 %, (I5, I6, I7, I8) ± 0.12 V, of actual value, within a single device (Analog Inputs) ± 1 %, Repetition accuracy of timing relays (of values) ± 3 %, of actual value, two easy devices (Analog Inputs)
CONVERSIONS	Each CPU cycle for Analog inputs 0.015 ms typ., Digital inputs 12 V DC (I1 - I8), Delay time from 1 to 0, Debounce OFF 0.015 ms typ., Digital inputs 24 V DC (I1 - I8), Delay time from 1 to 0, Debounce OFF 0.015 ms typ., Digital inputs 24 V DC (I1 - I8), Delay time from 0 to 1, Debounce OFF 20 ms typ., Digital inputs 12 V DC (I1 - I8), Delay time from 1 to 0, Debounce ON 20 ms typ., Digital inputs 12 V DC (I1 - I8), Delay time from 0 to 1, Debounce ON 20 ms typ., Digital inputs 24 V DC (I1 - I8), Delay time from 0 to 1, Debounce ON 20 ms typ., Digital inputs 24 V DC (I1 - I8), Delay time from 1 to 0, Debounce ON 0.015 ms typ., Digital inputs 12 V DC (I1 - I8), Delay time from 0 to 1, Debounce OFF
DELAY TIME	
INCREMENTAL COUNTER	Number of counter inputs: 2 (I1 + I2, I3 + I4) Value range: -2147483648 to +2147483647 Pulse shape: Square Pulse pause ratio: 1:1 Signal offset: 90° Counter frequency: ≤ 5 kHz
INCREMENTAL ENCODER	Cable length: ≤ 20 m (screened)
INPUT	Voltage (DC)
INPUT CURRENT	3.3 mA (I1 - I4, at 24 V DC, at signal 1)

OVERVOLTAGE CATEGORY	III
POLLUTION DEGREE	2
PRODUCT CATEGORY	Control relays easyE4
PROTECTION	Miniature circuit-breaker B16 or slow-blow 8 A fuse, Protection of an output relay
PROTOCOL	TCP/IP MODBUS
RATED IMPULSE WITHSTAND VOLTAGE (UIMP)	6 kV (contact-coil)
RESIDUAL RIPPLE	≤ 5 %
RESOLUTION	• 1 min (Range H:M) • 1 s (Range M:S) • 12 Bit (value 0 - 4095, Analog inputs) • 5 ms (Range S)
SOFTWARE	EASYSOFT-SWLIC/easySoft
SWITCHING FREQUENCY	10 Hz, Relay outputs 2 Hz, Resistive load/lamp load, Relay outputs 0.5 Hz, Inductive load, Relay outputs
TYPE	easyE4 base device
USED WITH	easyE4
UTILIZATION CATEGORY	B 300 Light Pilot Duty, UL/CSA Control Circuit Rating Codes AC R 300 Light Pilot Duty, UL/CSA Control Circuit Rating Codes DC
VOLTAGE TYPE	AC/DC

	2.2 mA (I5 - I8, at 24 V DC, at signal 1) 1 mA (Analog inputs) 200 mA
INPUT IMPEDANCE	13.3 kΩ
INPUT VOLTAGE	At signal 1: ≥ 15 V (I1 - I8, sinusoidal, Digital inputs, 24 V DC) Status 0: ≤ 8 V DC (I5 - I8, Digital inputs, 24 V DC) Status 1: ≥ 8 V DC (I5 - I8, Digital inputs, 24 V DC) Signal 0: ≤ 5 V DC (I1 - I4, Digital inputs, 12 V DC) Status 0: ≤ 15 V DC (I1 - I4, Digital inputs, 24 V DC) At signal 0: ≤ 5 V (I1 - I8, sinusoidal, Digital inputs, 24 V DC) Status 1: ≥ 15 V DC (I1 - I4, Digital inputs, 24 V DC)
MAKING/BREAKING CAPACITY	28/28 VA (DC, at R 300) 3600/360 VA (AC, at B 300)
NUMBER OF INPUTS (ANALOG)	0 4
NUMBER OF INPUTS (DIGITAL)	4 8
NUMBER OF OUTPUTS (ANALOG)	0
NUMBER OF OUTPUTS (DIGITAL)	4
OUTPUT	4 Relay Outputs > 500 mA (Relay outputs, Recommended for load: 12 V AC/DC) Relay outputs in groups of 1 Voltage Current
PARALLEL SWITCHING	Not permitted
RAPID COUNTER INPUTS	Counter frequency: ≤ 10 kHz Value range: -2147483648 to +2147483647 Cable length: ≤ 20 m (shielded) Pulse pause ratio: 1:1 Pulse shape: Square Number of rapid counter inputs: 4 (I1, I2, I3, I4)
SIGNAL RANGE	0 - 10 V DC, Analog inputs

Safety

EXPLOSION SAFETY CATEGORY FOR DUST

None

EXPLOSION SAFETY CATEGORY FOR GAS

None

POTENTIAL ISOLATION

Between Digital inputs 12 V DC and Outputs: yes
Between Analog inputs and Outputs: yes
Between Digital inputs 12 V DC and expansion devices: yes
Between Digital inputs 24 V DC and Outputs: yes
Between Relay outputs and expansion devices: yes
Between Digital inputs 24 V AC and Outputs: yes
Between Relay outputs and Power supply: yes
Between Digital inputs 24 V DC and expansion devices: yes
Between Digital inputs 24 V DC and Ethernet: yes
Basic isolation: 600 V AC (Relay outputs)
Between Analog inputs and expansion devices: yes
Between Relay outputs: yes
Between Relay outputs and Inputs: yes
Between Digital inputs 12 V DC and Ethernet: yes
Between Relay outputs and Ethernet: yes
Safe isolation according to EN 50178: 300 V AC (Relay outputs)
Between Digital inputs 24 V AC and expansion devices: yes
Between Digital inputs 24 V AC and Ethernet: yes

PROTECTION AGAINST POLARITY REVERSAL

Yes, for supply voltage (Siemens MPI optional)

SAFE ISOLATION

300 V AC, Between coil and contact, According to EN 50178
300 V AC, Between two contacts, According to EN 50178

Short-circuit rating

SHORT-CIRCUIT PROTECTION

≥ 1A (T), Fuse, Power supply

Terminal capacities

SCREWDRIVER SIZE	3.5 x 0.8 mm, Terminal screw
TERMINAL CAPACITY	0.2 - 4 mm ² (AWG 22 - 12), solid 0.2 - 2.5 mm ² (22 - 12 AWG), flexible with ferrule
TIGHTENING TORQUE	0.6 Nm, Screw terminals

Resources

APPLICATION NOTES [eaton-easye4-aws-ap050027-en-us.pdf](#)

CATALOGUES [eaton-product-overview-for-machinery-catalogue-ca08103003zen-en-us.pdf](#)

CHARACTERISTIC CURVE [eaton-electrical-timers-easy-control-relays-characteristic-curve-002.eps](#)

DECLARATIONS OF CONFORMITY [eaton-control-relay-declaration-of-conformity-eu250648en.pdf](#)
[eaton-control-relay-declaration-of-conformity-uk251131en.pdf](#)

[eaton-modular-plc-starter-kit-dimensions.eps](#)
DRAWINGS [eaton-general-easy-control-relays-symbol-002.tif](#)
[eaton-modular-plc-easy-control-relays-3d-drawing.eps](#)

ECAD MODEL [ETN.EASY-E4-UC-12RC1](#)

INSTALLATION INSTRUCTIONS [eaton-easye4-base-programmable-control-relays-il050020zu.pdf](#)

INSTALLATION VIDEOS [Control relay easyE4: The new generation](#)
[Video easy E4 control relay](#)

MANUALS AND USER GUIDES [eaton-easye-rtd-advanced-training-gh138-mn050015en-us.pdf](#)
[eaton-easye-easysoft-training-gh135-mn050014en-us.pdf](#)

MCAD MODEL [eaton-logic-modules-mcad-drawings-uc-12rc1.dwg](#)
[DA-CS-uc_12rc1](#)

[How to process ModbusRTU devices with the EASY-COM-RTU-M1 module on an easyE4?](#)
MULTIMEDIA [easyE4 SmartWire-DT module with Remote Touch Display and RMQ multi color indicator](#)
[How to connect the Remote Touch Display EASY-RTD to the easyE4?](#)

[How to process SmartWire-DT modules using the EASY-COM-SWD-C1 module connected to an easyE4?](#)

[Handling of the data logger as a ring buffer with the easyE4 using the ST programming language.](#)

[How to connect the easyE4 to the touch panel XV-102 for easy? - 5 Steps](#)

PRODUCT NOTIFICATIONS	MZ049014EN
SALES NOTES	eaton-easy-remote-touch-display-flyer-fl048004en-en-us.pdf eaton-control-relay-easye4-flyer-fl050007en-en-us.pdf
SOFTWARE, FIRMWARE, AND APPLICATIONS	easyE4 Anwendungsbeispiele e70 KOP EDP

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

DATE:



Eaton Corporation plc Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2026 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

