

Specifications



Eaton 197213

Eaton Moeller® series EASY Control relays easyE4 with display (expandable, Ethernet), 24 V DC, Inputs Digital: 8, of which can be used as analog: 4, screw terminal

General specifications

PRODUCT NAME	Eaton Moeller® series EASY Control relay
CATALOG NUMBER	197213
MODEL CODE	EASY-E4-DC-12TC1
EAN	4015081939466
PRODUCT LENGTH/DEPTH	58 mm
PRODUCT HEIGHT	90 mm
PRODUCT WIDTH	72 mm
PRODUCT WEIGHT	0.2 kg
COMPLIANCES	Eaton supports the product until its end of life
CERTIFICATIONS	CSA-C22.2 No. 61010 EN 61010 IEC/EN 61000-6-2 IEC 60068-2-27 IEC 60068-2-30 IEC/EN 61000-4-2 CULus per UL 61010 IEC 60068-2-6 IEC/EN 61000-6-3 IEC/EN 61131-2 EN 50178 UL Listed UL Category Control No.: NRAQ, NRAQ7 UL File No.: E205091 DNV GL CE UL hazardous location class I UL hazardous location group A (acetylene) UL hazardous location group D (propane) UL hazardous location group C (ethylene) UL hazardous location division 2



Powering Business Worldwide

	UL hazardous location group B (hydrogen)
CATALOG NOTES	Accuracy of the real-time clock depending on ambient air temperature - fluctuations of up to ± 5 s/day (± 0.5 h/year) are possible

Ambient conditions, mechanical

DROP AND TOPPLE	50 mm Drop height, Drop to IEC/EN 60068-2-31
HEIGHT OF FALL (IEC/EN 60068-2-32) - MAX	0.3 m
MOUNTING POSITION	Vertical Horizontal
SHOCK RESISTANCE	15 g, Mechanical, according to IEC/EN 60068-2-27, Half-sinusoidal shock 11 ms, 18 Impacts
VIBRATION RESISTANCE	10 - 57 Hz, 0.15 mm constant amplitude 57 - 150 Hz, 2 g constant acceleration According to IEC/EN 60068-2-6

Climatic environmental conditions

AIR PRESSURE	795 - 1080 hPa (operation)
AMBIENT OPERATING TEMPERATURE - MAX	55 °C
AMBIENT STORAGE TEMPERATURE - MAX	70 °C
AMBIENT OPERATING TEMPERATURE - MIN	-25 °C
AMBIENT STORAGE TEMPERATURE - MIN	-40 °C
ENVIRONMENTAL CONDITIONS	Condensation: prevent with appropriate measures Clearance in air and creepage distances according to EN 50178, EN 61010-2-201, UL61010-2-201, CSA-C22.2 NO. 61010-2-201
RELATIVE HUMIDITY	5 - 95 % (IEC 60068-2-30, IEC 60068-2-78)

Cable

CABLE LENGTH	≤ 30 m, screened, Analog inputs 100 m, unscreened, Digital inputs 24 V DC
CABLE TYPE	Ethernet: CAT5

Communication

CONNECTION TYPE	Screw terminal Ethernet: RJ45 plug, 8-pole
DATA TRANSFER RATE	10/100 MBit/s

Design verification

10.10 TEMPERATURE RISE	The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.
10.11 SHORT-CIRCUIT RATING	Is the panel builder's responsibility.
10.12 ELECTROMAGNETIC COMPATIBILITY	Is the panel builder's responsibility.
10.13 MECHANICAL FUNCTION	The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.
10.2.2 CORROSION RESISTANCE	Meets the product standard's requirements.
10.2.3.1 VERIFICATION OF THERMAL STABILITY OF ENCLOSURES	Meets the product standard's requirements.
10.2.3.2 VERIFICATION OF RESISTANCE OF INSULATING MATERIALS TO NORMAL HEAT	Meets the product standard's requirements.
10.2.3.3 RESIST. OF INSUL. MAT. TO ABNORMAL HEAT/FIRE BY INTERNAL ELECT. EFFECTS	Meets the product standard's requirements.
10.2.4 RESISTANCE TO ULTRA-VIOLET (UV) RADIATION	Meets the product standard's requirements.
10.2.5 LIFTING	Does not apply, since the entire switchgear needs to be evaluated.
10.2.6 MECHANICAL IMPACT	Does not apply, since the entire switchgear needs to be evaluated.
10.2.7 INSCRIPTIONS	Meets the product standard's requirements.
10.3 DEGREE OF PROTECTION OF ASSEMBLIES	Meets the product standard's requirements.
10.4 CLEARANCES AND CREEPAGE DISTANCES	Meets the product standard's requirements.
10.5 PROTECTION AGAINST ELECTRIC SHOCK	Does not apply, since the entire switchgear needs to be evaluated.
10.6 INCORPORATION OF SWITCHING DEVICES AND COMPONENTS	Does not apply, since the entire switchgear needs to be evaluated.

Electrical rating

CONVENTIONAL THERMAL CURRENT ITH OF AUXILIARY CONTACTS (1-POLE, OPEN)	0.5 A
HEAT DISSIPATION	3.4 W (at 24 V DC)
INRUSH CURRENT	12.5 A (for 6 ms)
POWER CONSUMPTION	2 W
POWER LOSS	2 W
RATED OPERATIONAL CURRENT (IE)	Max. 0.5 A at signal „1“ DC per channel
RATED OPERATIONAL VOLTAGE	24 V DC (-15 %/+ 20 % - power supply) 24 V DC (transistor outputs) 20.4 - 28.8 V DC (Transistor outputs) 24 V DC (digital inputs) 20.4 - 28.8 V DC
SUPPLY CURRENT	24/44 mA, Normally/max., On 1 signal, Transistor outputs 18/32 mA, Normally/max., On 0 signal, Transistor outputs
SUPPLY VOLTAGE AT DC - MAX	28.8 VDC
SUPPLY VOLTAGE AT DC - MIN	20.4 VDC

10.7 INTERNAL ELECTRICAL CIRCUITS AND CONNECTIONS	Is the panel builder's responsibility.
10.8 CONNECTIONS FOR EXTERNAL CONDUCTORS	Is the panel builder's responsibility.
10.9.2 POWER-FREQUENCY ELECTRIC STRENGTH	Is the panel builder's responsibility.
10.9.3 IMPULSE WITHSTAND VOLTAGE	Is the panel builder's responsibility.
10.9.4 TESTING OF ENCLOSURES MADE OF INSULATING MATERIAL	Is the panel builder's responsibility.
EQUIPMENT HEAT DISSIPATION, CURRENT-DEPENDENT PVID	0 W
HEAT DISSIPATION CAPACITY PDISS	0 W
HEAT DISSIPATION PER POLE, CURRENT-DEPENDENT PVID	0 W
RATED OPERATIONAL CURRENT FOR SPECIFIED HEAT DISSIPATION (IN)	0 A
STATIC HEAT DISSIPATION, NON-CURRENT-DEPENDENT PVS	2 W

Electro magnetic compatibility

AIR DISCHARGE	8 kV
BURST IMPULSE	According to IEC/EN 61000-4-4 2 kV, Supply cable 2 kV, Signal cable
CONTACT DISCHARGE	6 kV
ELECTROMAGNETIC FIELDS	3 V/m at 1.4 - 2 GHz (according to IEC EN 61000-4-3) 10 V/m at 0.8 - 1.0 GHz (according to IEC EN 61000-4-3) 1 V/m at 2.0 - 2.7 GHz (according to IEC EN 61000-4-3)
IMMUNITY TO LINE-CONDUCTED INTERFERENCE	10 V (according to IEC/EN 61000-4-6)
RADIO INTERFERENCE CLASS	Class B (EN 61000-6-3)
SURGE RATING	0.5 kV, Supply cables, symmetrical, power pulses (Surge), EMC According to IEC/EN 61000-4-5, power pulses (Surge), EMC 1 kV, Supply cables, asymmetrical, power pulses (Surge), EMC
VOLTAGE DIPS	20 ms ≤ 10 ms, Bridging voltage dips

Features & functions

FEATURES	Parallel connection of transistor outputs with resistive load, inductive load with external suppressor circuit, combination within a group - Group 1: Q1 to Q4 Networkable (Ethernet) Expandable Display indication of 6 lines x 16 characters
FITTED WITH:	Keypad Display Real time clock Timer
FUNCTIONS	Thermal cutout
INDICATION	LCD-display used as Output status indication of Transistor outputs LCD-display used as status indication of Digital inputs 24 V DC

General information

DEGREE OF PROTECTION	IP20
DISPLAY TEMPERATURE - MAX	55 °C
DISPLAY TEMPERATURE - MIN	0 °C
DISPLAY TYPE	Monochrome
DUTY FACTOR	100 % (Inductive load to EN 60947-5-1, With external suppressor circuit) 100 % (Inductive load to EN 60947-5-1, Without external suppressor circuit, T0.95 = 15 ms, R = 48 Ω, L = 0.24 H) 100 % (Inductive load to EN 60947-5-1, Without external suppressor circuit, DC-13, T0.95 = 72 ms, R = 48 Ω, L = 1.15 H)
FREQUENCY COUNTER	Cable length: ≤ 20 m (screened, Digital inputs 24 V DC) Number: 4 (I1, I2, I3, I4 - Digital inputs 24 V DC) Pulse pause ratio: 1:1 (Digital inputs 24 V DC) Pulse shape: Square (digital inputs 24 V DC) Counter frequency: 5 kHz (Digital inputs 24 V DC)
INSULATION RESISTANCE	According to EN 50178, EN 61010-2-201, UL61010-2-201, CSA-C22.2 NO. 61010-2-201
MOUNTING METHOD	Screw fixing using fixing brackets ZB4-101-GF1 (accessories) Top-hat rail fixing (according to IEC/EN 60715, 35 mm) Front build in possible Wall mounting/direct mounting Rail mounting possible
OPERATING FREQUENCY	Dependent on the cycle time of the basic device Dependent on the cycle- and transmission-time of the expansion devices Depending on the suppressor circuit (Inductive load to EN 60947-5-1, With external suppressor circuit, Max.

Input/Output

ACCURACY	± 2 %, (I5, I6, I7, I8) ± 0.12 V, of actual value, within a single device (Analog Inputs) ± 3 %, of actual value, two easy devices (Analog Inputs) ± 2 s/day, Real-time clock to inputs (± 0.2 hYear) ± 1 %, Repetition accuracy of timing relays (of values)
CONVERSIONS	Each CPU cycle for Analog inputs
DELAY TIME	0.015 ms typ., Digital inputs 24 V DC (I1 - I8), Delay time from 1 to 0, Debounce OFF 20 ms typ., Digital inputs 24 V DC (I1 - I8), Delay time from 1 to 0, Debounce ON 0.015 ms typ., Digital inputs 24 V DC (I1 - I8), Delay time from 0 to 1, Debounce OFF 20 ms typ., Digital inputs 24 V DC (I1 - I8), Delay time from 0 to 1, Debounce ON
INCREMENTAL COUNTER	Pulse pause ratio: 1:1 Pulse shape: Square Value range: -2147483648 to +2147483647 Number of counter inputs: 2 (I1 + I2, I3 + I4) Signal offset: 90° Counter frequency: ≤ 5 kHz
INCREMENTAL ENCODER	Cable length: ≤ 20 m (screened)
INPUT	Voltage (DC)
INPUT CURRENT	1 mA (Analog inputs) 3.3 mA (I1 - I4, at 24 V DC, at signal 1) 2.2 mA (I5 - I8, at 24 V DC, at signal 1) 80 mA
INPUT IMPEDANCE	13.3 kΩ
INPUT VOLTAGE	Status 0: ≤ 15 V DC (I1 - I4, Digital inputs, 24 V DC) Status 0: ≤ 8 V DC (I5 - I8, Digital inputs, 24 V DC) Status 1: ≥ 15 V DC (I1 - I4, Digital inputs, 24 V DC) Signal 0: ≤ 5 V DC (I1 - I8, Digital inputs, 24 V DC)

	switching frequency, max. duty factor)
OVERVOLTAGE CATEGORY	III
POLLUTION DEGREE	2
PRODUCT CATEGORY	Control relays easyE4
PROTOCOL	TCP/IP MODBUS
RESIDUAL CURRENT	0.1 mA (on signal "1" per channel)
RESIDUAL RIPPLE	5 % (transistor outputs) ≤ 5 %
RESOLUTION	• 1 min (Range H:M) • 1 s (Range M:S) • 12 Bit (value 0 - 4095, Analog inputs) • 5 ms (Range S)
SOFTWARE	EASYSOFT-SWLIC/easySoft
TYPE	easyE4 base device
USED WITH	easyE4
VOLTAGE TYPE	DC

LAMP LOAD	Max. 3 W (without Rv per channel)
NUMBER OF INPUTS (ANALOG)	0 4
NUMBER OF INPUTS (DIGITAL)	8
NUMBER OF OUTPUTS (ANALOG)	0
NUMBER OF OUTPUTS (DIGITAL)	4
OUTPUT	Parallel connection of max. 4 Transistor outputs 2 A, Max. total current, Outputs 4 Transistor Outputs Voltage Current
OUTPUT VOLTAGE	U = U _e - 1 V (signal 1 at I _e = 0.5 A, transistor outputs) Max. 2.5 V (at status 0 per channel, transistor outputs)
RAPID COUNTER INPUTS	Pulse pause ratio: 1:1 Counter frequency: ≤ 10 kHz Cable length: ≤ 20 m (shielded) Value range: -2147483648 to +2147483647 Pulse shape: Square Number of rapid counter inputs: 4 (I1, I2, I3, I4)
SIGNAL RANGE	0 - 10 V DC, Analog inputs
UTILIZATION FACTOR	0.25 (Inductive load to EN 60947-5-1, Without external suppressor circuit, DC-13, T0.95 = 72 ms, R = 48 Ω, L = 1.15 H) 0.25 (Inductive load to EN 60947-5-1, Without external suppressor circuit, T0.95 = 15 ms, R = 48 Ω, L = 0.24 H) 1 (Inductive load to EN 60947-5-1, With external suppressor circuit)

Safety

EXPLOSION SAFETY CATEGORY FOR DUST

None

EXPLOSION SAFETY CATEGORY FOR GAS

None

POTENTIAL ISOLATION

Between Transistor outputs and Ethernet: yes
Between Digital inputs 24 V DC and Ethernet: yes
Between Transistor outputs and control buttons: yes
Between Transistor outputs and Power supply: yes
Between Analog inputs and Outputs: yes
Between Transistor outputs and expansion devices: yes
Between Digital inputs 24 V DC and expansion devices: yes
Between Analog inputs and expansion devices: yes
Between Digital inputs 24 V DC: no
Between Transistor outputs and Inputs: yes
Between Transistor outputs: no
Between Digital inputs 24 V DC and Power supply: no
Between Analog inputs: no

Between Analog inputs and Memory card: no
Between Transistor outputs and Memory card: yes
Between Digital inputs 24 V DC and Outputs: yes
Between Analog inputs and Ethernet: yes
Between Digital inputs 24 V DC and Memory card: no

Between Analog inputs and Power supply: no

PROTECTION AGAINST POLARITY REVERSAL

For transistor outputs (Caution: A short circuit will result if 0 V/earth is applied to the outputs in the event that the supply voltage is connected to the wrong poles)

Short-circuit rating

SHORT-CIRCUIT CURRENT

6.8 A, Transistor outputs

SHORT-CIRCUIT PROTECTION

≥ 1 A (T), Fuse, Power supply
Yes, electronic (Q1 - Q4), Transistor outputs

SHORT-CIRCUIT TRIPPING CURRENT

$0.7 \leq I_e \leq 1.7$ per output, For $R_a \leq 10 \text{ m}\Omega$, Depending on number of active channels and their load, Transistor outputs

Yes, for supply voltage
(Siemens MPI optional)

Terminal capacities

SCREWDRIVER SIZE	3.5 x 0.8 mm, Terminal screw
TERMINAL CAPACITY	0.2 - 4 mm ² (AWG 22 - 12), solid 0.2 - 2.5 mm ² (22 - 12 AWG), flexible with ferrule
TIGHTENING TORQUE	0.6 Nm, Screw terminals

Resources

APPLICATION NOTES	eaton-easye4-aws-ap050027-en-us.pdf
CATALOGUES	eaton-product-overview-for-machinery-catalogue-ca08103003zen-en-us.pdf
CHARACTERISTIC CURVE	eaton-electrical-timers-easy-control-relays-characteristic-curve-002.eps
DECLARATIONS OF CONFORMITY	eaton-i-o-expansion-declaration-of-conformity-eu251486en.pdf eaton-i-o-expansion-declaration-of-conformity-uk251130en.pdf
DRAWINGS	eaton-modular-plc-starter-kit-dimensions.eps eaton-general-easy-control-relays-symbol-002.tif eaton-modular-plc-easy-control-relays-3d-drawing.eps
ECAD MODEL	DA-CE-ETN.EASY-E4-DC-12TC1
INSTALLATION INSTRUCTIONS	eaton-easye4-base-programmable-control-relays-il050020zu.pdf
INSTALLATION VIDEOS	Control relay easyE4: The new generation Video easy E4 control relay
MANUALS AND USER GUIDES	eaton-easye-rtd-advanced-training-gh138-mn050015en-us.pdf eaton-easye-easysoft-training-gh135-mn050014en-us.pdf
MCAD MODEL	DA-CS-uc_12rc1 eaton-logic-modules-mcad-drawings-uc-12rc1.dwg
MULTIMEDIA	How to process ModbusRTU devices with the EASY-COM-RTU-M1 module on an easyE4?

[easyE4 SmartWire-DT module with Remote Touch Display and RMQ multi color indicator](#)

[How to connect the Remote Touch Display EASY-RTD to the easyE4?](#)

[Handling of the data logger as a ring buffer with the easyE4 using the ST programming language.](#)

[How to process SmartWire-DT modules using the EASY-COM-SWD-C1 module connected to an easyE4?](#)

[How to connect the easyE4 to the touch panel XV-102 for easy? - 5 Steps](#)

PRODUCT NOTIFICATIONS	MZ049014EN
-----------------------	----------------------------

[eaton-control-relay-easye4-flyer-fl050007en-en-us.pdf](#)

SALES NOTES

[TT-197213 EASY-E4-DC-12TC1 -de DE](#)

[eaton-easy-remote-touch-display-flyer-fl048004en-en-us.pdf](#)

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

DATE:



Eaton Corporation plc Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2026 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

