

Specifications



Photo is representative



Eaton 197622

Eaton Moeller® series DILMT Power contactor, 3 pole, 380 V 400 V: 37 kW, 24 V 50/60 Hz, AC operation, Screw terminals

General specifications

PRODUCT NAME	Eaton Moeller® series DILMT Contactor
---------------------	---------------------------------------

CATALOG NUMBER	197622
-----------------------	--------

MODEL CODE	DILMT80(24V50/60HZ)
-------------------	---------------------

EAN	4015081945016
------------	---------------

PRODUCT LENGTH/DEPTH	124.5 mm
-----------------------------	----------

PRODUCT HEIGHT	111.5 mm
-----------------------	----------

PRODUCT WIDTH	72 mm
----------------------	-------

PRODUCT WEIGHT	1.26 kg
-----------------------	---------

CERTIFICATIONS	EN 60335-1 GB14048 IEC/EN 60947
-----------------------	---------------------------------------

CATALOG NOTES	Not suitable for motors with efficiency class IE3.
----------------------	--



Powering Business Worldwide

Climatic environmental conditions

AMBIENT OPERATING TEMPERATURE - MAX	55 °C
-------------------------------------	-------

AMBIENT STORAGE TEMPERATURE - MAX	80 °C
-----------------------------------	-------

AMBIENT OPERATING TEMPERATURE - MIN	-25 °C
-------------------------------------	--------

AMBIENT STORAGE TEMPERATURE - MIN	-40 °C
-----------------------------------	--------

CLIMATIC PROOFING	Damp heat, constant, to IEC 60068-2-78 Damp heat, cyclic, to IEC 60068-2-30
-------------------	--

Electrical rating

RATED BREAKING CAPACITY AT 380/400 V	640 A
--------------------------------------	-------

RATED INSULATION VOLTAGE (UI)	690 V
-------------------------------	-------

RATED OPERATIONAL CURRENT (IE) AT AC-1, 380 V, 400 V, 415 V	110 A
---	-------

RATED OPERATIONAL CURRENT (IE) AT AC-3, 220 V, 230 V, 240 V	80 A
---	------

RATED OPERATIONAL CURRENT (IE) AT AC-3, 380 V, 400 V, 415 V	80 A
---	------

RATED OPERATIONAL POWER AT AC-3, 380/400 V, 50 HZ	37 kW
---	-------

RATED OPERATIONAL POWER AT AC-3, 690 V, 50 HZ	37 kW
---	-------

RATED OPERATIONAL VOLTAGE (UE) AT AC - MAX	690 V
--	-------

Contacts

NUMBER OF AUXILIARY CONTACTS (NORMALLY CLOSED CONTACTS)	0
---	---

NUMBER OF AUXILIARY CONTACTS (NORMALLY OPEN CONTACTS)	0
---	---

Features & functions

NUMBER OF POLES	Three-pole
-----------------	------------

General information

APPLICATION	Contactors for Motors
CONNECTION	Screw terminals
CONNECTION TO SMARTWIRE-DT	No
DEGREE OF PROTECTION	IP20
FRAME SIZE	FS4
LIFESPAN, ELECTRICAL	900,000 Operations (at 400V, AC-3)
LIFESPAN, MECHANICAL	5,000,000 Operations (AC operated)
OPERATING FREQUENCY	3600 mechanical Operations/h (AC operated)
OVERVOLTAGE CATEGORY	III
POLLUTION DEGREE	3
PRODUCT CATEGORY	Contactors
RATED IMPULSE WITHSTAND VOLTAGE (UIMP)	6000 V AC
USED WITH	DILMT95-XHI11-SR and DILT-XHI01(10)
UTILIZATION CATEGORY	AC-4: Normal AC induction motors: starting, plugging, reversing, inching AC-3: Normal AC induction motors: starting, switch off during running AC-1: Non-inductive or slightly inductive loads, resistance furnaces
VOLTAGE TYPE	AC

Magnet system

PICK-UP VOLTAGE	0.85 - 1.1 V AC x U _c
POWER CONSUMPTION, PICK-UP, 50 HZ	0 VA, Dual-frequency coil in a cold state and 1.0 x U _s 350 VA, Dual-frequency coil in a cold state and 1.0 x U _s
POWER CONSUMPTION, PICK-UP, 60 HZ	0 VA, Dual-frequency coil in a cold state and 1.0 x U _s 350 VA, Dual-frequency coil in a cold state and 1.0 x U _s
POWER CONSUMPTION, SEALING, 50 HZ	8 W, Dual-frequency coil in a cold state and 1.0 x U _s 0 W, Dual-frequency coil in a cold state and 1.0 x U _s 9 VA, Coil in a cold state and 1.0 x U _s
POWER CONSUMPTION, SEALING, 60 HZ	0 VA, Dual-frequency coil in a cold state and 1.0 x U _s , at 60 Hz 8 W, Dual-frequency coil in a cold state and 1.0 x U _s 26 VA, Dual-frequency coil in a cold state and 1.0 x U _s , at 60 Hz 0 W, Dual-frequency coil in a cold state and 1.0 x U _s
RATED CONTROL SUPPLY VOLTAGE (US) AT AC, 50 HZ - MAX	24 V
RATED CONTROL SUPPLY VOLTAGE (US) AT AC, 50 HZ - MIN	24 V
RATED CONTROL SUPPLY VOLTAGE (US) AT AC, 60 HZ - MAX	24 V
RATED CONTROL SUPPLY VOLTAGE (US) AT AC, 60 HZ - MIN	24 V

Terminal capacities

SCREW SIZE	M3.5, Terminal screw
	M8, Terminal screw
SCREWDRIVER SIZE	4 mm AF, Hexagon socket-head spanner, Terminal screw
	2, Terminal screw, Pozidriv screwdriver
STRIPPING LENGTH (MAIN CABLE)	16 mm
TERMINAL CAPACITY (SOLID)	1 x (6 - 50) mm ² , Main cables
	2 x (0.75 - 2.5) mm ²
	2 x (6 - 25) mm ² , Main cables
	1 x (0.75 - 2.5) mm ²
TERMINAL CAPACITY (STRANDED)	1 x (6 - 50) mm ²
	2 x (6 - 25) mm ² , Main cables
TIGHTENING TORQUE	6 Nm, Screw terminals
	1.2 Nm, Screw terminals

Resources

BROCHURES	eaton-dilat-dilmt-contactors-zbt-motor-protection-relay-brochure-br034003en-en-us.pdf
	eaton-powerxl-variable-frequency-drives-hvac-brochure-br040012en-en-us.pdf
DRAWINGS	eaton-contactors-contactor-dimensions-006.eps
	eaton-contactors-contactor-dimensions-004.eps
	eaton-general-mounting-contactor-3d-drawing.eps
	eaton-contactors-contactor-3d-drawing-003.eps
ECAD MODEL	DA-CE-ETN.DILMT80(24V50_60HZ)
INSTALLATION INSTRUCTIONS	IL034052ZU
WIRING DIAGRAMS	eaton-contactors-contact-dilm-wiring-diagram-003.eps

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

DATE:



Eaton Corporation plc Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2026 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

