

Specifications



Eaton 199208

Eaton Moeller® series DILA Contactor relay, 24 V DC, 4 N/O, Push in terminals, DC operation

General specifications

PRODUCT NAME	Eaton Moeller® series DILA Control relay
CATALOG NUMBER	199208
MODEL CODE	DILA-40(24VDC)-PI
EAN	4015081972920
PRODUCT LENGTH/DEPTH	75 mm
PRODUCT HEIGHT	68 mm
PRODUCT WIDTH	45 mm
PRODUCT WEIGHT	0.287 kg

CERTIFICATIONS	IEC/EN 60947 EN 60947-5-1 VDE 0660 CSA File No.: 012528 CSA Class No.: 3211-03 UL File No.: E29184 UL 508 CSA-C22.2 No. 14-05 CE marking UL Category Control No.: NKCR UL CSA
-----------------------	--

Climatic environmental conditions

AMBIENT OPERATING TEMPERATURE - MAX	60 °C
AMBIENT STORAGE TEMPERATURE - MAX	80 °C
AMBIENT OPERATING TEMPERATURE - MIN	-25 °C
AMBIENT OPERATING TEMPERATURE (ENCLOSED) - MAX	40 °C
AMBIENT OPERATING TEMPERATURE (ENCLOSED) - MIN	25 °C
AMBIENT STORAGE TEMPERATURE - MIN	40 °C
CLIMATIC PROOFING	Damp heat, constant, to IEC 60068-2-78 Damp heat, cyclic, to IEC 60068-2-30

Contacts

CODE NUMBER	40E
CONTROL CIRCUIT RELIABILITY	$\lambda < 5 \times 10^{-7}$ (1 failure at 2,000,000 operations for $U_e = 24$ V DC, $U_{min} = 17$ V, $I_{min} = 5.4$ mA) $\lambda < 5 \times 1/10^7$ (1 failure at 2,000,000 operations for $U_e = 24$ V DC, $U_{min} = 17$ V, $I_{min} = 5.4$ mA)
NUMBER OF AUXILIARY CONTACTS (CHANGE-OVER CONTACTS)	0
NUMBER OF AUXILIARY CONTACTS (NORMALLY CLOSED CONTACTS)	0
NUMBER OF AUXILIARY CONTACTS (NORMALLY OPEN CONTACTS)	4
NUMBER OF CONTACTS (NORMALLY CLOSED CONTACTS)	0
NUMBER OF CONTACTS (NORMALLY OPEN CONTACTS)	4

Communication

CONNECTION TO SMARTWIRE-DT	In conjunction with DIL-SWD SmartWire DT contactor module Yes
----------------------------	--

Design verification

10.10 TEMPERATURE RISE	The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.
10.11 SHORT-CIRCUIT RATING	Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.12 ELECTROMAGNETIC COMPATIBILITY	Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.13 MECHANICAL FUNCTION	The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.
10.2.2 CORROSION RESISTANCE	Meets the product standard's requirements.
10.2.3.1 VERIFICATION OF THERMAL STABILITY OF ENCLOSURES	Meets the product standard's requirements.
10.2.3.2 VERIFICATION OF RESISTANCE OF INSULATING MATERIALS TO NORMAL HEAT	Meets the product standard's requirements.

10.2.3.3 RESIST. OF INSUL. MAT. TO ABNORMAL HEAT/FIRE BY INTERNAL ELECT. EFFECTS	Meets the product standard's requirements.
10.2.4 RESISTANCE TO ULTRA-VIOLET (UV) RADIATION	Meets the product standard's requirements.
10.2.5 LIFTING	Does not apply, since the entire switchgear needs to be evaluated.
10.2.6 MECHANICAL IMPACT	Does not apply, since the entire switchgear needs to be evaluated.
10.2.7 INSCRIPTIONS	Meets the product standard's requirements.
10.3 DEGREE OF PROTECTION OF ASSEMBLIES	Does not apply, since the entire switchgear needs to be evaluated.
10.4 CLEARANCES AND CREEPAGE DISTANCES	Meets the product standard's requirements.
10.5 PROTECTION AGAINST ELECTRIC SHOCK	Does not apply, since the entire switchgear needs to be evaluated.
10.6 INCORPORATION OF SWITCHING DEVICES AND COMPONENTS	Does not apply, since the entire switchgear needs to be evaluated.
10.7 INTERNAL ELECTRICAL CIRCUITS AND CONNECTIONS	Is the panel builder's responsibility.
10.8 CONNECTIONS FOR EXTERNAL CONDUCTORS	Is the panel builder's responsibility.
10.9.2 POWER-FREQUENCY ELECTRIC STRENGTH	Is the panel builder's responsibility.
10.9.3 IMPULSE WITHSTAND VOLTAGE	Is the panel builder's responsibility.
10.9.4 TESTING OF ENCLOSURES MADE OF INSULATING MATERIAL	Is the panel builder's responsibility.
EQUIPMENT HEAT DISSIPATION, CURRENT-DEPENDENT PVID	0 W
HEAT DISSIPATION CAPACITY PDISS	0 W

Electrical rating

RATED INSULATION VOLTAGE (UI)

690 V

RATED OPERATIONAL CURRENT (IE)

6 A at 60 V, DC L/R $\leq$ 15 ms (with 1 contact in series)
 5 A at 220 V, DC L/R $\leq$ 15 ms (with 3 contacts in series)
 10 A at 60 V, DC L/R $\leq$ 15 ms (with 2 contacts in series)
 1 A at 220 V, DC L/R $\leq$ 50 ms (with 3 contacts in series)
 6 A at 110 V, DC L/R $\leq$ 15 ms (with 3 contacts in series)
 2 A at 110 V, DC L/R $\leq$ 50 ms (with 3 contacts in series)
 3 A at 110 V, DC L/R $\leq$ 15 ms (with 1 contact in series)
 1 A at 220 V, DC L/R $\leq$ 15 ms (with 1 contact in series)
 4 A at 60 V, DC L/R $\leq$ 50 ms (with 3 contacts in series)
 10 A at 24 V, DC L/R $\leq$ 15 ms (with 1 contact in series)
 4 A at 24 V, DC L/R $\leq$ 50 ms (with 3 contacts in series)
 16 A

RATED OPERATIONAL CURRENT (IE) AT AC-15, 220 V, 230 V, 240 V

4 A

RATED OPERATIONAL CURRENT (IE) AT AC-15, 380 V, 400 V, 415 V

4 A

RATED OPERATIONAL CURRENT (IE) AT AC-15, 500 V

1.5 A

RATED OPERATIONAL VOLTAGE (UE) AT AC - MAX

690 V

SAFE ISOLATION

400 V AC, Between auxiliary contacts, According to EN 61140
 400 V AC, Between coil and auxiliary contacts, According to EN 61140

SHORT-CIRCUIT PROTECTION RATING WITHOUT WELDING

10 A gG/gL, 500 V, Max. Fuse, Contacts

SWITCHING CAPACITY

15 A, 600 V AC, (UL/CSA)

Features & functions

FEATURES

Positive operating contacts to EN 60947-5-1 appendix L, including auxiliary contact module

FITTED WITH:

Built-in suppressor circuit
 Varistor suppressor circuit
 Positive operation contacts
 Suppressor circuit

(AUXILIARY CONTACTS, GENERAL USE)	1 A, 250 V DC, (UL/CSA)
SWITCHING CAPACITY (AUXILIARY CONTACTS, PILOT DUTY)	A600, AC operated (UL/CSA) P300, DC operated (UL/CSA)

General information	
APPLICATION	Contact relays
CONNECTION	Push in terminals
DEGREE OF PROTECTION	IP20
LIFESPAN, MECHANICAL	20,000,000 Operations (DC operated)
MOUNTING METHOD	DIN-rail/screw
OPERATING FREQUENCY	9000 Operations/h
OVERVOLTAGE CATEGORY	III
POLLUTION DEGREE	3
PRODUCT CATEGORY	DILA relays
PROTECTION	Finger and back-of-hand proof, Protection against direct contact when actuated from front (EN 50274)
RATED IMPULSE WITHSTAND VOLTAGE (UIMP)	6000 V AC
SHOCK RESISTANCE	5 g, N/C auxiliary contact, Basic unit with auxiliary contact module, Mechanical, according to IEC/EN 60068-2-27, Half-sinusoidal shock 10 ms 7 g, N/O auxiliary contact, Basic unit with auxiliary contact module, Mechanical, according to IEC/EN 60068-2-27, Half-sinusoidal shock 10 ms
VOLTAGE TYPE	DC

Magnet system	
DUTY FACTOR	100 %
PICK-UP VOLTAGE	0.8 - 1.1 V DC x U _c 0.7 - 1.3 V DC x U _c (at 24 V: without auxiliary contact module and at ambient air temperature + 40 °C)
RATED CONTROL SUPPLY VOLTAGE (US) AT DC - MAX	24 V
RATED CONTROL SUPPLY VOLTAGE (US) AT DC - MIN	24 V
SWITCHING TIME (DC OPERATED, MAKE CONTACTS, CLOSING DELAY) - MAX	31 ms
SWITCHING TIME (DC OPERATED, MAKE CONTACTS, OPENING DELAY) - MAX	12 ms
VOLTAGE TOLERANCE	Smoothed DC, three-phase bridge rectifiers or smoothed double-wave rectification

Terminal capacities

SCREWDRIVER SIZE	3.0 x 0.5 mm, Terminal screw
STRIPPING LENGTH (MAIN CABLE)	10 mm
TERMINAL CAPACITY (FLEXIBLE WITH FERRULE)	2 x (0.5 - 1.5) mm ² 1 x (0.5 - 2.5) mm ²
TERMINAL CAPACITY (SOLID)	1 x (0.5 - 2.5) mm ² 2 x (0.5 - 2.5) mm ²
TERMINAL CAPACITY (SOLID/STRANDED AWG)	20 - 14
TERMINAL CAPACITY (FLEXIBLE)	1 x (0.5 - 2.5) mm ² 2 x (0.5 - 2.5) mm ²

Resources

CATALOGUES	eaton-product-overview-for-machinery-catalogue-ca08103003zen-en-us.pdf Product Range Catalog Switching and protecting motors
DECLARATIONS OF CONFORMITY	eaton-control-relay-declaration-of-conformity-eu250722en.pdf eaton-control-relay-declaration-of-conformity-uk251205en.pdf
DRAWINGS	eaton-contactors-dimensions-007.eps
ECAD MODEL	ETN.199208.edz
INSTALLATION VIDEOS	WIN-WIN with push-in technology
MCAD MODEL	eaton-iec-contactors-mcad-3d-models-dil-m7-15-pi.stp eaton-iec-contactors-mcad-drawings-dil-m7-15-pi.dwg

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

DATE:



Eaton Corporation plc Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2026 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

