

# Specifications



## Eaton 199913

Eaton Moeller® series P1 Main switch, 40 A, surface mounting, 3 pole, 1 N/O, 1 N/C, STOP function, With black rotary handle and locking ring, Lockable in the 0 (Off) position

### General specifications

|                             |                                                                       |
|-----------------------------|-----------------------------------------------------------------------|
| <b>PRODUCT NAME</b>         | Eaton Moeller® series P1 Main switch                                  |
| <b>CATALOG NUMBER</b>       | 199913                                                                |
| <b>MODEL CODE</b>           | P1-40/I2/SVB-SW/HI11                                                  |
| <b>EAN</b>                  | 4015082953362                                                         |
| <b>PRODUCT LENGTH/DEPTH</b> | 115 mm                                                                |
| <b>PRODUCT HEIGHT</b>       | 180 mm                                                                |
| <b>PRODUCT WIDTH</b>        | 100 mm                                                                |
| <b>PRODUCT WEIGHT</b>       | 0.596 kg                                                              |
| <b>COMPLIANCES</b>          | UKCA<br>CE                                                            |
| <b>CERTIFICATIONS</b>       | IEC/EN 60947<br>IEC/EN 60947-3<br>IEC/EN 60204                        |
| <b>CATALOG NOTES</b>        | Rated Short-time<br>Withstand Current (Icw)<br>for a time of 1 second |



Powering Business Worldwide

## Actuator

|                       |                            |
|-----------------------|----------------------------|
| <b>ACTUATOR COLOR</b> | Black                      |
| <b>ACTUATOR TYPE</b>  | Door coupling rotary drive |

## Contacts

|                                                                |                                                                                         |
|----------------------------------------------------------------|-----------------------------------------------------------------------------------------|
| <b>CONTROL CIRCUIT RELIABILITY</b>                             | 1 failure per 100,000 switching operations statistically determined, at 24 V DC, 10 mA) |
| <b>NUMBER OF AUXILIARY CONTACTS (CHANGE-OVER CONTACTS)</b>     | 0                                                                                       |
| <b>NUMBER OF AUXILIARY CONTACTS (NORMALLY CLOSED CONTACTS)</b> | 1                                                                                       |
| <b>NUMBER OF AUXILIARY CONTACTS (NORMALLY OPEN CONTACTS)</b>   | 1                                                                                       |

## Climatic environmental conditions

|                                                       |                                                                                |
|-------------------------------------------------------|--------------------------------------------------------------------------------|
| <b>AMBIENT OPERATING TEMPERATURE - MAX</b>            | 40 °C                                                                          |
| <b>AMBIENT OPERATING TEMPERATURE - MIN</b>            | -25 °C                                                                         |
| <b>AMBIENT OPERATING TEMPERATURE (ENCLOSED) - MAX</b> | 40 °C                                                                          |
| <b>AMBIENT OPERATING TEMPERATURE (ENCLOSED) - MIN</b> | -25 °C                                                                         |
| <b>CLIMATIC PROOFING</b>                              | Damp heat, constant, to IEC 60068-2-78<br>Damp heat, cyclic, to IEC 60068-2-30 |

## Design verification

|                                                                                         |                                                                                                                                  |
|-----------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------|
| <b>10.10 TEMPERATURE RISE</b>                                                           | The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices. |
| <b>10.11 SHORT-CIRCUIT RATING</b>                                                       | Is the panel builder's responsibility. The specifications for the switchgear must be observed.                                   |
| <b>10.12 ELECTROMAGNETIC COMPATIBILITY</b>                                              | Is the panel builder's responsibility. The specifications for the switchgear must be observed.                                   |
| <b>10.13 MECHANICAL FUNCTION</b>                                                        | The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.                         |
| <b>10.2.2 CORROSION RESISTANCE</b>                                                      | Meets the product standard's requirements.                                                                                       |
| <b>10.2.3.1 VERIFICATION OF THERMAL STABILITY OF ENCLOSURES</b>                         | Meets the product standard's requirements.                                                                                       |
| <b>10.2.3.2 VERIFICATION OF RESISTANCE OF INSULATING MATERIALS TO NORMAL HEAT</b>       | Meets the product standard's requirements.                                                                                       |
| <b>10.2.3.3 RESIST. OF INSUL. MAT. TO ABNORMAL HEAT/FIRE BY INTERNAL ELECT. EFFECTS</b> | Meets the product standard's requirements.                                                                                       |

|                                                                      |                                                                    |
|----------------------------------------------------------------------|--------------------------------------------------------------------|
| <b>10.2.4 RESISTANCE TO ULTRA-VIOLET (UV) RADIATION</b>              | UV resistance only in connection with protective shield.           |
| <b>10.2.5 LIFTING</b>                                                | Does not apply, since the entire switchgear needs to be evaluated. |
| <b>10.2.6 MECHANICAL IMPACT</b>                                      | Does not apply, since the entire switchgear needs to be evaluated. |
| <b>10.2.7 INSCRIPTIONS</b>                                           | Meets the product standard's requirements.                         |
| <b>10.3 DEGREE OF PROTECTION OF ASSEMBLIES</b>                       | Does not apply, since the entire switchgear needs to be evaluated. |
| <b>10.4 CLEARANCES AND CREEPAGE DISTANCES</b>                        | Meets the product standard's requirements.                         |
| <b>10.5 PROTECTION AGAINST ELECTRIC SHOCK</b>                        | Does not apply, since the entire switchgear needs to be evaluated. |
| <b>10.6 INCORPORATION OF SWITCHING DEVICES AND COMPONENTS</b>        | Does not apply, since the entire switchgear needs to be evaluated. |
| <b>10.7 INTERNAL ELECTRICAL CIRCUITS AND CONNECTIONS</b>             | Is the panel builder's responsibility.                             |
| <b>10.8 CONNECTIONS FOR EXTERNAL CONDUCTORS</b>                      | Is the panel builder's responsibility.                             |
| <b>10.9.2 POWER-FREQUENCY ELECTRIC STRENGTH</b>                      | Is the panel builder's responsibility.                             |
| <b>10.9.3 IMPULSE WITHSTAND VOLTAGE</b>                              | Is the panel builder's responsibility.                             |
| <b>10.9.4 TESTING OF ENCLOSURES MADE OF INSULATING MATERIAL</b>      | Is the panel builder's responsibility.                             |
| <b>EQUIPMENT HEAT DISSIPATION, CURRENT-DEPENDENT PVID</b>            | 0 W                                                                |
| <b>HEAT DISSIPATION CAPACITY PDISS</b>                               | 0 W                                                                |
| <b>HEAT DISSIPATION PER POLE, CURRENT-DEPENDENT PVID</b>             | 3.5 W                                                              |
| <b>RATED OPERATIONAL CURRENT FOR SPECIFIED HEAT DISSIPATION (IN)</b> | 40 A                                                               |
| <b>STATIC HEAT DISSIPATION, NON-CURRENT-DEPENDENT PVS</b>            | 0 W                                                                |

## Electrical rating

|                                                                              |        |
|------------------------------------------------------------------------------|--------|
| <b>RATED BREAKING<br/>CAPACITY AT 400/415 V<br/>(COS PHI TO IEC 60947-3)</b> | 290 kA |
|------------------------------------------------------------------------------|--------|

|                                                                              |        |
|------------------------------------------------------------------------------|--------|
| <b>RATED BREAKING<br/>CAPACITY AT 660/690 V<br/>(COS PHI TO IEC 60947-3)</b> | 130 kA |
|------------------------------------------------------------------------------|--------|

|                                                               |      |
|---------------------------------------------------------------|------|
| <b>RATED OPERATIONAL<br/>CURRENT (IE) AT AC-21,<br/>440 V</b> | 40 A |
|---------------------------------------------------------------|------|

|                                                                |      |
|----------------------------------------------------------------|------|
| <b>RATED OPERATIONAL<br/>CURRENT (IE) AT AC-23A,<br/>230 V</b> | 40 A |
|----------------------------------------------------------------|------|

|                                                                       |      |
|-----------------------------------------------------------------------|------|
| <b>RATED OPERATIONAL<br/>CURRENT (IE) AT AC-23A,<br/>400 V, 415 V</b> | 40 A |
|-----------------------------------------------------------------------|------|

|                                                                |      |
|----------------------------------------------------------------|------|
| <b>RATED OPERATIONAL<br/>CURRENT (IE) AT AC-23A,<br/>690 V</b> | 20 A |
|----------------------------------------------------------------|------|

|                                                                            |      |
|----------------------------------------------------------------------------|------|
| <b>RATED OPERATIONAL<br/>CURRENT (IE) AT AC-3,<br/>220 V, 230 V, 240 V</b> | 30 A |
|----------------------------------------------------------------------------|------|

|                                                                            |      |
|----------------------------------------------------------------------------|------|
| <b>RATED OPERATIONAL<br/>CURRENT (IE) AT AC-3,<br/>380 V, 400 V, 415 V</b> | 30 A |
|----------------------------------------------------------------------------|------|

|                                                                     |      |
|---------------------------------------------------------------------|------|
| <b>RATED OPERATIONAL<br/>CURRENT (IE) AT AC-3,<br/>660 V, 690 V</b> | 17 A |
|---------------------------------------------------------------------|------|

|                                                                    |       |
|--------------------------------------------------------------------|-------|
| <b>RATED OPERATIONAL<br/>POWER AT AC-23A,<br/>220/230 V, 50 HZ</b> | 11 kW |
|--------------------------------------------------------------------|-------|

|                                                                |       |
|----------------------------------------------------------------|-------|
| <b>RATED OPERATIONAL<br/>POWER AT AC-23A, 400 V,<br/>50 HZ</b> | 22 kW |
|----------------------------------------------------------------|-------|

|                                                                |         |
|----------------------------------------------------------------|---------|
| <b>RATED OPERATIONAL<br/>POWER AT AC-23A, 690 V,<br/>50 HZ</b> | 18.5 kW |
|----------------------------------------------------------------|---------|

|                                                                  |       |
|------------------------------------------------------------------|-------|
| <b>RATED OPERATIONAL<br/>POWER AT AC-3, 380/400<br/>V, 50 HZ</b> | 15 kW |
|------------------------------------------------------------------|-------|

|                                                              |       |
|--------------------------------------------------------------|-------|
| <b>RATED OPERATIONAL<br/>POWER AT AC-3, 415 V, 50<br/>HZ</b> | 15 kW |
|--------------------------------------------------------------|-------|

|                                                              |       |
|--------------------------------------------------------------|-------|
| <b>RATED OPERATIONAL<br/>POWER AT AC-3, 690 V, 50<br/>HZ</b> | 15 kW |
|--------------------------------------------------------------|-------|

|                                                           |       |
|-----------------------------------------------------------|-------|
| <b>RATED OPERATIONAL<br/>VOLTAGE (UE) AT AC -<br/>MAX</b> | 690 V |
|-----------------------------------------------------------|-------|

|                                             |      |
|---------------------------------------------|------|
| <b>RATED UNINTERRUPTED<br/>CURRENT (IU)</b> | 40 A |
|---------------------------------------------|------|

|                      |                     |
|----------------------|---------------------|
| <b>UNINTERRUPTED</b> | Rated uninterrupted |
|----------------------|---------------------|

## Features & functions

|                           |               |
|---------------------------|---------------|
| <b>ENCLOSURE MATERIAL</b> | Polycarbonate |
|---------------------------|---------------|

|                 |                                                                      |
|-----------------|----------------------------------------------------------------------|
| <b>FEATURES</b> | Version as main switch<br>Version as maintenance-<br>/service switch |
|-----------------|----------------------------------------------------------------------|

|                     |                                         |
|---------------------|-----------------------------------------|
| <b>FITTED WITH:</b> | Black rotary handle and<br>locking ring |
|---------------------|-----------------------------------------|

|                  |                                |
|------------------|--------------------------------|
| <b>FUNCTIONS</b> | STOP function<br>Interlockable |
|------------------|--------------------------------|

|                         |                                     |
|-------------------------|-------------------------------------|
| <b>LOCKING FACILITY</b> | Lockable in the 0 (Off)<br>position |
|-------------------------|-------------------------------------|

|                        |   |
|------------------------|---|
| <b>NUMBER OF POLES</b> | 3 |
|------------------------|---|

|                |                                                             |
|----------------|-------------------------------------------------------------|
| <b>CURRENT</b> | current I <sub>u</sub> is specified for max. cross-section. |
|----------------|-------------------------------------------------------------|

## General information

|                                               |                                                                               |
|-----------------------------------------------|-------------------------------------------------------------------------------|
| <b>ACCESSORIES</b>                            | Auxiliary contact or neutral conductor fitted by user.                        |
| <b>DEGREE OF PROTECTION</b>                   | IP65                                                                          |
| <b>DEGREE OF PROTECTION (FRONT SIDE)</b>      | IP65                                                                          |
| <b>LIFESPAN, MECHANICAL</b>                   | 300,000 Operations                                                            |
| <b>MOUNTING METHOD</b>                        | Surface mounting                                                              |
| <b>MOUNTING POSITION</b>                      | As required                                                                   |
| <b>OPERATING FREQUENCY</b>                    | 50 Operations/h                                                               |
| <b>OVERVOLTAGE CATEGORY</b>                   | III                                                                           |
| <b>POLLUTION DEGREE</b>                       | 3                                                                             |
| <b>PRODUCT CATEGORY</b>                       | Main switch                                                                   |
| <b>RATED IMPULSE WITHSTAND VOLTAGE (UIMP)</b> | 6000 V AC                                                                     |
| <b>SAFE ISOLATION</b>                         | 440 V AC, Between the contacts, According to EN 61140                         |
| <b>SHOCK RESISTANCE</b>                       | 15 g, Mechanical, According to IEC/EN 60068-2-27, Half-sinusoidal shock 20 ms |
| <b>SWITCHING ANGLE</b>                        | 90 °                                                                          |

## Switching capacity

|                    |                                                                                                                                                                                                                                               |
|--------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>LOAD RATING</b> | 1.3 x I <sub>e</sub> (with intermittent operation class 12, 60 % duty factor)<br>1.6 x I <sub>e</sub> (with intermittent operation class 12, 40 % duty factor)<br>2 x I <sub>e</sub> (with intermittent operation class 12, 25 % duty factor) |
|--------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|

## Short-circuit rating

|                                                     |                                      |
|-----------------------------------------------------|--------------------------------------|
| <b>RATED CONDITIONAL SHORT-CIRCUIT CURRENT (IQ)</b> | 80 kA                                |
| <b>RATED SHORT-TIME WITHSTAND CURRENT (ICW)</b>     | 0.64 kA<br>640 A, Contacts, 1 second |
| <b>SHORT-CIRCUIT PROTECTION RATING</b>              | 50 A gG/gL, Fuse, Contacts           |

## Terminal capacities

|                          |                                                                                                                                                                                                                                  |
|--------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>SCREW SIZE</b>        | M4, Terminal screw                                                                                                                                                                                                               |
| <b>TERMINAL CAPACITY</b> | 1 x (1 - 4) mm <sup>2</sup> , flexible with ferrules to DIN 46228<br>2 x (1 - 4) mm <sup>2</sup> , flexible with ferrules to DIN 46228<br>1 x 10 mm <sup>2</sup> with fork terminal<br>2 x 10 mm <sup>2</sup> with fork terminal |
| <b>TIGHTENING TORQUE</b> | 1.6 Nm, Screw terminals                                                                                                                                                                                                          |

## Resources

|                            |                                                                                       |
|----------------------------|---------------------------------------------------------------------------------------|
| BROCHURES                  | <a href="#">P1-40 Switch-disconnectors brochure</a>                                   |
|                            | <a href="#">Brochure - T Rotary Cam switch and P Switch-disconnector</a>              |
| CATALOGUES                 | <a href="#">P1-40 Switch-disconnectors</a>                                            |
|                            | <a href="#">P Switch-disconnectors and T Rotary cam switches catalogue CA042001EN</a> |
| DECLARATIONS OF CONFORMITY | <a href="#">eaton-main-switch-declaration-of-conformity-eu250806en.pdf</a>            |
|                            | <a href="#">eaton-main-switch-declaration-of-conformity-uk251289en.pdf</a>            |
| ECAD MODEL                 | <a href="#">ETN.199913.edz</a>                                                        |
| INSTALLATION INSTRUCTIONS  | <a href="#">eaton-switch-discon-p1-insulated-enclosure-il03802001z.pdf</a>            |
| INSTALLATION VIDEOS        | <a href="#">Eaton's P Switch-disconnectors used in a factory</a>                      |
| MCAD MODEL                 | <a href="#">eaton-erd-mcad-3d-models-p1-i2-svb.stp</a>                                |
|                            | <a href="#">eaton-erd-mcad-drawings-p1-i2-svb.dwg</a>                                 |
| MULTIMEDIA                 | <a href="#">Unboxing Video P140</a>                                                   |
| PEP ECO-PASSPORT           | <a href="#">eaton-enclosed-rotary-disconnects-pep-eato-00155-v0101-en.pdf</a>         |

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

DATE:



**Eaton Corporation plc** Eaton House  
30 Pembroke Road  
Dublin 4, Ireland  
Eaton.com

© 2026 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

