

Specifications



Photo is representative

Eaton 207266

Eaton Moeller® series T5
Changeoverswitches, T5, 100 A, surface
mounting, 3 contact unit(s), Contacts: 6, 60 °,
maintained, With 0 (Off) position, 1-0-2,
Design number 8212

General specifications

PRODUCT NAME	Eaton Moeller® series T5 Changeover switch
CATALOG NUMBER	207266
MODEL CODE	T5-3-8212/I5
EAN	4015082072667
PRODUCT LENGTH/DEPTH	280 mm
PRODUCT HEIGHT	197 mm
PRODUCT WIDTH	200 mm
PRODUCT WEIGHT	2.018 kg
CERTIFICATIONS	IEC 60947 EN 60204 EN 60947 VDE IEC/EN 60947 IEC/EN 60947-3 VDE 0660 IEC/EN 60204
CATALOG NOTES	Rated Short-time Withstand Current (Icw) for a time of 1 second



Powering Business Worldwide

Actuator

ACTUATOR FUNCTION	Maintained With 0 (Off) position
ACTUATOR TYPE	Short thumb-grip

Contacts

CONTROL CIRCUIT RELIABILITY	1 failure per 100,000 switching operations statistically determined, at 24 V DC, 10 mA)
NUMBER OF AUXILIARY CONTACTS (CHANGE-OVER CONTACTS)	0
NUMBER OF AUXILIARY CONTACTS (NORMALLY CLOSED CONTACTS)	0
NUMBER OF AUXILIARY CONTACTS (NORMALLY OPEN CONTACTS)	0
NUMBER OF CONTACTS	6

Climatic environmental conditions

AMBIENT OPERATING TEMPERATURE - MAX	40 °C
AMBIENT OPERATING TEMPERATURE - MIN	-25 °C
AMBIENT OPERATING TEMPERATURE (ENCLOSED) - MAX	40 °C
AMBIENT OPERATING TEMPERATURE (ENCLOSED) - MIN	-25 °C
CLIMATIC PROOFING	Damp heat, cyclic, to IEC 60068-2-30 Damp heat, constant, to IEC 60068-2-78

Design verification

10.10 TEMPERATURE RISE	The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.
10.11 SHORT-CIRCUIT RATING	Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.12 ELECTROMAGNETIC COMPATIBILITY	Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.13 MECHANICAL FUNCTION	The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.
10.2.2 CORROSION RESISTANCE	Meets the product standard's requirements.
10.2.3.1 VERIFICATION OF THERMAL STABILITY OF ENCLOSURES	Meets the product standard's requirements.
10.2.3.2 VERIFICATION OF RESISTANCE OF INSULATING MATERIALS TO NORMAL HEAT	Meets the product standard's requirements.
10.2.3.3 RESIST. OF INSUL. MAT. TO ABNORMAL HEAT/FIRE BY INTERNAL ELECT. EFFECTS	Meets the product standard's requirements.

10.2.4 RESISTANCE TO ULTRA-VIOLET (UV) RADIATION	UV resistance only in connection with protective shield.
10.2.5 LIFTING	Does not apply, since the entire switchgear needs to be evaluated.
10.2.6 MECHANICAL IMPACT	Does not apply, since the entire switchgear needs to be evaluated.
10.2.7 INSCRIPTIONS	Meets the product standard's requirements.
10.3 DEGREE OF PROTECTION OF ASSEMBLIES	Does not apply, since the entire switchgear needs to be evaluated.
10.4 CLEARANCES AND CREEPAGE DISTANCES	Meets the product standard's requirements.
10.5 PROTECTION AGAINST ELECTRIC SHOCK	Does not apply, since the entire switchgear needs to be evaluated.
10.6 INCORPORATION OF SWITCHING DEVICES AND COMPONENTS	Does not apply, since the entire switchgear needs to be evaluated.
10.7 INTERNAL ELECTRICAL CIRCUITS AND CONNECTIONS	Is the panel builder's responsibility.
10.8 CONNECTIONS FOR EXTERNAL CONDUCTORS	Is the panel builder's responsibility.
10.9.2 POWER-FREQUENCY ELECTRIC STRENGTH	Is the panel builder's responsibility.
10.9.3 IMPULSE WITHSTAND VOLTAGE	Is the panel builder's responsibility.
10.9.4 TESTING OF ENCLOSURES MADE OF INSULATING MATERIAL	Is the panel builder's responsibility.
EQUIPMENT HEAT DISSIPATION, CURRENT-DEPENDENT PVID	0 W
HEAT DISSIPATION CAPACITY PDISS	0 W
HEAT DISSIPATION PER POLE, CURRENT-DEPENDENT PVID	7.5 W
RATED OPERATIONAL CURRENT FOR SPECIFIED HEAT DISSIPATION (IN)	100 A
STATIC HEAT DISSIPATION, NON-CURRENT-DEPENDENT PVS	0 W

Electrical rating

**RATED BREAKING
CAPACITY AT 220/230 V
(COS PHI TO IEC 60947-3)** 760 A

**RATED BREAKING
CAPACITY AT 400/415 V
(COS PHI TO IEC 60947-3)** 740 A

**RATED BREAKING
CAPACITY AT 500 V (COS
PHI TO IEC 60947-3)** 590 A

**RATED BREAKING
CAPACITY AT 660/690 V
(COS PHI TO IEC 60947-3)** 420 A

**RATED OPERATIONAL
CURRENT (IE)** 100 A at AC-3, 230 V star-
delta
29.4 A at AC-3, 690 V star-
delta
95.3 A at AC-3, 400 V star-
delta
76.2 A at AC-3, 500 V star-
delta

**RATED OPERATIONAL
CURRENT (IE) AT AC-21,
440 V** 100 A

**RATED OPERATIONAL
CURRENT (IE) AT AC-23A,
230 V** 100 A

**RATED OPERATIONAL
CURRENT (IE) AT AC-23A,
400 V, 415 V** 100 A

**RATED OPERATIONAL
CURRENT (IE) AT AC-23A,
500 V** 55 A

**RATED OPERATIONAL
CURRENT (IE) AT AC-23A,
690 V** 32 A

**RATED OPERATIONAL
CURRENT (IE) AT AC-3,
220 V, 230 V, 240 V** 71 A

**RATED OPERATIONAL
CURRENT (IE) AT AC-3,
380 V, 400 V, 415 V** 55 A

**RATED OPERATIONAL
CURRENT (IE) AT AC-3,
500 V** 44 A

**RATED OPERATIONAL
CURRENT (IE) AT AC-3,
660 V, 690 V** 17 A

**RATED OPERATIONAL
CURRENT (IE) AT DC-1,
LOAD-BREAK SWITCHES
L/R = 1 MS** 80 A

RATED OPERATIONAL 30 kW

Features & functions

ENCLOSURE MATERIAL Plastic

FEATURES Complete device in
housing

FITTED WITH: 0 (off) position
Black thumb grip and
front plate

INSCRIPTION 1-0-2

NUMBER OF POLES 3

POWER AT AC-23A, 220/230 V, 50 HZ	
RATED OPERATIONAL POWER AT AC-23A, 400 V, 50 HZ	
	55 kW
RATED OPERATIONAL POWER AT AC-23A, 500 V, 50 HZ	
	37 kW
RATED OPERATIONAL POWER AT AC-23A, 690 V, 50 HZ	
	30 kW
RATED OPERATIONAL POWER AT AC-3, 380/400 V, 50 HZ	
	30 kW
RATED OPERATIONAL POWER AT AC-3, 415 V, 50 HZ	
	30 kW
RATED OPERATIONAL POWER AT AC-3, 690 V, 50 HZ	
	15 kW
RATED OPERATIONAL POWER STAR-DELTA AT 220/230 V, 50 HZ	
	30 kW
RATED OPERATIONAL POWER STAR-DELTA AT 380/400 V, 50 HZ	
	45 kW
RATED OPERATIONAL POWER STAR-DELTA AT 500 V, 50 HZ	
	45 kW
RATED OPERATIONAL POWER STAR-DELTA AT 690 V, 50 HZ	
	22 kW
RATED OPERATIONAL VOLTAGE (UE) AT AC - MAX	
	690 V
RATED UNINTERRUPTED CURRENT (IU)	
	100 A
UNINTERRUPTED CURRENT	Rated uninterrupted current I _u is specified for max. cross-section.

General information

DEGREE OF PROTECTION	IP65
DEGREE OF PROTECTION (FRONT SIDE)	IP65 NEMA 12
LIFESPAN, MECHANICAL	500,000 Operations
MODEL	Reverser
MOUNTING METHOD	Surface mounting
MOUNTING POSITION	As required
NUMBER OF CONTACT UNITS	3
OPERATING FREQUENCY	1200 Operations/h
OVERVOLTAGE CATEGORY	III
POLLUTION DEGREE	3
PRODUCT CATEGORY	Control switches
RATED IMPULSE WITHSTAND VOLTAGE (UIMP)	6000 V AC
SAFE ISOLATION	440 V AC, Between the contacts, According to EN 61140
SAFETY PARAMETER (EN ISO 13849-1)	B10d values as per EN ISO 13849-1, table C.1
SHOCK RESISTANCE	15 g, Mechanical, According to IEC/EN 60068-2-27, Half-sinusoidal shock 20 ms
SUITABLE FOR	Ground mounting Front mounting
SWITCHING ANGLE	60 °
TYPE	Changeover switch

Switching capacity

LOAD RATING	$2 \times I_e$ (with intermittent operation class 12, 25 % duty factor) $1.6 \times I_e$ (with intermittent operation class 12, 40 % duty factor) $1.3 \times I_e$ (with intermittent operation class 12, 60 % duty factor)
RATED MAKING CAPACITY UP TO 690 V (COS PHI TO IEC/EN 60947-3)	950 A
VOLTAGE PER CONTACT PAIR IN SERIES	60 V

Short-circuit rating

RATED CONDITIONAL SHORT-CIRCUIT CURRENT (IQ)	2 kA
RATED SHORT-TIME WITHSTAND CURRENT (ICW)	1,7 kA, Contacts, 1 second
SHORT-CIRCUIT PROTECTION RATING	100 A gG/gL, Fuse, Contacts

Terminal capacities

SCREW SIZE	M6, Terminal screw
TERMINAL CAPACITY (FLEXIBLE WITH FERRULE)	$2 \times (1.5 - 10) \text{ mm}^2$, ferrule to DIN 46228 $1 \times (1 - 25) \text{ mm}^2$, ferrules to DIN 46228
TERMINAL CAPACITY (SOLID/STRANDED)	$2 \times (2.5 - 16) \text{ mm}^2$ $1 \times (2.5 - 35) \text{ mm}^2$
TIGHTENING TORQUE	35.4 lb-in, Screw terminals 4 Nm, Screw terminals

Resources

BROCHURES	Brochure - T Rotary Cam switch and P Switch-disconnector
CATALOGUES	P Switch-disconnectors and T Rotary cam switches catalogue CA042001EN
DECLARATIONS OF CONFORMITY	eaton-changeover-switch-declaration-of-conformity-eu251494en.pdf
DRAWINGS	eaton-rotary-switches-t5-changeover-switch-dimensions-002.eps
	eaton-rotary-switches-surface-mounting-t0-changeover-switch-3d-drawing.eps
	eaton-rotary-switches-front-plate-t0-changeover-switch-symbol-009.eps
	eaton-general-rotary-switch-t0-step-switch-symbol.eps
	eaton-general-totally-insulated-t0-main-switch-symbol.eps
ECAD MODEL	ETN.207266.edz
INSTALLATION INSTRUCTIONS	IL03801009Z
INSTALLATION VIDEOS	Eaton's P Switch-disconnectors used in a factory
MCAD MODEL	eaton-cam-switches-mcad-drawings-bauform18.dwg
	DA-CS-bauform18
PRODUCT NOTIFICATIONS	MZ008006ZU_Orderform_Customized_Switch.pdf
	MZ008005ZU_Orderform_Customized_Switch.pdf
WIRING DIAGRAMS	eaton-rotary-switches-changeover-switch-t0-changeover-switch-wiring-diagram-003.eps

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

DATE:



Eaton Corporation plc Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2026 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

