

Specifications



Eaton 208218

Eaton Moeller® series DILM Contactor, 380 V 400 V 355 kW, 2 N/O, 2 NC, RA 110: 48 - 110 V 40 - 60 Hz/48 - 110 V DC, AC and DC operation, Screw connection

General specifications

PRODUCT NAME	Eaton Moeller® series DILM Contactor
CATALOG NUMBER	208218
MODEL CODE	DILM650/22(RA110)
EAN	4015082082185
PRODUCT LENGTH/DEPTH	232 mm
PRODUCT HEIGHT	296 mm
PRODUCT WIDTH	250 mm
PRODUCT WEIGHT	16.209 kg
CERTIFICATIONS	CE VDE 0660 CSA-C22.2 No. 60947-4-1-14 IEC/EN 60947 CSA CSA Class No.: 3211-04 UL 60947-4-1 UL Category Control No.: NLDX IEC/EN 60947-4-1 UL File No.: E29096 UL CSA File No.: 012528

CATALOG NOTES

- Contacts according to EN 50012
- Also tested according to AC-3e up to 690 V.
- Also suitable for motors with efficiency class IE3.
- Conventional thermal current Ith of main contacts (1-pole, open) at 60°



Powering Business Worldwide

AC-1/Conventional thermal current Ith

CONVENTIONAL THERMAL CURRENT ITH AT 40°C (3-POLE, OPEN)	1041 A
---	--------

CONVENTIONAL THERMAL CURRENT ITH AT 50°C (3-POLE, OPEN)	931 A
---	-------

CONVENTIONAL THERMAL CURRENT ITH AT 55°C (3-POLE, OPEN)	888 A
---	-------

CONVENTIONAL THERMAL CURRENT ITH AT 60°C (3-POLE, OPEN)	850 A
---	-------

CONVENTIONAL THERMAL CURRENT ITH OF MAIN CONTACTS (1- POLE, OPEN)	2125 A
--	--------

Contacts

NUMBER OF AUXILIARY CONTACTS (NORMALLY CLOSED CONTACTS)	2
---	---

NUMBER OF AUXILIARY CONTACTS (NORMALLY OPEN CONTACTS)	2
---	---

NUMBER OF CONTACTS (NORMALLY CLOSED CONTACTS)	2
---	---

NUMBER OF CONTACTS (NORMALLY OPEN CONTACTS)	2
---	---

Climatic environmental conditions

ALTITUDE	Max. 2000 m
----------	-------------

AMBIENT OPERATING TEMPERATURE - MAX	60 °C
--	-------

AMBIENT STORAGE TEMPERATURE - MAX	80 °C
--------------------------------------	-------

AMBIENT OPERATING TEMPERATURE - MIN	-40 °C
--	--------

AMBIENT OPERATING TEMPERATURE (ENCLOSED) - MAX	40 °C
--	-------

AMBIENT OPERATING TEMPERATURE (ENCLOSED) - MIN	-40 °C
--	--------

AMBIENT STORAGE TEMPERATURE - MIN	-40 °C
--------------------------------------	--------

CLIMATIC PROOFING	Damp heat, constant, to IEC 60068-2-78 Damp heat, cyclic, to IEC 60068-2-30
-------------------	--

Design verification

10.10 TEMPERATURE RISE	The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.
------------------------	--

10.11 SHORT-CIRCUIT RATING	Is the panel builder's responsibility. The specifications for the switchgear must be observed.
----------------------------	--

10.12 ELECTROMAGNETIC COMPATIBILITY	Is the panel builder's responsibility. The specifications for the switchgear must be observed.
-------------------------------------	--

10.13 MECHANICAL FUNCTION	The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.
---------------------------	--

10.2.2 CORROSION RESISTANCE	Meets the product standard's requirements.
-----------------------------	--

10.2.3.1 VERIFICATION OF THERMAL STABILITY OF ENCLOSURES	Meets the product standard's requirements.
--	--

10.2.3.2 VERIFICATION OF RESISTANCE OF INSULATING MATERIALS	Meets the product standard's requirements.
---	--

TO NORMAL HEAT	
10.2.3.3 RESIST. OF INSUL. MAT. TO ABNORMAL HEAT/FIRE BY INTERNAL ELECT. EFFECTS	Meets the product standard's requirements.
10.2.4 RESISTANCE TO ULTRA-VIOLET (UV) RADIATION	Meets the product standard's requirements.
10.2.5 LIFTING	Does not apply, since the entire switchgear needs to be evaluated.
10.2.6 MECHANICAL IMPACT	Does not apply, since the entire switchgear needs to be evaluated.
10.2.7 INSCRIPTIONS	Meets the product standard's requirements.
10.3 DEGREE OF PROTECTION OF ASSEMBLIES	Does not apply, since the entire switchgear needs to be evaluated.
10.4 CLEARANCES AND CREEPAGE DISTANCES	Meets the product standard's requirements.
10.5 PROTECTION AGAINST ELECTRIC SHOCK	Does not apply, since the entire switchgear needs to be evaluated.
10.6 INCORPORATION OF SWITCHING DEVICES AND COMPONENTS	Does not apply, since the entire switchgear needs to be evaluated.
10.7 INTERNAL ELECTRICAL CIRCUITS AND CONNECTIONS	Is the panel builder's responsibility.
10.8 CONNECTIONS FOR EXTERNAL CONDUCTORS	Is the panel builder's responsibility.
10.9.2 POWER-FREQUENCY ELECTRIC STRENGTH	Is the panel builder's responsibility.
10.9.3 IMPULSE WITHSTAND VOLTAGE	Is the panel builder's responsibility.
10.9.4 TESTING OF ENCLOSURES MADE OF INSULATING MATERIAL	Is the panel builder's responsibility.
EQUIPMENT HEAT DISSIPATION, CURRENT-DEPENDENT PVID	0 W
HEAT DISSIPATION CAPACITY PDISS	0 W
HEAT DISSIPATION PER POLE, CURRENT-DEPENDENT PVID	13.67 W
RATED OPERATIONAL CURRENT FOR SPECIFIED HEAT DISSIPATION (IN)	650 A

STATIC HEAT DISSIPATION, NON- CURRENT-DEPENDENT PVS	6.5 W
--	-------

Electrical rating

INRUSH CURRENT	Max. 30 x I _e (peak)
RATED BREAKING CAPACITY AT 1000 V	4350 A
RATED BREAKING CAPACITY AT 220/230 V	6500 A
RATED BREAKING CAPACITY AT 380/400 V	6500 A
RATED BREAKING CAPACITY AT 500 V	6500 A
RATED BREAKING CAPACITY AT 660/690 V	6500 A
RATED INSULATION VOLTAGE (UI)	1000 V
RATED MAKING CAPACITY (COS PHI TO IEC/EN 60947)	7800 A
RATED OPERATIONAL CURRENT (IE)	463 A at up to 525 V (Individual compensation, three-phase capacitors, open) 265 A at 690 V (Individual compensation, three-phase capacitors, open)
RATED OPERATIONAL CURRENT (IE) AT AC-3, 1000 V	435 A
RATED OPERATIONAL CURRENT (IE) AT AC-3, 220 V, 230 V, 240 V	650 A
RATED OPERATIONAL CURRENT (IE) AT AC-3, 380 V, 400 V, 415 V	650 A
RATED OPERATIONAL CURRENT (IE) AT AC-3, 440 V	650 A
RATED OPERATIONAL CURRENT (IE) AT AC-3, 500 V	650 A
RATED OPERATIONAL CURRENT (IE) AT AC-3, 660 V, 690 V	650 A
RATED OPERATIONAL CURRENT (IE) AT AC-4, 1000 V	348 A
RATED OPERATIONAL CURRENT (IE) AT AC-4, 220 V, 230 V, 240 V	512 A
RATED OPERATIONAL CURRENT (IE) AT AC-4, 440 V	512 A

General information

ACCESSORIES	Fitting options auxiliary contacts: on the side: 2 x DILM820-XHI11(V)-SI; 2 x DILM820-XHI11-SA
APPLICATION	Contactors for Motors
CONNECTION	Screw terminals
DEGREE OF PROTECTION	IP00
ELECTROMAGNETIC COMPATIBILITY	Designed for operation in industrial environments. Its use in residential environments may cause radio-frequency interference, requiring additional noise suppression.
FITTED WITH:	Suppressor circuit in actuating electronics
LIFESPAN, ELECTRICAL	100,000 Operations (at Condensor operation)
LIFESPAN, MECHANICAL	5,000,000 Operations (AC operated) 5,000,000 Operations (DC operated)
OPERATING FREQUENCY	200 Operations/h 1000 mechanical Operations/h (AC operated) 1000 mechanical Operations/h (DC operated)
OVERVOLTAGE CATEGORY	III
POLLUTION DEGREE	3
PRODUCT CATEGORY	Contactors
PROTECTION	Finger and back-of-hand proof with terminal shroud or terminal block, Protection against direct contact when actuated from front (EN 50274)
RATED IMPULSE WITHSTAND VOLTAGE (UIMP)	8000 V AC
RESISTANCE	500 mΩ (Admissible transitional contact resistance - of the external control circuit device when actuating A11)
SHOCK RESISTANCE	10 g, N/O auxiliary contact, Mechanical, according to

RATED OPERATIONAL CURRENT (IE) AT AC-4, 500 V	512 A
RATED OPERATIONAL CURRENT (IE) AT AC-4, 660 V, 690 V	512 A
RATED OPERATIONAL POWER AT AC-3, 1000 V, 50 HZ	600 kW
RATED OPERATIONAL POWER AT AC-3, 240 V, 50 HZ	225 kW
RATED OPERATIONAL POWER AT AC-3, 380/400 V, 50 HZ	355 kW
RATED OPERATIONAL POWER AT AC-3, 415 V, 50 HZ	390 kW
RATED OPERATIONAL POWER AT AC-3, 440 V, 50 HZ	420 kW
RATED OPERATIONAL POWER AT AC-3, 500 V, 50 HZ	470 kW
RATED OPERATIONAL POWER AT AC-3, 690 V, 50 HZ	630 kW
RATED OPERATIONAL POWER AT AC-4, 1000 V, 50 HZ	509 kW
RATED OPERATIONAL POWER AT AC-4, 220/230 V, 50 HZ	161 kW
RATED OPERATIONAL POWER AT AC-4, 240 V, 50 HZ	176 kW
RATED OPERATIONAL POWER AT AC-4, 415 V, 50 HZ	307 kW
RATED OPERATIONAL POWER AT AC-4, 440 V, 50 HZ	326 kW
RATED OPERATIONAL POWER AT AC-4, 500 V, 50 HZ	370 kW
RATED OPERATIONAL POWER AT AC-4, 660/690 V, 50 HZ	494 kW
RATED OPERATIONAL VOLTAGE (UE) AT AC - MAX	1000 V
SAFE ISOLATION	1000 V AC, Between coil and contacts, According to

	IEC/EN 60068-2-27, Half-sinusoidal shock 10 ms 8 g, N/C auxiliary contact, Mechanical, according to IEC/EN 60068-2-27, Half-sinusoidal shock 10 ms 10 g, N/O main contact, Mechanical, according to IEC/EN 60068-2-27, Half-sinusoidal shock 10 ms
SIGNAL LEVEL	5 V - 15 V, PLC signal level (A3 - A4) to IEC/EN 61131-2 (type 2), Magnet systems
UTILIZATION CATEGORY	AC-3: Normal AC induction motors: starting, switch off during running AC-1: Non-inductive or slightly inductive loads, resistance furnaces AC-4: Normal AC induction motors: starting, plugging, reversing, inching
VOLTAGE TYPE	AC/DC

	EN 61140
SPECIAL PURPOSE RATING OF DEFINITE PURPOSE RATING	4350 A, LRA 600 V 60 Hz 3- ph, 100,000 cycles acc. to UL 1995, (UL/CSA) 725 A, FLA 600 V 60 Hz 3- ph, 100,000 cycles acc. to UL 1995, (UL/CSA) 725 A, FLA 480 V 60 Hz 3- ph, 100,000 cycles acc. to UL 1995, (UL/CSA) 4350 A, LRA 480 V 60 Hz 3- ph, 100,000 cycles acc. to UL 1995, (UL/CSA)

Magnet system

BEHAVIOR IN MARGINAL AND TRANSITIONAL CONDITIONS

Sealing - Voltage drops ($0.2 - 0.6 \times U_{c \min} \leq 12 \text{ ms}$: Time is bridged successfully
 Sealing - Voltage interruptions $0 - 0.2 \times U_{c \min} > 10 \text{ ms}$: Drop-out of the contactor
 Sealing - Pick-up phase ($0.7 \times U_{c \min} - 1.15 \times U_{c \max}$): Contactor switches on with certainty
 Sealing - Pick-up phase ($0 - 0.7 \times U_{c \min}$: Contactor does not switch on
 Sealing - Voltage drops ($0.2 - 0.6 \times U_{c \min} > 12 \text{ ms}$: Drop-out of the contactor
 Sealing - Voltage drops ($0.6 - 0.7 \times U_{c \min}$: Contactor remains switched on
 Sealing - Voltage interruptions ($0 - 0.2 \times U_{c \min} \leq 10 \text{ ms}$: Time is bridged successfully
 Sealing - Excess voltage ($1.15 - 1.3 \times U_{c \max}$): Contactor remains switched on

DROP-OUT VOLTAGE

$0.2 \times U_S \text{ max} - 0.6 \times U_S \text{ min}$, DC operated
 AC operated: $0.2 \times U_S \text{ max} - 0.6 \times U_S \text{ min}$, AC operated

DUTY FACTOR

100 %

PICK-UP VOLTAGE

$0.7 - 1.15 \text{ V AC} \times U_S$
 $0.7 - 1.15 \text{ V DC} \times U_S$

POWER CONSUMPTION

Control transformer with $u_k \leq 7\%$

POWER CONSUMPTION, PICK-UP, 50 HZ

1100 VA, Pull-in power, Coil in a cold state and $1.0 \times U_S$

POWER CONSUMPTION, PICK-UP, 60 HZ

1100 VA, Pull-in power, Coil in a cold state and $1.0 \times U_S$

POWER CONSUMPTION, SEALING, 50 HZ

10.3 W, Coil in a cold state and $1.0 \times U_S$
 26.4 VA, Coil in a cold state and $1.0 \times U_S$

POWER CONSUMPTION, SEALING, 60 HZ

10.3 W, Coil in a cold state and $1.0 \times U_S$
 26.4 VA, Coil in a cold state and $1.0 \times U_S$

Motor rating

ASSIGNED MOTOR

POWER AT 200/208 V, 60 HZ, 3-PHASE 200 HP

ASSIGNED MOTOR

POWER AT 230/240 V, 60 HZ, 3-PHASE 250 HP

ASSIGNED MOTOR

POWER AT 460/480 V, 60 HZ, 3-PHASE 500 HP

ASSIGNED MOTOR

POWER AT 575/600 V, 60 HZ, 3-PHASE 600 HP

RATED CONTROL SUPPLY VOLTAGE (US) AT AC, 50 HZ - MAX	110 V
RATED CONTROL SUPPLY VOLTAGE (US) AT AC, 50 HZ - MIN	48 V
RATED CONTROL SUPPLY VOLTAGE (US) AT AC, 60 HZ - MAX	110 V
RATED CONTROL SUPPLY VOLTAGE (US) AT AC, 60 HZ - MIN	48 V
RATED CONTROL SUPPLY VOLTAGE (US) AT DC - MAX	100 V
RATED CONTROL SUPPLY VOLTAGE (US) AT DC - MIN	48 V
SWITCHING TIME (AC OPERATED, MAKE CONTACTS, CLOSING DELAY) - MAX	70 ms
SWITCHING TIME (AC OPERATED, MAKE CONTACTS, OPENING DELAY) - MAX	110 ms

Short-circuit rating

SHORT-CIRCUIT CURRENT RATING (BASIC RATING)	2000 A, max. Fuse, SCCR (UL/CSA)
	30 kA, SCCR (UL/CSA)
	1200 A, max. CB, SCCR (UL/CSA)
SHORT-CIRCUIT CURRENT RATING (HIGH FAULT AT 480 V)	2000 A, max. Fuse, SCCR (UL/CSA)
	85 kA, CB, SCCR (UL/CSA)
	85 kA, Fuse, SCCR (UL/CSA)
SHORT-CIRCUIT CURRENT RATING (HIGH FAULT AT 600 V)	1200 A, max. CB, SCCR (UL/CSA)
	85 kA, Fuse, SCCR (UL/CSA)
	85 kA, Fuse, SCCR (UL/CSA)
SHORT-CIRCUIT PROTECTION RATING (TYPE 1 COORDINATION) AT 1000 V	630 A gG/gL
SHORT-CIRCUIT PROTECTION RATING (TYPE 1 COORDINATION) AT 400 V	1000 A gG/gL
SHORT-CIRCUIT PROTECTION RATING (TYPE 1 COORDINATION) AT 690 V	1000 A gG/gL
SHORT-CIRCUIT PROTECTION RATING (TYPE 2 COORDINATION) AT 1000 V	500 A gG/gL
SHORT-CIRCUIT PROTECTION RATING (TYPE 2 COORDINATION) AT 400 V	630 A gG/gL
SHORT-CIRCUIT PROTECTION RATING (TYPE 2 COORDINATION) AT 690 V	630 A gG/gL

Switching capacity

SWITCHING CAPACITY (AUXILIARY CONTACTS, GENERAL USE)	1 A, 250 V DC, (UL/CSA) 15 A, 600 V AC, (UL/CSA)
SWITCHING CAPACITY (AUXILIARY CONTACTS, PILOT DUTY)	A600, AC operated (UL/CSA) P300, DC operated (UL/CSA)
SWITCHING CAPACITY (MAIN CONTACTS, GENERAL USE)	1041 A, Maximum motor rating (UL/CSA)

Terminal capacities

SCREW SIZE	M10, Terminal screw, Main connections M3.5, Terminal screw, Control circuit cables
SCREWDRIVER SIZE	2, Terminal screw, Control circuit cables, Pozidriv screwdriver
TERMINAL CAPACITY (BUSBAR)	50 mm width, Main connection
TERMINAL CAPACITY (COPPER BAND)	Fixing with flat cable terminal or cable terminal blocks; See terminal capacity for cable terminal blocks
TERMINAL CAPACITY (FLEXIBLE WITH CABLE LUG)	50 - 240 mm ²
TERMINAL CAPACITY (FLEXIBLE WITH FERRULE)	2 x (0.75 - 2.5) mm ² , Control circuit cables 1 x (0.75 - 2.5) mm ² , Control circuit cables
TERMINAL CAPACITY (SOLID)	1 x (0.75 - 2.5) mm ² , Control circuit cables 2 x (0.75 - 2.5) mm ² , Control circuit cables
TERMINAL CAPACITY (SOLID/STRANDED AWG)	2/0 - 500 MCM, Main cables 18 - 14, Control circuit cables
TERMINAL CAPACITY (STRANDED WITH CABLE LUG)	70 - 240 mm ²
TIGHTENING TORQUE	24 Nm, Main cable connection screw/bolt 1.2 Nm, Screw terminals, Control circuit cables
WIDTH ACROSS FLATS	16 mm

Resources

BROCHURES	eaton-product-brochure-dilm580-power-contactors-brochure-br034010en-en-us.pdf
CHARACTERISTIC CURVE	eaton-contactors-component-dilm-characteristic-curve-002.eps eaton-contactors-short-time-loading-dilm-characteristic-curve-002.eps eaton-contactors-component-dilm-characteristic-curve-003.eps eaton-contactors-component-dilm-characteristic-curve.eps
DECLARATIONS OF CONFORMITY	eaton-contactor-declaration-of-conformity-eu250667en.pdf eaton-contactor-declaration-of-conformity-uk251150en.pdf
DRAWINGS	eaton-contactors-mounting-dilm-dimensions.eps eaton-contactors-mounting-dilm-dimensions-002.eps eaton-contactors-dilm-dimensions-005.eps eaton-contactors-dilm-3d-drawing-006.eps eaton-contactors-mounting-dilm-3d-drawing-002.eps
ECAD MODEL	DA-CE-ETN.DILM650_22(RA110)
INSTALLATION INSTRUCTIONS	eaton-contactors-dilm580-to-dilm1000-il03407023z.pdf
MCAD MODEL	eaton-iec-contactors-mcad-drawings-dil-m580-820.dwg eaton-dil_m580_820-3d-model.stp

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

DATE:



Eaton Corporation plc Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2026 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

