


Specifications

Eaton 216405

Eaton Moeller® series M22 Plunger Bridge



General specifications

PRODUCT NAME	Eaton Moeller® series M22 plunger bridge
CATALOG NUMBER	216405
MODEL CODE	M22-XW
EAN	4015082164058
PRODUCT LENGTH/DEPTH	19 mm
PRODUCT HEIGHT	16 mm
PRODUCT WIDTH	11 mm
PRODUCT WEIGHT	0.32 g
COMPLIANCES	CE Marked
CERTIFICATIONS	UL 508 EN 60947-5 CSA Std. C22.2 No. 94-91 CSA Std. C22.2 No. 14-05 IEC 60947-5 CSA CSA File No.: 012528 CSA Class No.: 3211-03 CSA-C22.2 No. 94-91 CSA-C22.2 No. 14-05 IEC/EN 60947-5 UL File No.: E29184 CE UL UL Category Control No.: NKR

Actuator

FUNCTIONS

For actuating the middle contact element of the M22-W...3 non-illuminated 3-position selector switch actuator

Communication

CONNECTION TO SMARTWIRE-DT

No

Climatic environmental conditions

AMBIENT OPERATING TEMPERATURE - MAX

70 °C

AMBIENT OPERATING TEMPERATURE - MIN

-25 °C

Design verification

10.10 TEMPERATURE RISE Not applicable.

10.11 SHORT-CIRCUIT RATING

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

10.12 ELECTROMAGNETIC COMPATIBILITY

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

10.13 MECHANICAL FUNCTION

The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

10.2.2 CORROSION RESISTANCE

Meets the product standard's requirements.

10.2.3.1 VERIFICATION OF THERMAL STABILITY OF ENCLOSURES

Meets the product standard's requirements.

10.2.3.2 VERIFICATION OF RESISTANCE OF INSULATING MATERIALS TO NORMAL HEAT

Meets the product standard's requirements.

10.2.3.3 RESIST. OF INSUL. MAT. TO ABNORMAL HEAT/FIRE BY INTERNAL ELECT. EFFECTS

Meets the product standard's requirements.

10.2.4 RESISTANCE TO ULTRA-VIOLET (UV) RADIATION

Please enquire

10.2.5 LIFTING

Does not apply, since the entire switchgear needs to be evaluated.

10.2.6 MECHANICAL IMPACT

Does not apply, since the entire switchgear needs to be evaluated.

10.2.7 INSCRIPTIONS

Meets the product standard's requirements.

10.3 DEGREE OF PROTECTION OF

Does not apply, since the entire switchgear needs to

ASSEMBLIES	be evaluated.
10.4 CLEARANCES AND CREEPAGE DISTANCES	Meets the product standard's requirements.
10.5 PROTECTION AGAINST ELECTRIC SHOCK	Does not apply, since the entire switchgear needs to be evaluated.
10.6 INCORPORATION OF SWITCHING DEVICES AND COMPONENTS	Does not apply, since the entire switchgear needs to be evaluated.
10.7 INTERNAL ELECTRICAL CIRCUITS AND CONNECTIONS	Is the panel builder's responsibility.
10.8 CONNECTIONS FOR EXTERNAL CONDUCTORS	Is the panel builder's responsibility.
10.9.2 POWER-FREQUENCY ELECTRIC STRENGTH	Is the panel builder's responsibility.
10.9.3 IMPULSE WITHSTAND VOLTAGE	Is the panel builder's responsibility.
10.9.4 TESTING OF ENCLOSURES MADE OF INSULATING MATERIAL	Is the panel builder's responsibility.
EQUIPMENT HEAT DISSIPATION, CURRENT-DEPENDENT PVID	0 W
HEAT DISSIPATION CAPACITY PDISS	0 W
HEAT DISSIPATION PER POLE, CURRENT-DEPENDENT PVID	0 W
RATED OPERATIONAL CURRENT FOR SPECIFIED HEAT DISSIPATION (IN)	0 A
STATIC HEAT DISSIPATION, NON-CURRENT-DEPENDENT PVS	0 W

General information

ACCESSORY/SPARE PART TYPE	Accessory Spare part
----------------------------------	-------------------------

Resources

CATALOGUES	eaton-pushbuttons-signal-towers-sensors-assortment-overview-catalog-ca047003en-en-us.pdf
DRAWINGS	1161284
INSTALLATION INSTRUCTIONS	IL04716002Z
MCAD MODEL	eaton-pushbu-switch-renewal-parts-accessory-mcad-3d-models-m22-xw.stp

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

DATE:



Eaton Corporation plc Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2026 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

