

Specifications



Eaton 216408

Eaton Moeller® series M22 Set of adapter rings

General specifications

PRODUCT NAME	Eaton Moeller® series M22 reduction ring set
CATALOG NUMBER	216408
MODEL CODE	M22S-R30
EAN	4015082164089
PRODUCT LENGTH/DEPTH	10 mm
PRODUCT HEIGHT	50 mm
PRODUCT WIDTH	50 mm
PRODUCT WEIGHT	0.006 kg
CERTIFICATIONS	UL/CSA certification not required
CATALOG NOTES	Consists of adapter ring and lock nut

Actuator

BEZEL COLOR	Black
-------------	-------

Communication

CONNECTION TO SMARTWIRE-DT	No
-------------------------------	----

Climatic environmental conditions

AMBIENT OPERATING TEMPERATURE - MAX	70 °C
--	-------

AMBIENT OPERATING TEMPERATURE - MIN	-25 °C
--	--------

Design verification

10.10 TEMPERATURE RISE	Not applicable.
------------------------	-----------------

10.11 SHORT-CIRCUIT RATING	Is the panel builder's responsibility. The specifications for the switchgear must be observed.
-------------------------------	--

10.12 ELECTROMAGNETIC COMPATIBILITY	Is the panel builder's responsibility. The specifications for the switchgear must be observed.
--	--

10.13 MECHANICAL FUNCTION	The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.
------------------------------	--

10.2.2 CORROSION RESISTANCE	Meets the product standard's requirements.
--------------------------------	--

10.2.3.1 VERIFICATION OF THERMAL STABILITY OF ENCLOSURES	Meets the product standard's requirements.
--	--

10.2.3.2 VERIFICATION OF RESISTANCE OF INSULATING MATERIALS TO NORMAL HEAT	Meets the product standard's requirements.
---	--

10.2.3.3 RESIST. OF INSUL. MAT. TO ABNORMAL HEAT/FIRE BY INTERNAL ELECT. EFFECTS	Meets the product standard's requirements.
--	--

10.2.4 RESISTANCE TO ULTRA-VIOLET (UV) RADIATION	Please enquire
--	----------------

10.2.5 LIFTING	Does not apply, since the entire switchgear needs to be evaluated.
----------------	--

10.2.6 MECHANICAL IMPACT	Does not apply, since the entire switchgear needs to be evaluated.
-----------------------------	--

10.2.7 INSCRIPTIONS	Meets the product standard's requirements.
---------------------	--

10.3 DEGREE OF PROTECTION OF ASSEMBLIES	Does not apply, since the entire switchgear needs to be evaluated.
---	--

10.4 CLEARANCES AND CREEPAGE DISTANCES	Meets the product standard's requirements.
10.5 PROTECTION AGAINST ELECTRIC SHOCK	Does not apply, since the entire switchgear needs to be evaluated.
10.6 INCORPORATION OF SWITCHING DEVICES AND COMPONENTS	Does not apply, since the entire switchgear needs to be evaluated.
10.7 INTERNAL ELECTRICAL CIRCUITS AND CONNECTIONS	Is the panel builder's responsibility.
10.8 CONNECTIONS FOR EXTERNAL CONDUCTORS	Is the panel builder's responsibility.
10.9.2 POWER-FREQUENCY ELECTRIC STRENGTH	Is the panel builder's responsibility.
10.9.3 IMPULSE WITHSTAND VOLTAGE	Is the panel builder's responsibility.
10.9.4 TESTING OF ENCLOSURES MADE OF INSULATING MATERIAL	Is the panel builder's responsibility.
EQUIPMENT HEAT DISSIPATION, CURRENT-DEPENDENT PVID	0 W
HEAT DISSIPATION CAPACITY PDISS	0 W
HEAT DISSIPATION PER POLE, CURRENT-DEPENDENT PVID	0 W
RATED OPERATIONAL CURRENT FOR SPECIFIED HEAT DISSIPATION (IN)	0 A
STATIC HEAT DISSIPATION, NON-CURRENT-DEPENDENT PVS	0 W

General information

ACCESSORY/SPARE PART TYPE	Accessory
DEGREE OF PROTECTION	IP66 IP69K IP67

Resources

CATALOGUES	eaton-pushbuttons-signal-towers-sensors-assortment-overview-catalog-ca047003en-en-us.pdf
DECLARATIONS OF CONFORMITY	eaton-potentiometer-declaration-of-conformity-eu251540en.pdf
DRAWINGS	eaton-operating-button-symbol-005.eps
INSTALLATION INSTRUCTIONS	IL04716002Z

MCAD MODEL	eaton-pushbu-switch-renewal-parts-accessory-mcad-3d-models-m22s-r30.stp
	eaton-accessory-mcad-drawings-reduzierring.dwg

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

DATE:



Eaton Corporation plc Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2026 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

