

Specifications



Eaton 216501

Eaton Moeller® series M22 Carrier, +label,
MAN 0 AUTO

General specifications

PRODUCT NAME	Eaton Moeller® series M22 legend holder
CATALOG NUMBER	216501
MODEL CODE	M22S-ST-GB12
EAN	4015082165017
PRODUCT LENGTH/DEPTH	4 mm
PRODUCT HEIGHT	50 mm
PRODUCT WIDTH	30 mm
PRODUCT WEIGHT	0.002 kg
CERTIFICATIONS	UL/CSA certification not required

Actuator

DESIGN Round

INSCRIPTION MAN. 0 AUTO
" MAN. 0 AUTO "

RAL-NUMBER 9005

Communication

**CONNECTION TO
SMARTWIRE-DT** No

Climatic environmental conditions

**AMBIENT OPERATING
TEMPERATURE - MAX** 70 °C

**AMBIENT OPERATING
TEMPERATURE - MIN** -25 °C

Design verification

10.10 TEMPERATURE RISE Not applicable.

**10.11 SHORT-CIRCUIT
RATING** Is the panel builder's
responsibility. The
specifications for the
switchgear must be
observed.

**10.12 ELECTROMAGNETIC
COMPATIBILITY** Is the panel builder's
responsibility. The
specifications for the
switchgear must be
observed.

**10.13 MECHANICAL
FUNCTION** The device meets the
requirements, provided
the information in the
instruction leaflet (IL) is
observed.

**10.2.2 CORROSION
RESISTANCE** Meets the product
standard's requirements.

**10.2.3.1 VERIFICATION OF
THERMAL STABILITY OF
ENCLOSURES** Meets the product
standard's requirements.

**10.2.3.2 VERIFICATION OF
RESISTANCE OF
INSULATING MATERIALS
TO NORMAL HEAT** Meets the product
standard's requirements.

**10.2.3.3 RESIST. OF
INSUL. MAT. TO
ABNORMAL HEAT/FIRE
BY INTERNAL ELECT.
EFFECTS** Meets the product
standard's requirements.

**10.2.4 RESISTANCE TO
ULTRA-VIOLET (UV)
RADIATION** Please enquire

10.2.5 LIFTING Does not apply, since the
entire switchgear needs to
be evaluated.

**10.2.6 MECHANICAL
IMPACT** Does not apply, since the
entire switchgear needs to
be evaluated.

10.2.7 INSCRIPTIONS Meets the product
standard's requirements.

**10.3 DEGREE OF
PROTECTION OF
ASSEMBLIES** Does not apply, since the
entire switchgear needs to
be evaluated.

10.4 CLEARANCES AND CREEPAGE DISTANCES	Meets the product standard's requirements.
10.5 PROTECTION AGAINST ELECTRIC SHOCK	Does not apply, since the entire switchgear needs to be evaluated.
10.6 INCORPORATION OF SWITCHING DEVICES AND COMPONENTS	Does not apply, since the entire switchgear needs to be evaluated.
10.7 INTERNAL ELECTRICAL CIRCUITS AND CONNECTIONS	Is the panel builder's responsibility.
10.8 CONNECTIONS FOR EXTERNAL CONDUCTORS	Is the panel builder's responsibility.
10.9.2 POWER-FREQUENCY ELECTRIC STRENGTH	Is the panel builder's responsibility.
10.9.3 IMPULSE WITHSTAND VOLTAGE	Is the panel builder's responsibility.
10.9.4 TESTING OF ENCLOSURES MADE OF INSULATING MATERIAL	Is the panel builder's responsibility.
EQUIPMENT HEAT DISSIPATION, CURRENT-DEPENDENT PVID	0 W
HEAT DISSIPATION CAPACITY PDISS	0 W
HEAT DISSIPATION PER POLE, CURRENT-DEPENDENT PVID	0 W
RATED OPERATIONAL CURRENT FOR SPECIFIED HEAT DISSIPATION (IN)	0 A
STATIC HEAT DISSIPATION, NON-CURRENT-DEPENDENT PVS	0 W

General information

DEGREE OF PROTECTION	IP66
OPENING DIAMETER	22 mm
PRODUCT CATEGORY	Accessories

Resources

CATALOGUES	eaton-pushbuttons-signal-towers-sensors-assortment-overview-catalog-ca047003en-en-us.pdf
DRAWINGS	eaton-operating-label-m22-legend-holder-dimensions.eps eaton-operating-mounting-m22-legend-holder-dimensions.eps

	eaton-operating-actuation-m22-legend-holder-dimensions.eps eaton-operating-mounting-m22-legend-holder-dimensions-003.eps eaton-operating-mounting-m22-legend-holder-dimensions-002.eps
ECAD MODEL	ETN.216501.edz
INSTALLATION INSTRUCTIONS	IL04716002Z
MCAD MODEL	eaton-accessory-mcad-drawings-tastenzusatzschild.dwg DA-CS-tastenzusatzschild
PEP ECO-PASSPORT	eaton-pushbu-switch-renewal-parts-accessory-pep-eato-00050-v0101-en.pdf

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

DATE:



Eaton Corporation plc Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2026 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

