

Specifications



Photo is representative

Eaton 216562

Eaton Moeller® series M22 LED element, green, base fixing, 12-30VAC/DC

General specifications

PRODUCT NAME	Eaton Moeller® series M22 LED element
CATALOG NUMBER	216562
MODEL CODE	M22-LEDC-G
EAN	4015082165628
PRODUCT LENGTH/DEPTH	38 mm
PRODUCT HEIGHT	10 mm
PRODUCT WIDTH	37 mm
PRODUCT WEIGHT	0.011 kg
COMPLIANCES	CE Marked
CERTIFICATIONS	CSA Std. C22.2 No. 14-05 UL 508 CSA Std. C22.2 No. 94-91 EN 60947-5 IEC 60947-5 VDE CSA-C22.2 No. 94-91 CSA File No.: 012528 IEC 60947-5-1 UL File No.: E29184 CSA-C22.2 No. 14-05 CE CSA UL CSA Class No.: 3211-03 IEC/EN 60947-5 UL Category Control No.: NKCR



Powering Business Worldwide

Climatic environmental conditions

AMBIENT OPERATING TEMPERATURE - MAX	70 °C
-------------------------------------	-------

AMBIENT STORAGE TEMPERATURE - MAX	80 °C
-----------------------------------	-------

AMBIENT OPERATING TEMPERATURE - MIN	-25 °C
-------------------------------------	--------

AMBIENT STORAGE TEMPERATURE - MIN	-40 °C
-----------------------------------	--------

CLIMATIC PROOFING	Damp heat, cyclic, to IEC 60068-2-30 Damp heat, constant, to IEC 60068-2-78
-------------------	--

Contacts

FORCE FOR POSITIVE OPENING - MIN	0 N
----------------------------------	-----

Communication

CONNECTION TO SMARTWIRE-DT	No
----------------------------	----

Design verification

10.10 TEMPERATURE RISE	The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.
------------------------	--

10.11 SHORT-CIRCUIT RATING	Is the panel builder's responsibility. The specifications for the switchgear must be observed.
----------------------------	--

10.12 ELECTROMAGNETIC COMPATIBILITY	Is the panel builder's responsibility. The specifications for the switchgear must be observed.
-------------------------------------	--

10.13 MECHANICAL FUNCTION	The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.
---------------------------	--

10.2.2 CORROSION RESISTANCE	Meets the product standard's requirements.
-----------------------------	--

10.2.3.1 VERIFICATION OF THERMAL STABILITY OF ENCLOSURES	Meets the product standard's requirements.
--	--

10.2.3.2 VERIFICATION OF RESISTANCE OF INSULATING MATERIALS TO NORMAL HEAT	Meets the product standard's requirements.
--	--

10.2.3.3 RESIST. OF INSUL. MAT. TO ABNORMAL HEAT/FIRE BY INTERNAL ELECT. EFFECTS	Meets the product standard's requirements.
--	--

10.2.4 RESISTANCE TO	Meets the product
----------------------	-------------------

ULTRA-VIOLET (UV) RADIATION	standard's requirements.
10.2.5 LIFTING	Does not apply, since the entire switchgear needs to be evaluated.
10.2.6 MECHANICAL IMPACT	Does not apply, since the entire switchgear needs to be evaluated.
10.2.7 INSCRIPTIONS	Meets the product standard's requirements.
10.3 DEGREE OF PROTECTION OF ASSEMBLIES	Does not apply, since the entire switchgear needs to be evaluated.
10.4 CLEARANCES AND CREEPAGE DISTANCES	Meets the product standard's requirements.
10.5 PROTECTION AGAINST ELECTRIC SHOCK	Does not apply, since the entire switchgear needs to be evaluated.
10.6 INCORPORATION OF SWITCHING DEVICES AND COMPONENTS	Does not apply, since the entire switchgear needs to be evaluated.
10.7 INTERNAL ELECTRICAL CIRCUITS AND CONNECTIONS	Is the panel builder's responsibility.
10.8 CONNECTIONS FOR EXTERNAL CONDUCTORS	Is the panel builder's responsibility.
10.9.2 POWER-FREQUENCY ELECTRIC STRENGTH	Is the panel builder's responsibility.
10.9.3 IMPULSE WITHSTAND VOLTAGE	Is the panel builder's responsibility.
10.9.4 TESTING OF ENCLOSURES MADE OF INSULATING MATERIAL	Is the panel builder's responsibility.
EQUIPMENT HEAT DISSIPATION, CURRENT-DEPENDENT PVID	0 W
HEAT DISSIPATION CAPACITY PDISS	0 W
HEAT DISSIPATION PER POLE, CURRENT-DEPENDENT PVID	0 W
RATED OPERATIONAL CURRENT FOR SPECIFIED HEAT DISSIPATION (IN)	0 A
STATIC HEAT DISSIPATION, NON-CURRENT-DEPENDENT PVS	0.45 W

Electrical rating

POWER CONSUMPTION	Max. 0.26 W
-------------------	-------------

RATED INSULATION VOLTAGE (UI)	500 V
-------------------------------	-------

RATED OPERATIONAL CURRENT (IE) - MAX	14 mA
--------------------------------------	-------

RATED OPERATIONAL CURRENT (IE) - MIN	5 mA
--------------------------------------	------

RATED OPERATIONAL VOLTAGE (UE) AT AC - MAX	30 V
--	------

RATED OPERATIONAL VOLTAGE (UE) AT AC - MIN	12 V
--	------

RATED OPERATIONAL VOLTAGE (UE) AT DC - MAX	30 V
--	------

RATED OPERATIONAL VOLTAGE (UE) AT DC - MIN	12 V
--	------

General information

DEGREE OF PROTECTION	IP20
----------------------	------

LIFESPAN, ELECTRICAL	100,000 h (at 25°C, according to EN60064)
----------------------	---

OPERATING TORQUE	0.8 Nm
------------------	--------

OVERVOLTAGE CATEGORY	III
----------------------	-----

POLLUTION DEGREE	3
------------------	---

RATED IMPULSE WITHSTAND VOLTAGE (UIMP)	6000 V AC
--	-----------

VOLTAGE TYPE	AC/DC
--------------	-------

Mounting details

CONNECTION TYPE	Base fixing
-----------------	-------------

MOUNTING POSITION	As required
-------------------	-------------

Features & functions

FITTED WITH:	Diode Light source
--------------	-----------------------

LIGHT COLOR	Green
-------------	-------

LED Details

LIGHT COLOR	Green
-------------	-------

Terminal capacities

TERMINAL CAPACITY (SOLID)	0.75 - 2.5 mm ²
---------------------------	----------------------------

TERMINAL CAPACITY (STRANDED)	0.5 - 2.5 mm ²
------------------------------	---------------------------

Resources

CATALOGUES	eaton-pushbuttons-signal-towers-sensors-assortment-overview-catalog-ca047003en-en-us.pdf
DECLARATIONS OF CONFORMITY	eaton-led-element-declaration-of-conformity-eu260070en.pdf
DRAWINGS	eaton-operating-button-symbol-004.eps eaton-operating-led-m22-led-element-standards.eps
ECAD MODEL	ETN.216562.edz
INSTALLATION INSTRUCTIONS	eaton-operating-devices-rmq-titan-m22-instruction-leaflet-il047018zu.pdf IL04716002Z
MCAD MODEL	DA-CS-led element schraube boden eaton-lampblock-mcad-drawings-led-element-schraube-boden.dwg
PEP ECO-PASSPORT	eaton-lamp-holder-blocks-pep-eato-00309-v0101-en.pdf

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

DATE:



Eaton Corporation plc Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2026 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

