

Specifications



Eaton 248432

Eaton Distribution board accessory,
Auxiliary contact, 1N/O+1N/C, 8 A, 250 V AC

General specifications

PRODUCT NAME	Eaton distribution board accessory
CATALOG NUMBER	248432
MODEL CODE	Z-HK
EAN	4015082484323
PRODUCT LENGTH/DEPTH	80 mm
PRODUCT HEIGHT	65.5 mm
PRODUCT WIDTH	8.8 mm
PRODUCT WEIGHT	0.04 kg
COMPLIANCES	RoHS conform
CERTIFICATIONS	EN45545-2 IEC 61373

Product specifications

USED WITH	Auxiliary contacts Accessory for residual current circuit breaker Accessory
ACCESSORY/SPARE PART TYPE	Auxiliary contacts
MOUNTING METHOD	For fitting on left to: FI
ADDITIONAL EQUIPMENT REQUIRED	Auxiliary switch
AMBIENT OPERATING TEMPERATURE - MAX	55 °C
AMBIENT OPERATING TEMPERATURE - MIN	-5 °C
ASSEMBLY WIDTH	0.5
NUMBER OF CONTACTS (CHANGE-OVER CONTACTS)	0
NUMBER OF CONTACTS (NORMALLY CLOSED CONTACTS)	1
NUMBER OF CONTACTS (NORMALLY OPEN CONTACTS)	1
NUMBER OF POLES AT MAIN CONTACT UNIT - MAX	2
NUMBER OF SWITCHES (FAULT SIGNAL)	0
VOLTAGE TYPE	AC
FUNCTIONS	Auxiliary switch
DEVICE FITTING	Earth leakage switch
TYPE	• Accessory • Accessory for residual current circuit breaker
APPLICATION	Switchgear for industrial and advanced commercial applications
RATED OPERATIONAL VOLTAGE (UE) - MAX	230 V
RATED SWITCH CURRENT	3 A
SUITABLE FOR CURRENT OF MAIN CONTACT UNIT - MAX	8 A

Resources

DECLARATIONS OF CONFORMITY	eaton-distribution-parts-declaration-of-conformity-eu250437en.pdf
DRAWINGS	eaton-dimensions-mas-hk.jpg eaton-dimensions-mas-z-hk.eps
ECAD MODEL	DA-CE-ETN.Z-HK
INSTALLATION INSTRUCTIONS	IL019072ZU
MCAD MODEL	eaton-auxiliary-switches-mcad-drawings-z-fam-z-fw-003-z-hk-fip-xhi11.dwg z_hk.stp
WIRING DIAGRAMS	HK

PROJECT NAME:
PROJECT NUMBER:
PREPARED BY:
DATE:



Eaton Corporation plc Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2026 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

