

Specifications



Eaton 248442

Eaton Distribution parts. Shunt release, up to 125A, 110-415V, 1.5HP

General specifications

PRODUCT NAME	Eaton Shunt trip
CATALOG NUMBER	248442
MODEL CODE	Z-LHASA/230
EAN	4015082484422
PRODUCT LENGTH/DEPTH	80 mm
PRODUCT HEIGHT	75 mm
PRODUCT WIDTH	39.1 mm
PRODUCT WEIGHT	0.158 kg
COMPLIANCES	RoHS conform
CERTIFICATIONS	EN45545-2 IEC 61373



Powering Business Worldwide

Product specifications

USED WITH	Shunt releases
ACCESSORY/SPARE PART TYPE	Shunt release
MOUNTING METHOD	For fitting on left to: AZ
ADDITIONAL EQUIPMENT REQUIRED	Shunt release (for power circuit breaker)
AMBIENT OPERATING TEMPERATURE - MAX	40 °C
AMBIENT OPERATING TEMPERATURE - MIN	-5 °C
ASSEMBLY WIDTH	1.5
NUMBER OF CONTACTS (CHANGE-OVER CONTACTS)	0
NUMBER OF CONTACTS (NORMALLY CLOSED CONTACTS)	1
NUMBER OF CONTACTS (NORMALLY OPEN CONTACTS)	1
NUMBER OF POLES AT MAIN CONTACT UNIT - MAX	1
NUMBER OF SWITCHES (FAULT SIGNAL)	0
VOLTAGE TYPE	AC
FUNCTIONS	Shunt release (for power circuit breaker)
DEVICE FITTING	Miniature circuit breaker (MCB)
TYPE	• Accessory • Accessory for miniature circuit breaker
APPLICATION	Switchgear for industrial and advanced commercial applications
RATED OPERATIONAL VOLTAGE (UE) - MAX	230 V
RATED SWITCH CURRENT	2 A
SUITABLE FOR CURRENT OF MAIN CONTACT UNIT - MAX	2 A

Resources

CATALOGUES	eaton-xeffect-industrial-switchgear-range-catalog-ca003002en-en-us.pdf eaton-xpole-accessories-ca019015en-en-us.pdf
DECLARATIONS OF CONFORMITY	eaton-distribution-parts-declaration-of-conformity-eu250432en.pdf eaton-dimensions-ma-lhasa.jpg
DRAWINGS	eaton-dimensions-mas-lhasa.eps ETN.Z-LHASA_230.edz
ECAD MODEL	IL019166ZU
INSTALLATION INSTRUCTIONS	eaton-auxiliary-switches-mcad-drawings-az-xaa-z-bhasa-z-lhasa.dwg z_lhasa_230.stp
MCAD MODEL	Z7_asa
WIRING DIAGRAMS	

PROJECT NAME:
PROJECT NUMBER:
PREPARED BY:
DATE:



Eaton Corporation plc Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2026 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

