

Specifications



Eaton 260176

Eaton Moeller series NZM - Molded Case Circuit Breaker. Door coupling rotary handle, lockable on the handle, size 3

General specifications

PRODUCT NAME	Eaton Moeller series NZM operating element
CATALOG NUMBER	260176
MODEL CODE	NZM3-XTVDV
EAN	4015082601768
PRODUCT LENGTH/DEPTH	75 mm
PRODUCT HEIGHT	190 mm
PRODUCT WIDTH	90 mm
PRODUCT WEIGHT	1.446 kg
COMPLIANCES	UL/CSA IEC RoHS conform
CERTIFICATIONS	IEC60947 UL listed CSA certified CSA (File No. 22086) UL (Category Control Number DIHS) CSA (Class No. 1437-01) UL489 UL (File No. E140305) CE marking CSA-C22.2 No. 5-09



Powering Business Worldwide

Delivery programme

FEATURES	Standard: black / gray Lockable
FITTED WITH:	Padlock
FRAME	NZM3
SPECIAL FEATURES	• Door coupling rotary handle for operating the switch through a closed control panel door • External warning plate/designation label can be clipped on. • Complete including rotary drive and coupling parts • Extension shaft additionally required.
SUITABLE FOR	Switch disconnecter Power circuit breaker
TYPE	Door coupling rotary handle
USED WITH	NZM3(-4), PN3(-4), N(S)3(-4)

Design verification to IEC/EN 61439

10.10 TEMPERATURE RISE	The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.
10.11 SHORT-CIRCUIT RATING	Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.12 ELECTROMAGNETIC COMPATIBILITY	Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.13 MECHANICAL FUNCTION	The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.
10.2.2 CORROSION RESISTANCE	Meets the product standard's requirements.
10.2.3.1 VERIFICATION OF THERMAL STABILITY OF ENCLOSURES	Meets the product standard's requirements.
10.2.3.2 VERIFICATION OF RESISTANCE OF INSULATING MATERIALS TO NORMAL HEAT	Meets the product standard's requirements.
10.2.3.3 RESIST. OF INSUL. MAT. TO ABNORMAL HEAT/FIRE BY INTERNAL ELECT. EFFECTS	Meets the product standard's requirements.
10.2.4 RESISTANCE TO ULTRA-VIOLET (UV) RADIATION	Meets the product standard's requirements.
10.2.5 LIFTING	Does not apply, since the entire switchgear needs to be evaluated.
10.2.6 MECHANICAL IMPACT	Does not apply, since the entire switchgear needs to be evaluated.
10.2.7 INSCRIPTIONS	Meets the product standard's requirements.
10.3 DEGREE OF PROTECTION OF ASSEMBLIES	Does not apply, since the entire switchgear needs to be evaluated.
10.4 CLEARANCES AND CREEPAGE DISTANCES	Meets the product standard's requirements.
10.5 PROTECTION	Does not apply, since the

AGAINST ELECTRIC SHOCK	entire switchgear needs to be evaluated.
10.6 INCORPORATION OF SWITCHING DEVICES AND COMPONENTS	Does not apply, since the entire switchgear needs to be evaluated.
10.7 INTERNAL ELECTRICAL CIRCUITS AND CONNECTIONS	Is the panel builder's responsibility.
10.8 CONNECTIONS FOR EXTERNAL CONDUCTORS	Is the panel builder's responsibility.
10.9.2 POWER-FREQUENCY ELECTRIC STRENGTH	Is the panel builder's responsibility.
10.9.3 IMPULSE WITHSTAND VOLTAGE	Is the panel builder's responsibility.
10.9.4 TESTING OF ENCLOSURES MADE OF INSULATING MATERIAL	Is the panel builder's responsibility.

Technical data - mechanical

COLOR	Black
COVER/DOOR TYPE	Door interlock can be modified such that it can be defeated from the outside using a screwdriver Door interlock can be modified in the unlocked ON position Door can be opened in OFF Door interlock not defeated in the locked OFF and ON positions
DEGREE OF PROTECTION / NEMA ENCLOSURE TYPE	IP66 4X. 12
LOCK NUMBER	Double lockable
LOCKING FACILITY	Modifiable on handle in I position as well With door interlock Lockable on the handle on the switch using up to 3 padlocks
SPECIAL FEATURES	• Door coupling rotary handle for operating the switch through a closed control panel door • External warning plate/designation label can be clipped on. • Complete including rotary drive and coupling parts • Extension shaft additionally required.

Resources

BROCHURES	eaton-feerum-the-whole-grain-solution-success-story-en-us.pdf eaton-digital-nzm-brochure-br013003en-en-us.pdf
CATALOGUES	eaton-digital-nzm-catalog-ca013003en-en-us.pdf eaton-circuit-breaker-door-nzm-rotary-handle-dimensions-003.eps eaton-circuit-breaker-door-nzm-rotary-handle-dimensions-006.eps
DRAWINGS	eaton-circuit-breaker-padlock-nzm-rotary-handle-dimensions.eps eaton-circuit-breaker-door-nzm-rotary-handle-3d-drawing-005.eps
INSTALLATION INSTRUCTIONS	IL01208007Z
INSTALLATION VIDEOS	Introduction of the new digital circuit breaker NZM The new digital NZM Range
MCAD MODEL	eaton-handle-mechanisms-mcad-3d-models-nzm3-xtvd.stp eaton-handle-mechanisms-mcad-drawings-nzm3-xtvd.dwg
TECHNICAL DATA SHEETS	eaton-nzm-technical-information-sheet

PROJECT NAME:
PROJECT NUMBER:
PREPARED BY:
DATE:



Eaton Corporation plc Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2026 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

