

Specifications



Eaton 262414

Eaton Distribution board accessory,
Auxiliary contact, for FAZ, PKNM, 2W, 0.5HP

General specifications

PRODUCT NAME	Eaton distribution board accessory
CATALOG NUMBER	262414
MODEL CODE	FAZ-XAM002
EAN	4015082624149
PRODUCT LENGTH/DEPTH	80 mm
PRODUCT HEIGHT	75.5 mm
PRODUCT WIDTH	8.8 mm
PRODUCT WEIGHT	0.045 kg
COMPLIANCES	RoHS conform
CERTIFICATIONS	CE marking UL (File No. E177451) North America (UL listed, certified by UL for use in Canada) IEC/EN 60947-2 UL (Category Control Number QVNU2, QVNU8) CSA-C22.2 No. 235 UL 1077 CSA (Class No. 3215-30) IEC/EN 60898 EN45545-2 IEC 61373



Powering Business Worldwide

Product specifications

USED WITH	Accessory for miniature circuit breaker Accessory
VOLTAGE RATING	250 V AC
AMPERAGE RATING	4 A
ACCESSORY/SPARE PART TYPE	Auxiliary contacts
DEGREE OF PROTECTION	UL/CSA Type: - IP20 (IEC) IP40
FRAME	Standard front dimension: 45 mm
FREQUENCY RATING	50 Hz / 60 Hz
RATED IMPULSE WITHSTAND VOLTAGE (UIMP)	2.5 kV
MOUNTING METHOD	On MCB
ADDITIONAL EQUIPMENT REQUIRED	Other
ADMISSIBLE BACK-UP FUSE - MAX	4 A gL
TERMINAL PROTECTION	Protection against electric shock to IEC 536
TERMINAL TYPE	Lift terminals
AMBIENT OPERATING TEMPERATURE - MAX	40 °C
AMBIENT OPERATING TEMPERATURE - MIN	-5 °C
ASSEMBLY WIDTH	0.5
CONVENTIONAL THERMAL CURRENT ITH OF AUXILIARY CONTACTS (1-POLE, OPEN)	4 A
ENCLOSURE WIDTH	80 mm
NUMBER OF CONTACTS (CHANGE-OVER CONTACTS)	2
NUMBER OF CONTACTS (NORMALLY CLOSED CONTACTS)	0
NUMBER OF CONTACTS (NORMALLY OPEN CONTACTS)	0
NUMBER OF POLES AT MAIN CONTACT UNIT - MAX	2
NUMBER OF SWITCHES (FAULT SIGNAL)	0

Resources

DECLARATIONS OF CONFORMITY	eaton-distribution-parts-declaration-of-conformity-eu250423en.pdf eaton-distribution-parts-declaration-of-conformity-uk251473en.pdf
DRAWINGS	122I094 eaton-mcb-dimensions-122x149.eps
ECAD MODEL	DA-CE-ETN.FAZ-XAM002
INSTALLATION INSTRUCTIONS	IL1760 xam002.stp
MCAD MODEL	eaton-auxiliary-switches-mcad-drawings-zp-nhk-faz-xam002.dwg
WIRING DIAGRAMS	122S061

RATED CONDITIONAL SHORT-CIRCUIT CURRENT (IQ) WITH 6 A BACK-UP FUSE	1 kA
RATED INSULATION VOLTAGE (UI)	250 VAC
VOLTAGE TYPE	AC
FUNCTIONS	Auxiliary switch
CONTACT FUNCTION	2 C/O
DEVICE FITTING	Earth leakage circuit breaker and miniature circuit breaker (MCB)
TYPE	• Accessory • Accessory for miniature circuit breaker
MOUNTING WIDTH	8.8 mm (0.5 space units)
RATED OPERATIONAL VOLTAGE (UE) - MAX	250 V
RATED SWITCH CURRENT	3 A
VOLTAGE RATING PER CONTACT - MIN	5 VDC
RATED OPERATIONAL CURRENT	3 A (250 V AC-12) 0.5 A (110 V DC-13) 2 A (250 V AC-15)
TERMINAL CAPACITY (CABLE)	0.5 mm ² - 2.5 mm ²
TERMINAL CAPACITY (SOLID WIRE)	0.5 mm ² - 2.5 mm ²

PROJECT NAME:
PROJECT NUMBER:
PREPARED BY:
DATE:



Eaton Corporation plc Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2026 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

