

Specifications



Eaton 264024

Eaton xEffect Ci Enclosures Switch- & Controlgear Enclosure. Insulated enclosure, removable flanges equipped, HxWxD=546x421x225mm, NA type

General specifications

PRODUCT NAME	Eaton xEffect Ci Enclosures Switch- & Controlgear Enclosure
CATALOG NUMBER	264024
MODEL CODE	CI45-200-NA
EAN	4015082640248
PRODUCT LENGTH/DEPTH	225 mm
PRODUCT HEIGHT	546 mm
PRODUCT WIDTH	421 mm
PRODUCT WEIGHT	3.523 kg
COMPLIANCES	CE marking UL 508A CSA-C22.2 No.94 IEC/EN62208 RoHS conform
CERTIFICATIONS	Specially designed for North America UL (Category Control Number NITW) UL (File No. E499317) UL508A UL listed



Powering Business Worldwide

Product specifications

USED WITH	Industrial control panels
SPECIAL FEATURES	Fitted with removable smooth flanges on all 4 sides Fixing straps for wall fixing Sealable cover fasteners
TYPE	Basic enclosure Distribution board enclosures for North America Panel enclosures with cover and flanges xEnergy Safety Ci
FEATURES	UV resistance beneath protective shield Cover with overpressure release
10.10 TEMPERATURE RISE	The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.
10.11 SHORT-CIRCUIT RATING	Is the panel builder's responsibility.
10.12 ELECTROMAGNETIC COMPATIBILITY	Is the panel builder's responsibility.
10.13 MECHANICAL FUNCTION	Meets the product standard's requirements.
10.2.2 CORROSION RESISTANCE	Meets the product standard's requirements.
10.2.3.1 VERIFICATION OF THERMAL STABILITY OF ENCLOSURES	Meets the product standard's requirements.
10.2.3.2 VERIFICATION OF RESISTANCE OF INSULATING MATERIALS TO NORMAL HEAT	Meets the product standard's requirements.
10.2.3.3 RESIST. OF INSUL. MAT. TO ABNORMAL HEAT/FIRE BY INTERNAL ELECT. EFFECTS	Lower part: 960 °C / cover: 850 °C
10.2.4 RESISTANCE TO ULTRA-VIOLET (UV) RADIATION	Not relevant to indoor installations.
10.2.5 LIFTING	30 kg per enclosure with support frame and lifting aid met; assembled and secured as per the latest applicable instruction leaflet.
10.2.6 MECHANICAL	IK10

Resources

CERTIFICATION REPORTS	eaton-xeffect-ci-certificate-of-compliance-en-us.pdf
DECLARATIONS OF CONFORMITY	eaton-empty-enclosure-declaration-of-conformity-eu250306en.pdf
DRAWINGS	eaton-enclosures-flanges-xeffect-ci-enclosure-dimensions-002.eps
	eaton-enclosures-enclosure-xenergy-safety-ci-lv-systems-dimensions-016.eps
	eaton-enclosures-enclosure-xenergy-safety-ci-lv-systems-dimensions-017.eps
	eaton-enclosures-xenergy-safety-ci-lv-systems-dimensions-009.eps
	eaton-enclosures-flanges-xeffect-ci-enclosure-dimensions-003.eps
INSTALLATION INSTRUCTIONS	05670392.pdf eaton-xenergy-safety-ci-enclosure-brochure-br014001en-en-us.pdf
INSTALLATION VIDEOS	xEffect CI stand-alone polycarbonate enclosure
MCAD MODEL	ci45_200_na.stp eaton-front-access-switchboard-mcad-drawings-ci45-200-na.dwg
PEP ECO-PASSPORT	eaton-front-access-switchboard-pep-eato-00214-v0101-en.pdf

IMPACT	
10.2.7 INSCRIPTIONS	Meets the product standard's requirements.
10.3 DEGREE OF PROTECTION OF ASSEMBLIES	IP65
10.4 CLEARANCES AND CREEPAGE DISTANCES	Is the panel builder's responsibility.
10.5 PROTECTION AGAINST ELECTRIC SHOCK	Protection class 2, therefore not applicable.
10.6 INCORPORATION OF SWITCHING DEVICES AND COMPONENTS	Is the panel builder's responsibility.
10.7 INTERNAL ELECTRICAL CIRCUITS AND CONNECTIONS	Is the panel builder's responsibility.
10.8 CONNECTIONS FOR EXTERNAL CONDUCTORS	Is the panel builder's responsibility.
10.9.2 POWER-FREQUENCY ELECTRIC STRENGTH	Ui = 1000 V AC
10.9.3 IMPULSE WITHSTAND VOLTAGE	8 kV
10.9.4 TESTING OF ENCLOSURES MADE OF INSULATING MATERIAL	Meets the product standard's requirements.
SURFACE FINISHING	RAL 7035, light gray (base) Transparent, smoky gray (cover)
CLIMATIC PROOFING	Damp heat, cyclic, to IEC 60068-2-30 Damp heat, constant, to IEC 60068-2-78
CREEPAGE RESISTANCE	KB160, KC175 (base, to IEC 60112) KB100, KC200 (cover, to IEC 60112)
DEGREE OF PROTECTION	IK10 IP65 (IEC) UL/CSA Types 1, 12, 13, 4X, indoor only 4X (NEMA) IP65
ENCLOSURE MATERIAL	Plastic
SURFACE PROTECTION	Other
CIRCUIT INTEGRITY	Other
BASE TYPE	Enclosure side plates with removable smooth flanges
UNIT TYPE	Single unit
BUILT-IN DEPTH	200 mm

HEAT DISS. AMBIENT 35°C DELTA T:20°C WALL MOUNT INDIVID. ENCL. TOP (IEC 60890)	36 W
HEAT DISS. AMBIENT 35°C DELTA T: 20°C WALL MOUNT MIDDLE ENCL. TOP (IEC 60890)	31 W
HEAT DISS. AMBIENT 35°C DELTA T:20°C WALL MOUNT STARTING ENCL. TOP (IEC 60890)	33 W
HEAT DISS. AMBIENT 35°C DELTA T:35°C WALL MOUNT INDIVID. ENCL. TOP (IEC 60890)	72 W
HEAT DISS. AMBIENT 35°C DELTA T: 35°C WALL MOUNT MIDDLE ENCL. TOP (IEC 60890)	62 W
HEAT DISS. AMBIENT 35°C DELTA T:35°C WALL MOUNT STARTING ENCL. TOP (IEC 60890)	67 W
COLOR	Gray
COVER/DOOR COLOR	Transparent
COVER/DOOR MODEL	Closed
COVER/DOOR TYPE	None Cover Transparent
NUMBER OF OPENINGS (FLANGE PLATES)	0
PLATE THICKNESS (CABINET)	6 mm
PLATE THICKNESS (COVER/DOOR)	6 mm
RAL-NUMBER	7035
SURFACE RESISTANCE (IEC 60093)	10 TΩ
WIDTH IN NUMBER OF MODULAR SPACINGS	17
AMBIENT OPERATING TEMPERATURE DETAILS	-40 °C - 80 °C
MOUNTING METHOD	Surface mounted (plaster)
NUMBER OF ROWS	0
DIELECTRIC STRENGTH	30 kV/mm
FUNCTIONS	Extension possible
PROTECTION CLASS	II
NUMBER OF MODULES	1
INTERNAL DEPTH	200 mm

MOUNTING DEPTH	200 mm
NOMINAL CURRENT	1600 A
NUMBER OF CONDUIT INLETS	0
SUITABLE FOR	Lightning protection Outdoor use
SALINE SPRAY RESISTANCE	IEC 60068-2-11
ENCLOSURE MATERIAL QUALITY	Other
TYPE OF COATING	Other

PROJECT NAME:
PROJECT NUMBER:
PREPARED BY:
DATE:



Eaton Corporation plc Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2026 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

