

Specifications



Photo is representative

Eaton 264978

Eaton Moeller series xPole - PLS6/M
Miniature circuit breaker (MCB), 25 A, 3p,
characteristic: OV

General specifications

PRODUCT NAME	Eaton Moeller series xPole - PLS6/M MCB
CATALOG NUMBER	264978
MODEL CODE	PLSM-OV25/3
EAN	4015082649784
PRODUCT LENGTH/DEPTH	80 mm
PRODUCT HEIGHT	72 mm
PRODUCT WIDTH	52.8 mm
PRODUCT WEIGHT	0.36 kg
COMPLIANCES	RoHS conform

Additional information

CURRENT LIMITING CLASS	3
FEATURES	Additional equipment possible
SPECIAL FEATURES	Ambient temperature hint: a 1 °C increase results in a 0.5% linear reduction of current carrying capacity
USED WITH	PLSM Miniature circuit breaker

Design verification to IEC/EN 61439 - technical data

AMBIENT OPERATING TEMPERATURE - MAX	75 °C
AMBIENT OPERATING TEMPERATURE - MIN	-25 °C
HEAT DISSIPATION CAPACITY	0 W
HEAT DISSIPATION PER POLE, CURRENT-DEPENDENT	0 W
RATED OPERATIONAL CURRENT FOR SPECIFIED HEAT DISSIPATION (IN)	25 A
STATIC HEAT DISSIPATION, NON-CURRENT-DEPENDENT	0 W

Delivery programme

AMPERAGE RATING	25 A
APPLICATION	- Switchgear for residential and commercial applications - xPole - Switchgear for residential and commercial applications
NUMBER OF POLES	Three-pole
NUMBER OF POLES (PROTECTED)	3
NUMBER OF POLES (TOTAL)	3
RELEASE CHARACTERISTIC	Other
TYPE	- Miniature circuit breaker - PLSM

Technical data - electrical

FREQUENCY RATING - MAX	60 Hz
FREQUENCY RATING - MIN	50 Hz
OVERVOLTAGE CATEGORY	III
POLLUTION DEGREE	2
RATED IMPULSE WITHSTAND VOLTAGE (UIMP)	4 kV
RATED INSULATION VOLTAGE (UI)	440 V
RATED OPERATIONAL VOLTAGE (UE) - MAX	400 V
RATED SHORT-CIRCUIT BREAKING CAPACITY (IEC/EN 60898-1) - ICN AT 230 V	10 kA
RATED SHORT-CIRCUIT BREAKING CAPACITY (IEC/EN 60898-1)- ICN AT 400 V	10 kA
VOLTAGE TYPE	AC

Technical data - mechanical

BUILT-IN DEPTH 70.5 mm

**CONNECTABLE
CONDUCTOR CROSS
SECTION (MULTI-WIRED)
- MAX** 25 mm²

**CONNECTABLE
CONDUCTOR CROSS
SECTION (MULTI-WIRED)
- MIN** 1 mm²

**CONNECTABLE
CONDUCTOR CROSS
SECTION (SOLID-CORE) -
MAX** 25 mm²

**CONNECTABLE
CONDUCTOR CROSS
SECTION (SOLID-CORE) -
MIN** 1 mm²

DEGREE OF PROTECTION IP20

**WIDTH IN NUMBER OF
MODULAR SPACINGS** 3

Resources

CATALOGUES [eaton-xpole-protective-devices-catalog-ca019014en-en-us.pdf](#)

**DECLARATIONS OF
CONFORMITY** [eaton-mcb-declaration-of-conformity-eu251398en.pdf](#)
[eaton-mcb-declaration-of-conformity-uk251442en.pdf](#)

ECAD MODEL [ETN.PLSM-OV25_3.edz](#)

**INSTALLATION
INSTRUCTIONS** [eaton-mcb-rccb-rcbo-g9-il019140zu.pdf](#)

MCAD MODEL [eaton-non-selective-universal-mcb-mcad-3d-models-faz-xxx-3p.stp](#)
[pls_3p.stp](#)

PEP ECO-PASSPORT [eaton-non-selective-universal-mcb-pep-eato-00046-v0102-en.pdf](#)

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

DATE:



Eaton Corporation plc Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2026 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

