

Specifications



Eaton 266029

Eaton Moeller series NZM - Molded Case Circuit Breaker. Switch-disconnector 4p 800A BG4

General specifications

PRODUCT NAME	Eaton Moeller series NZM switch-disconnector
CATALOG NUMBER	266029
MODEL CODE	N4-4-800
EAN	4015082660291
PRODUCT LENGTH/DEPTH	401 mm
PRODUCT HEIGHT	207 mm
PRODUCT WIDTH	280 mm
PRODUCT WEIGHT	22.723 kg
COMPLIANCES	RoHS conform
CERTIFICATIONS	IEC/EN 60947 IEC

Additional information

FUNCTIONS

Disconnectors/main
switches
Interlockable
Voltage release optional

Delivery programme

AMPERAGE RATING 800 A

APPLICATION Use in unearthed supply
systems at 525 V

**CIRCUIT BREAKER FRAME
TYPE** N4

FEATURES Motor drive optional
Version as main switch
Version as maintenance-
/service switch
Version as emergency stop
installation

NUMBER OF POLES Four-pole

SPECIAL FEATURES

- Main switch characteristics including positive drive to IEC/EN 60204 and VDE 0113.
- Isolating characteristics to IEC/EN 60947-3 and VDE 0660.
- Busbar tag shroud to VDE 0160 Part 100.
- Rated current = rated uninterrupted current: 800 A

TYPE Switch-disconnector

Design verification to IEC/EN 61439

10.10 TEMPERATURE RISE	The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.
10.11 SHORT-CIRCUIT RATING	Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.12 ELECTROMAGNETIC COMPATIBILITY	Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.13 MECHANICAL FUNCTION	The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.
10.2.2 CORROSION RESISTANCE	Meets the product standard's requirements.
10.2.3.1 VERIFICATION OF THERMAL STABILITY OF ENCLOSURES	Meets the product standard's requirements.
10.2.3.2 VERIFICATION OF RESISTANCE OF INSULATING MATERIALS TO NORMAL HEAT	Meets the product standard's requirements.
10.2.3.3 RESIST. OF INSUL. MAT. TO ABNORMAL HEAT/FIRE BY INTERNAL ELECT. EFFECTS	Meets the product standard's requirements.
10.2.4 RESISTANCE TO ULTRA-VIOLET (UV) RADIATION	Meets the product standard's requirements.
10.2.5 LIFTING	Does not apply, since the entire switchgear needs to be evaluated.
10.2.6 MECHANICAL IMPACT	Does not apply, since the entire switchgear needs to be evaluated.
10.2.7 INSCRIPTIONS	Meets the product standard's requirements.
10.3 DEGREE OF PROTECTION OF ASSEMBLIES	Does not apply, since the entire switchgear needs to be evaluated.
10.4 CLEARANCES AND CREEPAGE DISTANCES	Meets the product standard's requirements.
10.5 PROTECTION	Does not apply, since the

Design verification to IEC/EN 61439 - technical data

AMBIENT OPERATING TEMPERATURE - MAX	70 °C
AMBIENT STORAGE TEMPERATURE - MAX	70 °C
AMBIENT OPERATING TEMPERATURE - MIN	-25 °C
AMBIENT STORAGE TEMPERATURE - MIN	-40 °C
EQUIPMENT HEAT DISSIPATION, CURRENT-DEPENDENT	79 W
RATED OPERATIONAL CURRENT FOR SPECIFIED HEAT DISSIPATION (IN)	800 A

AGAINST ELECTRIC SHOCK	entire switchgear needs to be evaluated.
10.6 INCORPORATION OF SWITCHING DEVICES AND COMPONENTS	Does not apply, since the entire switchgear needs to be evaluated.
10.7 INTERNAL ELECTRICAL CIRCUITS AND CONNECTIONS	Is the panel builder's responsibility.
10.8 CONNECTIONS FOR EXTERNAL CONDUCTORS	Is the panel builder's responsibility.
10.9.2 POWER-FREQUENCY ELECTRIC STRENGTH	Is the panel builder's responsibility.
10.9.3 IMPULSE WITHSTAND VOLTAGE	Is the panel builder's responsibility.
10.9.4 TESTING OF ENCLOSURES MADE OF INSULATING MATERIAL	Is the panel builder's responsibility.

Technical data - electrical

AMPERAGE RATING	800 A
DIRECTION OF INCOMING SUPPLY	As required
ELECTRICAL CONNECTION TYPE OF MAIN CIRCUIT	Bolt connection
HANDLE TYPE	Rocker lever
ISOLATION	500 V AC (between auxiliary contacts and main contacts) 300 V AC (between the auxiliary contacts)
LIFESPAN, ELECTRICAL	1000 operations at 690 V AC-3 2000 operations at 690 V AC-1 2000 operations at 415 V AC-3 3000 operations at 415 V AC-1 2000 operations at 400 V AC-3 3000 operations at 400 V AC-1
NUMBER OF OPERATIONS PER HOUR - MAX	60
OVERVOLTAGE CATEGORY	III
POLLUTION DEGREE	3
RATED CONDITIONAL SHORT-CIRCUIT CURRENT WITH BACK-UP FUSE	80 kA at 690 V N4-630...1600: 2 x 800 AgGgL 100 kA at 400/415 V
RATED CONDITIONAL SHORT-CIRCUIT CURRENT WITH DOWNSTREAM FUSE	80 kA at 690 V 100 kA at 400/415 V N4-630...1600: 2 x 800 AgGgL
RATED IMPULSE WITHSTAND VOLTAGE (UIMP) AT AUXILIARY CONTACTS	6000 V
RATED IMPULSE WITHSTAND VOLTAGE (UIMP) AT MAIN CONTACTS	8000 V
RATED INSULATION VOLTAGE (UI)	1000 V
RATED OPERATING FREQUENCY	50 Hz
RATED OPERATING POWER AT AC-23, 400 V	450 kW

Technical data - mechanical

CLIMATIC PROOFING	Damp heat, constant, to IEC 60068-2-78 Damp heat, cyclic, to IEC 60068-2-30
DEGREE OF PROTECTION	IP20 (basic protection type, in the area of the HMI devices) Other
DEGREE OF PROTECTION (IP), FRONT SIDE	IP40 (with insulating surround) IP20 IP66 (with door coupling rotary handle)
DEGREE OF PROTECTION (TERMINATIONS)	IP10 (tunnel terminal) IP00 (terminations, phase isolator and band terminal)
HANDLE COLOR	Black
LIFESPAN, MECHANICAL	10000 operations
MOUNTING METHOD	Intermediate mounting Fixed Distribution board installation Ground mounting Built-in device fixed built-in technique
NUMBER OF AUXILIARY CONTACTS (CHANGE-OVER CONTACTS)	0
NUMBER OF AUXILIARY CONTACTS (NORMALLY CLOSED CONTACTS)	0
NUMBER OF AUXILIARY CONTACTS (NORMALLY OPEN CONTACTS)	0
NUMBER OF SWITCHES	1
PROTECTION AGAINST DIRECT CONTACT	Finger and back-of-hand proof to DIN EN 50274/VDE 0106 part 263
SHOCK RESISTANCE	15 g (half-sinusoidal shock 11 ms)
SPECIAL FEATURES	- Main switch characteristics including positive drive to IEC/EN 60204 and VDE 0113. - Isolating characteristics to IEC/EN 60947-3 and VDE 0660.

RATED OPERATING VOLTAGE (UE) AT AC - MAX	690 V
RATED OPERATIONAL CURRENT	1600 A (690 V AC-22/23A, making and breaking capacity) 1600 A (415 V AC-22/23A, making and breaking capacity)
RATED SHORT-CIRCUIT MAKING CAPACITY ICM AT 690 V, 50/60 HZ	53 kA
RATED SHORT-TIME WITHSTAND CURRENT (ICW)	25 kA
RATED SHORT-TIME WITHSTAND CURRENT (T = 0.3 S)	25 kA
RATED SHORT-TIME WITHSTAND CURRENT (T = 1 S)	25 kA
SHORT-CIRCUIT PROTECTIVE DEVICE FUSES - MAX	1600 A gL
VOLTAGE RATING	690 V - 690 V

	• Busbar tag shroud to VDE 0160 Part 100. • Rated current = rated uninterrupted current: 800 A
SWITCH POSITIONS	I, +, 0

Technical data - mechanical - terminals

OPTIONAL TERMINALS	Connection on rear. Strip terminal. Tunnel terminal
STANDARD TERMINALS	Screw terminal
TERMINAL CAPACITY (ALUMINUM SOLID CONDUCTOR/CABLE)	240 mm ² (2x) at rear-side width extension 70 mm ² - 240 mm ² (6x) at rear-side width extension
TERMINAL CAPACITY (ALUMINUM STRANDED CONDUCTOR/CABLE)	50 mm ² - 240 mm ² (4x) at 4-hole tunnel terminal
TERMINAL CAPACITY (COPPER BUSBAR)	50 mm x 10 mm (2x) at rear-side 2-hole module plate Min. 25 mm x 5 mm direct at switch rear-side connection Max. 80 mm x 10 mm (2x) at rear-side width extension M10 at rear-side screw connection Max. 50 mm x 10 mm (2x) at rear-side 1-hole module plate Max. 50 mm x 10 mm (2x) direct at switch rear-side connection Min. 60 mm x 10 mm at rear-side width extension Min. 25 mm x 5 mm at rear-side 1-hole module plate
TERMINAL CAPACITY (COPPER SOLID CONDUCTOR/CABLE)	50 mm ² - 240 mm ² (4x) at 4-hole tunnel terminal 300 mm ² (4x) at rear-side width extension 95 mm ² - 240 mm ² (6x) at rear-side width extension 185 mm ² - 240 mm ² (1x) at rear-side 1-hole module plate 50 mm ² (4x) at rear-side 2-hole module plate 35 mm ² - 185 mm ² (4x) at rear-side 2-hole module plate 70 mm ² - 185 mm ² (2x) at rear-side 1-hole module plate
TERMINAL CAPACITY (COPPER STRANDED CONDUCTOR/CABLE)	120 mm ² - 185 mm ² (1x) direct at switch rear-side connection 50 mm ² - 185 mm ² (4x) direct at switch rear-side connection

Resources

BROCHURES	eaton-digital-nzm-brochure-br013003en-en-us.pdf eaton-feerum-the-whole-grain-solution-success-story-en-us.pdf
CATALOGUES	eaton-digital-nzm-catalog-ca013003en-en-us.pdf
DECLARATIONS OF CONFORMITY	eaton-switch-disconnector-declaration-of-conformity-eu250128en.pdf
DRAWINGS	eaton-circuit-breaker-nzm-mccb-dimensions-023.eps
ECAD MODEL	DA-CE-ETN.N4-4-800
INSTALLATION INSTRUCTIONS	eaton-circuit-breaker-basic-unit-bg4-il012101zu.pdf
INSTALLATION VIDEOS	Introduction of the new digital circuit breaker NZM The new digital NZM Range
MCAD MODEL	eaton-molded-case-switches-mcad-drawings-nzm4-4p.dwg DA-CS-nzm4_4p
PEP ECO-PASSPORT	eaton-switch-disconnectors-pep-eato-00228-v0101-en.pdf
TECHNICAL DATA SHEETS	eaton-nzm-technical-information-sheet

**TERMINAL CAPACITY
(COPPER STRIP)**

10 segments of 50 mm x 1 mm (2x) at 1-hole module plate
Max. 10 segments of 50 mm x 1 mm (2x) at rear-side connection (punched)

Max. 10 segments of 32 mm x 1 mm (2x) at flat conductor terminal
10 segments of 80 mm x 1 mm (2x) at rear-side width extension
Min. 10 segments of 50 mm x 1 mm (2x) at rear-side connection (punched)

Min. 6 segments of 16 mm x 0.8 mm at flat conductor terminal

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

DATE:



Eaton Corporation plc Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2026 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

