

Specifications



Photo is representative

Eaton 271445

Eaton Moeller series NZM - Molded Case Circuit Breaker. Door coupling rotary handle, black, lockable, size 1, NA type

General specifications

PRODUCT NAME	Eaton Moeller series NZM operating element NA
CATALOG NUMBER	271445
MODEL CODE	NZM1-XTVD-NA
EAN	4015082714451
PRODUCT LENGTH/DEPTH	75 mm
PRODUCT HEIGHT	190 mm
PRODUCT WIDTH	90 mm
PRODUCT WEIGHT	0.619 kg
COMPLIANCES	UL/CSA IEC RoHS conform
CERTIFICATIONS	UL (Category Control Number DIHS) CE marking UL listed CSA (Class No. 1437-01) CSA (File No. 22086) CSA-C22.2 No. 5-09 IEC60947 CSA certified UL (File No. E140305) UL489



Powering Business Worldwide

Delivery programme

FEATURES	Lockable Standard: black / gray
FITTED WITH:	Padlock
FRAME	NZM1
NUMBER OF POLES	Single-pole
SPECIAL FEATURES	• Complete including rotary drive and coupling parts • Extension shaft additionally required. • Cannot be combined with mechanical interlock • External warning plate/designation label can be clipped on. • Door coupling rotary handle for operating the switch through a closed control panel door
SUITABLE FOR	Power circuit breaker Switch disconnecter
TYPE	• Accessory • Door coupling rotary handle
USED WITH	NZM1, N1

Design verification to IEC/EN 61439

10.10 TEMPERATURE RISE	The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.
10.11 SHORT-CIRCUIT RATING	Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.12 ELECTROMAGNETIC COMPATIBILITY	Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.13 MECHANICAL FUNCTION	The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.
10.2.2 CORROSION RESISTANCE	Meets the product standard's requirements.
10.2.3.1 VERIFICATION OF THERMAL STABILITY OF ENCLOSURES	Meets the product standard's requirements.
10.2.3.2 VERIFICATION OF RESISTANCE OF INSULATING MATERIALS TO NORMAL HEAT	Meets the product standard's requirements.
10.2.3.3 RESIST. OF INSUL. MAT. TO ABNORMAL HEAT/FIRE BY INTERNAL ELECT. EFFECTS	Meets the product standard's requirements.
10.2.4 RESISTANCE TO ULTRA-VIOLET (UV) RADIATION	Meets the product standard's requirements.
10.2.5 LIFTING	Does not apply, since the entire switchgear needs to be evaluated.
10.2.6 MECHANICAL IMPACT	Does not apply, since the entire switchgear needs to be evaluated.
10.2.7 INSCRIPTIONS	Meets the product standard's requirements.
10.3 DEGREE OF PROTECTION OF ASSEMBLIES	Does not apply, since the entire switchgear needs to be evaluated.
10.4 CLEARANCES AND CREEPAGE DISTANCES	Meets the product standard's requirements.
10.5 PROTECTION	Does not apply, since the

AGAINST ELECTRIC SHOCK	entire switchgear needs to be evaluated.
10.6 INCORPORATION OF SWITCHING DEVICES AND COMPONENTS	Does not apply, since the entire switchgear needs to be evaluated.
10.7 INTERNAL ELECTRICAL CIRCUITS AND CONNECTIONS	Is the panel builder's responsibility.
10.8 CONNECTIONS FOR EXTERNAL CONDUCTORS	Is the panel builder's responsibility.
10.9.2 POWER-FREQUENCY ELECTRIC STRENGTH	Is the panel builder's responsibility.
10.9.3 IMPULSE WITHSTAND VOLTAGE	Is the panel builder's responsibility.
10.9.4 TESTING OF ENCLOSURES MADE OF INSULATING MATERIAL	Is the panel builder's responsibility.

Technical data - mechanical

COLOR	Black
COVER/DOOR TYPE	Door opens only with active rotation beyond the 0 position Door interlock not defeated in the locked OFF position.
DEGREE OF PROTECTION / NEMA ENCLOSURE TYPE	IP66 4X. 12
LOCK NUMBER	Single lockable
LOCKING FACILITY	Lockable on the 0 position on the handle using up to 3 padlocks With door interlock
SPECIAL FEATURES	• Complete including rotary drive and coupling parts • Extension shaft additionally required. • Cannot be combined with mechanical interlock • External warning plate/designation label can be clipped on. • Door coupling rotary handle for operating the switch through a closed control panel door

Resources

BROCHURES	eaton-digital-nzm-brochure-br013003en-en-us.pdf eaton-feerum-the-whole-grain-solution-success-story-en-us.pdf
CATALOGUES	eaton-digital-nzm-catalog-ca013003en-en-us.pdf eaton-circuit-breaker-door-nzm-rotary-handle-dimensions-010.eps eaton-circuit-breaker-padlock-nzm-rotary-handle-dimensions.eps
DRAWINGS	eaton-circuit-breaker-door-nzm-rotary-handle-dimensions-005.eps eaton-circuit-breaker-door-nzm-rotary-handle-3d-drawing-004.eps
INSTALLATION INSTRUCTIONS	eaton-door-coupling-rotary-handle-nzm1-2-xt-il01203005z.pdf
INSTALLATION VIDEOS	Introduction of the new digital circuit breaker NZM The new digital NZM Range
MCAD MODEL	eaton-handle-mechanisms-mcad-3d-models-nzm1-xtvd.stp eaton-handle-mechanisms-mcad-drawings-nzm1-xtvd.dwg
TECHNICAL DATA SHEETS	eaton-nzm-technical-information-sheet

PROJECT NAME:
PROJECT NUMBER:
PREPARED BY:
DATE:



Eaton Corporation plc Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2026 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

