

Specifications



Photo is representative

Eaton 271459

Eaton Moeller series NZM - Molded Case Circuit Breaker. Tunnel terminal, 3p, 1 page, max. 185mm², size 3

General specifications

PRODUCT NAME	Eaton Moeller series NZM connection type
CATALOG NUMBER	271459
MODEL CODE	NZM3-XKA1
EAN	4015082714598
PRODUCT LENGTH/DEPTH	92.5 mm
PRODUCT HEIGHT	102 mm
PRODUCT WIDTH	137 mm
PRODUCT WEIGHT	0.691 kg
COMPLIANCES	IEC RoHS conform

Additional information

MODEL

Other

Delivery programme

AMPERAGE RATING

□ 350 A (Cu), 225 A (Al)

FRAME

NZM3

NUMBER OF POLES

Three-pole

SUITABLE FOR

Three-pole
Copper cable

TYPE

- Accessory
- Tunnel terminal

USED WITH

NZM3, PN3, N(S)3

Design verification to IEC/EN 61439

10.10 TEMPERATURE RISE	The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.
10.11 SHORT-CIRCUIT RATING	Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.12 ELECTROMAGNETIC COMPATIBILITY	Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.13 MECHANICAL FUNCTION	The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.
10.2.2 CORROSION RESISTANCE	Meets the product standard's requirements.
10.2.3.1 VERIFICATION OF THERMAL STABILITY OF ENCLOSURES	Meets the product standard's requirements.
10.2.3.2 VERIFICATION OF RESISTANCE OF INSULATING MATERIALS TO NORMAL HEAT	Meets the product standard's requirements.
10.2.3.3 RESIST. OF INSUL. MAT. TO ABNORMAL HEAT/FIRE BY INTERNAL ELECT. EFFECTS	Meets the product standard's requirements.
10.2.4 RESISTANCE TO ULTRA-VIOLET (UV) RADIATION	Meets the product standard's requirements.
10.2.5 LIFTING	Does not apply, since the entire switchgear needs to be evaluated.
10.2.6 MECHANICAL IMPACT	Does not apply, since the entire switchgear needs to be evaluated.
10.2.7 INSCRIPTIONS	Meets the product standard's requirements.
10.3 DEGREE OF PROTECTION OF ASSEMBLIES	Does not apply, since the entire switchgear needs to be evaluated.
10.4 CLEARANCES AND CREEPAGE DISTANCES	Meets the product standard's requirements.
10.5 PROTECTION	Does not apply, since the

Technical data - electrical

AMPERAGE RATING

□ 350 A (Cu), 225 A (Al)

AGAINST ELECTRIC SHOCK	entire switchgear needs to be evaluated.
10.6 INCORPORATION OF SWITCHING DEVICES AND COMPONENTS	Does not apply, since the entire switchgear needs to be evaluated.
10.7 INTERNAL ELECTRICAL CIRCUITS AND CONNECTIONS	Is the panel builder's responsibility.
10.8 CONNECTIONS FOR EXTERNAL CONDUCTORS	Is the panel builder's responsibility.
10.9.2 POWER-FREQUENCY ELECTRIC STRENGTH	Is the panel builder's responsibility.
10.9.3 IMPULSE WITHSTAND VOLTAGE	Is the panel builder's responsibility.
10.9.4 TESTING OF ENCLOSURES MADE OF INSULATING MATERIAL	Is the panel builder's responsibility.

Technical data - mechanical - terminals

TERMINAL CAPACITY (STRANDED CABLE)	6 - 350 AWG/kcmil (1x) 16 mm ² - 185 mm ² (1x)
---	---

Resources

BROCHURES

[eaton-digital-nzm-brochure-br013003en-en-us.pdf](#)

[eaton-feerum-the-whole-grain-solution-success-story-en-us.pdf](#)

CATALOGUES

[eaton-digital-nzm-catalog-ca013003en-en-us.pdf](#)

[eaton-circuit-breaker-terminals-nzm-tunnel-terminal-dimensions-002.eps](#)

DRAWINGS

[eaton-general-nzm-tunnel-terminal-dimensions.eps](#)

[eaton-circuit-breaker-terminals-nzm-tunnel-terminal-3d-drawing-004.eps](#)

INSTALLATION INSTRUCTIONS

[eaton-circuit-breaker-tunnel-terminal-nzm2-3-il01210007z.pdf](#)

INSTALLATION VIDEOS

[Introduction of the new digital circuit breaker NZM](#)

[The new digital NZM Range](#)

MCAD MODEL

[eaton-mccb-terminals-mcad-drawings-nzm3-xka1.dwg](#)

[nzm3_xka1.stp](#)

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

DATE:



Eaton Corporation plc Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2026 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

