

Specifications



Eaton 276280

Main load disconnect Switch with isolation function, highly wear resistant contacts and classified for the use in rail rolling stock, 240/415 V, 80 A, 3P

General specifications

PRODUCT NAME	Eaton Moeller series IS Disconnecter
CATALOG NUMBER	276280
MODEL CODE	IS-80/3
EAN	4015082762803
PRODUCT LENGTH/DEPTH	60 mm
PRODUCT HEIGHT	80 mm
PRODUCT WIDTH	53.1 mm
PRODUCT WEIGHT	0.314 kg
COMPLIANCES	RoHS conform
CERTIFICATIONS	CE



Powering Business Worldwide

Delivery program

TYPE	IS. Main load disconnect switch
AMPERAGE RATING	80 A
APPLICATION	Switchgear for industrial and advanced commercial applications
NUMBER OF POLES	Three-pole

Technical data - mechanical

WIDTH IN NUMBER OF MODULAR SPACINGS	3
DEGREE OF PROTECTION	IP40 IP10
BUILT-IN DEPTH	69.5 mm
TERMINALS	Lift terminal
NUMBER OF CONTACTS (CHANGE-OVER CONTACTS)	0
NUMBER OF CONTACTS (NORMALLY OPEN CONTACTS)	3
NUMBER OF CONTACTS (NORMALLY CLOSED CONTACTS)	0
COLOR CALOTTE	Other
LAMP SOCKET	Other
LAMP TYPE	Other
SWITCH TYPE	Other

Additional information

IMPRINT/INDICATION	Symbol "arrows"
---------------------------	-----------------

Technical data - electrical

RATED OPERATIONAL VOLTAGE (UE) - MAX	415 V
VOLTAGE TYPE	AC
RATED SHORT-TIME WITHSTAND CURRENT (ICW)	2 kA
RATED SWITCHING CAPACITY	12.5 kA
VOLTAGE RATING - MIN	240 V

Design verification as per IEC/EN 61439 - technical data

AMBIENT OPERATING TEMPERATURE - MAX	40 °C
AMBIENT OPERATING TEMPERATURE - MIN	-5 °C
HEAT DISSIPATION PER POLE, CURRENT-DEPENDENT	2.6 W
RATED OPERATIONAL CURRENT FOR SPECIFIED HEAT DISSIPATION (IN)	80 A

Resources

DECLARATIONS OF CONFORMITY	eaton-disconnector-declaration-of-conformity-eu250428en.pdf
DRAWINGS	eaton-dimensions-mas-is.jpg 122I172
ECAD MODEL	ETN.IS-80_3.edz
MCAD MODEL	eaton-main-load-disconnector-switch-mcad-drawings-is-3p.dwg

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

DATE:



Eaton Corporation plc Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2026 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

