

Specifications



Eaton 277908

Eaton Moeller® series DILM Contactor, 3 pole, 380 V 400 V 30 kW, RDC 24: 24 - 27 V DC, DC operation, Screw terminals DILM65(RDC24)

General specifications

PRODUCT NAME	Eaton Moeller® series DILM contactor
CATALOG NUMBER	277908
MODEL CODE	DILM65(RDC24)
EAN	4015082779085
PRODUCT LENGTH/DEPTH	132.1 mm
PRODUCT HEIGHT	115 mm
PRODUCT WIDTH	55 mm
PRODUCT WEIGHT	1.052 kg
CERTIFICATIONS	CSA File No.: 012528 CSA-C22.2 No. 60947-4-1-14 UL Category Control No.: NLDX CE CSA Class No.: 2411-03, 3211-04 UL File No.: E29096 IEC/EN 60947 UL 60947-4-1 VDE 0660 UL IEC/EN 60947-4-1 CSA
CATALOG NOTES	Contacts according to EN 50012

Ambient conditions, mechanical

SHOCK RESISTANCE

5 g, N/C auxiliary contact, Mechanical, according to IEC/EN 60068-2-27, Half-sinusoidal shock 10 ms
10 g, N/O main contact, Mechanical, according to IEC/EN 60068-2-27 when tabletop-mounted, Half-sinusoidal shock 10 ms
7 g, N/O auxiliary contact, Mechanical, according to IEC/EN 60068-2-27 when tabletop-mounted, Half-sinusoidal shock 10 ms
5 g, N/C auxiliary contact, Mechanical, according to IEC/EN 60068-2-27 when tabletop-mounted, Half-sinusoidal shock 10 ms
7 g, N/O auxiliary contact, Mechanical, according to IEC/EN 60068-2-27, Half-sinusoidal shock 10 ms
10 g, N/O main contact, Mechanical, according to IEC/EN 60068-2-27, Half-sinusoidal shock 10 ms

Climatic environmental conditions

ALTITUDE	Max. 2000 m
AMBIENT OPERATING TEMPERATURE - MAX	60 °C
AMBIENT STORAGE TEMPERATURE - MAX	80 °C
AMBIENT OPERATING TEMPERATURE - MIN	-25 °C
AMBIENT OPERATING TEMPERATURE (ENCLOSED) - MAX	40 °C
AMBIENT OPERATING TEMPERATURE (ENCLOSED) - MIN	-25 °C
AMBIENT STORAGE TEMPERATURE - MIN	-40 °C
CLIMATIC PROOFING	Damp heat, constant, to IEC 60068-2-78 Damp heat, cyclic, to IEC 60068-2-30

Communication

CONNECTION TO SMARTWIRE-DT	No
----------------------------	----

Contacts

NUMBER OF MAIN CONTACTS (NORMALLY OPEN CONTACT)	3
NUMBER OF AUXILIARY CONTACTS (NORMALLY CLOSED CONTACTS)	0
NUMBER OF AUXILIARY CONTACTS (NORMALLY OPEN CONTACTS)	0
NUMBER OF CONTACTS (NORMALLY CLOSED) AS MAIN CONTACT	0

Conventional thermal current I_{th}

**CONVENTIONAL
THERMAL CURRENT I_{TH}
(1-POLE, ENCLOSED)** 180 A

**CONVENTIONAL
THERMAL CURRENT I_{TH}
(3-POLE, ENCLOSED)** 72 A

**CONVENTIONAL
THERMAL CURRENT I_{TH}
AT 55°C (3-POLE, OPEN)** 83 A

**CONVENTIONAL
THERMAL CURRENT I_{TH}
AT 60°C (3-POLE, OPEN)** 80 A

**CONVENTIONAL
THERMAL CURRENT I_{TH}
OF MAIN CONTACTS (1-
POLE, OPEN)** 200 A

Design verification

10.10 TEMPERATURE RISE The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.

10.11 SHORT-CIRCUIT RATING Is the panel builder's responsibility. The specifications for the switchgear must be observed.

10.12 ELECTROMAGNETIC COMPATIBILITY Is the panel builder's responsibility. The specifications for the switchgear must be observed.

10.13 MECHANICAL FUNCTION The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

10.2.2 CORROSION RESISTANCE Meets the product standard's requirements.

10.2.3.1 VERIFICATION OF THERMAL STABILITY OF ENCLOSURES Meets the product standard's requirements.

10.2.3.2 VERIFICATION OF RESISTANCE OF INSULATING MATERIALS TO NORMAL HEAT Meets the product standard's requirements.

10.2.3.3 RESIST. OF INSUL. MAT. TO ABNORMAL HEAT/FIRE BY INTERNAL ELECT. EFFECTS Meets the product standard's requirements.

10.2.4 RESISTANCE TO ULTRA-VIOLET (UV) RADIATION Meets the product standard's requirements.

10.2.5 LIFTING Does not apply, since the entire switchgear needs to be evaluated.

10.2.6 MECHANICAL IMPACT Does not apply, since the entire switchgear needs to be evaluated.

10.2.7 INSCRIPTIONS Meets the product standard's requirements.

10.3 DEGREE OF PROTECTION OF ASSEMBLIES Does not apply, since the entire switchgear needs to be evaluated.

10.4 CLEARANCES AND CREEPAGE DISTANCES Meets the product standard's requirements.

10.5 PROTECTION Does not apply, since the

AGAINST ELECTRIC SHOCK	entire switchgear needs to be evaluated.
10.6 INCORPORATION OF SWITCHING DEVICES AND COMPONENTS	Does not apply, since the entire switchgear needs to be evaluated.
10.7 INTERNAL ELECTRICAL CIRCUITS AND CONNECTIONS	Is the panel builder's responsibility.
10.8 CONNECTIONS FOR EXTERNAL CONDUCTORS	Is the panel builder's responsibility.
10.9.2 POWER-FREQUENCY ELECTRIC STRENGTH	Is the panel builder's responsibility.
10.9.3 IMPULSE WITHSTAND VOLTAGE	Is the panel builder's responsibility.
10.9.4 TESTING OF ENCLOSURES MADE OF INSULATING MATERIAL	Is the panel builder's responsibility.
EQUIPMENT HEAT DISSIPATION, CURRENT-DEPENDENT PVID	17.1 W
HEAT DISSIPATION CAPACITY PDISS	0 W
HEAT DISSIPATION PER POLE, CURRENT-DEPENDENT PVID	5.7 W
RATED OPERATIONAL CURRENT FOR SPECIFIED HEAT DISSIPATION (IN)	65 A
STATIC HEAT DISSIPATION, NON-CURRENT-DEPENDENT PVS	1 W

Electrical rating

RATED BREAKING CAPACITY AT 220/230 V	650 A
---	-------

RATED BREAKING CAPACITY AT 380/400 V	650 A
---	-------

RATED BREAKING CAPACITY AT 500 V	650 A
---	-------

RATED BREAKING CAPACITY AT 660/690 V	370 A
---	-------

RATED INSULATION VOLTAGE (UI)	690 V
--------------------------------------	-------

RATED MAKING CAPACITY UP TO 690 V (COS PHI TO IEC/EN 60947)	910 A
--	-------

RATED OPERATIONAL CURRENT (IE) AT AC-1, 380 V, 400 V, 415 V	98 A
--	------

RATED OPERATIONAL CURRENT (IE) AT AC-3, 220 V, 230 V, 240 V	65 A
--	------

RATED OPERATIONAL CURRENT (IE) AT AC-3, 380 V, 400 V, 415 V	65 A
--	------

RATED OPERATIONAL CURRENT (IE) AT AC-3, 440 V	65 A
--	------

RATED OPERATIONAL CURRENT (IE) AT AC-3, 500 V	65 A
--	------

RATED OPERATIONAL CURRENT (IE) AT AC-3, 660 V, 690 V	37 A
---	------

RATED OPERATIONAL CURRENT (IE) AT AC-4, 220 V, 230 V, 240 V	25 A
--	------

RATED OPERATIONAL CURRENT (IE) AT AC-4, 440 V	25 A
--	------

RATED OPERATIONAL CURRENT (IE) AT AC-4, 500 V	25 A
--	------

RATED OPERATIONAL CURRENT (IE) AT AC-4, 660 V, 690 V	20 A
---	------

RATED OPERATIONAL CURRENT (IE) AT DC-1, 110 V	72 A
--	------

RATED OPERATIONAL CURRENT (IE) AT DC-1, 220 V	65 A
--	------

Electro magnetic compatibility

EMITTED INTERFERENCE	According to EN 60947-1
-----------------------------	-------------------------

INTERFERENCE IMMUNITY	According to EN 60947-1
------------------------------	-------------------------

RATED OPERATIONAL CURRENT (IE) AT DC-1, 60 V	72 A
RATED OPERATIONAL POWER AT AC-3, 240 V, 50 HZ	22 kW
RATED OPERATIONAL POWER AT AC-3, 380/400 V, 50 HZ	30 kW
RATED OPERATIONAL POWER AT AC-3, 415 V, 50 HZ	39 kW
RATED OPERATIONAL POWER AT AC-3, 440 V, 50 HZ	41 kW
RATED OPERATIONAL POWER AT AC-3, 500 V, 50 HZ	47 kW
RATED OPERATIONAL POWER AT AC-3, 690 V, 50 HZ	35 kW
RATED OPERATIONAL POWER AT AC-4, 220/230 V, 50 HZ	7 kW
RATED OPERATIONAL POWER AT AC-4, 240 V, 50 HZ	7.5 kW
RATED OPERATIONAL POWER AT AC-4, 415 V, 50 HZ	13 kW
RATED OPERATIONAL POWER AT AC-4, 440 V, 50 HZ	14 kW
RATED OPERATIONAL POWER AT AC-4, 500 V, 50 HZ	16 kW
RATED OPERATIONAL POWER AT AC-4, 660/690 V, 50 HZ	17 kW
RATED OPERATIONAL VOLTAGE (UE) AT AC - MAX	690 V

Features & functions	
FITTED WITH:	Suppressor circuit in actuating electronics
NUMBER OF POLES	Three-pole

General information	
APPLICATION	Contactors for Motors
CONNECTION	Screw terminals
DEGREE OF PROTECTION	IP00
LIFESPAN, MECHANICAL	10,000,000 Operations (DC operated)
OPERATING FREQUENCY	5000 mechanical

	Operations/h (DC operated)
OVERVOLTAGE CATEGORY	III
POLLUTION DEGREE	3
PRODUCT CATEGORY	Contactors
PROTECTION	Finger and back-of-hand proof, Protection against direct contact when actuated from front (EN 50274)
RATED IMPULSE WITHSTAND VOLTAGE (UIMP)	8000 V AC
RESISTANCE PER POLE	1.9 mΩ
SUITABLE FOR	Also motors with efficiency class IE3
UTILIZATION CATEGORY	AC-4: Normal AC induction motors: starting, plugging, reversing, inching AC-1: Non-inductive or slightly inductive loads, resistance furnaces AC-3: Normal AC induction motors: starting, switch off during running
VOLTAGE TYPE	DC
FRAME SIZE	FS3

Magnet system

ARCING TIME	10 ms
DROP-OUT VOLTAGE	At least smoothed two-phase bridge rectifier or three-phase rectifier 0.6 - 0.15 x UC, DC operated
DUTY FACTOR	100 %
PICK-UP VOLTAGE	24 - 27 V DC (RDC 24) 0.7 - 1.2 V DC x Uc
POWER CONSUMPTION (PICK-UP) AT DC	24 W
POWER CONSUMPTION (SEALING) AT DC	1 W
RATED CONTROL SUPPLY VOLTAGE (US) AT DC - MAX	27 V
RATED CONTROL SUPPLY VOLTAGE (US) AT DC - MIN	24 V
SWITCHING TIME (DC OPERATED, MAKE CONTACTS, CLOSING DELAY) - MAX	54 ms
SWITCHING TIME (DC OPERATED, MAKE CONTACTS, OPENING DELAY) - MAX	24 ms

Safety

SAFE ISOLATION	440 V AC, Between the contacts, According to EN 61140 440 V AC, Between coil and contacts, According to EN 61140
-----------------------	---

Motor rating

ASSIGNED MOTOR POWER AT 115/120 V, 60 HZ, 1-PHASE	5 HP
ASSIGNED MOTOR POWER AT 200/208 V, 60 HZ, 3-PHASE	20 HP
ASSIGNED MOTOR POWER AT 230/240 V, 60 HZ, 1-PHASE	15 HP
ASSIGNED MOTOR POWER AT 230/240 V, 60 HZ, 3-PHASE	25 HP
ASSIGNED MOTOR POWER AT 460/480 V, 60 HZ, 3-PHASE	50 HP
ASSIGNED MOTOR POWER AT 575/600 V, 60 HZ, 3-PHASE	60 HP

Short-circuit rating

SHORT-CIRCUIT CURRENT RATING (BASIC RATING)	10 kA, 250 A max. fuse, SCCR (UL/CSA) 10 kA, 250 A max. CB, SCCR (UL/CSA)
SHORT-CIRCUIT CURRENT RATING (HIGH FAULT AT 480 V)	100 kA, 150 A CLASS J max. fuse, SCCR (UL/CSA) 30 kA, 250 A max. fuse, SCCR (UL/CSA) 65 kA, 100 A max. CB, SCCR (UL/CSA) 30 kA, 250 A max. CB, SCCR (UL/CSA)
SHORT-CIRCUIT CURRENT RATING (HIGH FAULT AT 600 V)	100 kA, 150 A CLASS J max. fuse, SCCR (UL/CSA) 30 kA, 250 A max. fuse, SCCR (UL/CSA) 30 kA, 250 A max. CB, SCCR (UL/CSA)
SHORT-CIRCUIT PROTECTION RATING (TYPE 1 COORDINATION)	250 A gG/gL

AT 400 V

SHORT-CIRCUIT PROTECTION RATING (TYPE 1 COORDINATION) AT 690 V	100 A gG/gL
---	-------------

SHORT-CIRCUIT PROTECTION RATING (TYPE 2 COORDINATION) AT 400 V	125 A gG/gL
---	-------------

SHORT-CIRCUIT PROTECTION RATING (TYPE 2 COORDINATION) AT 690 V	80 A gG/gL
---	------------

Special purpose ratings**SPECIAL PURPOSE
RATING OF DEFINITE
PURPOSE RATING**

65 A, FLA 480 V 60 Hz 3-ph,
100,000 cycles acc. to UL
1995, (UL/CSA)
390 A, LRA 480 V 60 Hz 3-
ph, 100,000 cycles acc. to
UL 1995, (UL/CSA)

**SPECIAL PURPOSE
RATING OF ELEVATOR
CONTROL**

10 HP, 200 V 60 Hz 3-ph,
(UL/CSA)
32.2 A, 200 V 60 Hz 3-ph,
(UL/CSA)
15 HP, 240 V 60 Hz 3-ph,
(UL/CSA)
30 HP, 480 V 60 Hz 3-ph,
(UL/CSA)
42 A, 240 V 60 Hz 3-ph,
(UL/CSA)
41 A, 600 V 60 Hz 3-ph,
(UL/CSA)
40 A, 480 V 60 Hz 3-ph,
(UL/CSA)
40 HP, 600 V 60 Hz 3-ph,
(UL/CSA)

**SPECIAL PURPOSE
RATING OF RESISTANCE
AIR HEATING**

88 A, 600 V 60 Hz 3phase,
347 V 60 Hz 1phase,
(UL/CSA)
88 A, 480 V 60 Hz 3phase,
277 V 60 Hz 1phase,
(UL/CSA)

**SPECIAL PURPOSE
RATING OF TUNGSTEN
INCANDESCENT LAMPS**

88 A, 600 V 60 Hz 3phase,
347 V 60 Hz 1phase,
(UL/CSA)
88 A, 480 V 60 Hz 3phase,
277 V 60 Hz 1phase,
(UL/CSA)

**SPECIAL PURPOSE
RATING OF BALLAST
ELECTRICAL DISCHARGE
LAMPS**

88 A (600V 60Hz 3phase,
347V 60Hz 1phase)
88 A (480V 60Hz 3phase,
277V 60Hz 1phase)

Switching capacity

SWITCHING CAPACITY (MAIN CONTACTS, GENERAL USE)	88 A, Maximum motor rating (UL/CSA)
--	--

Terminal capacities

SCREW SIZE	M3.5, Terminal screw, Control circuit cables M6, Terminal screw, Main cables
SCREWDRIVER SIZE	0.8 x 5.5/1 x 6 mm, Terminal screw, Standard screwdriver 2, Terminal screw, Pozidriv screwdriver
STRIPPING LENGTH (CONTROL CIRCUIT CABLE)	10 mm
STRIPPING LENGTH (MAIN CABLE)	14 mm
TERMINAL CAPACITY (COPPER BAND)	2 x (6 x 9 x 0.8) mm (Number of segments x width x thickness), Main cables
TERMINAL CAPACITY (SOLID)	1 x (0.75 - 4) mm ² , Control circuit cables 1 x (0.75 - 16) mm ² , Main cables 2 x (0.75 - 2.5) mm ² , Control circuit cables 2 x (0.75 - 16) mm ² , Main cables
TERMINAL CAPACITY (STRANDED)	2 x (16 - 35) mm ² , Main cables 1 x (16 - 50) mm ² , Main cables
TIGHTENING TORQUE	3.3 Nm, Screw terminals, Main cables 1.2 Nm, Screw terminals, Control circuit cables
TERMINAL CAPACITY (FLEXIBLE WITH FERRULE)	1 x (0.75 - 2.5) mm ² , Control circuit cables 1 x (0.75 - 35) mm ² , Main cables 2 x (0.75 - 25) mm ² , Main cables 2 x (0.75 - 2.5) mm ² , Control circuit cables
TERMINAL CAPACITY (SOLID/STRANDED AWG)	Single 14 - 1, double 14 - 2, Main cables 18 - 14, Control circuit cables

Resources

CATALOGUES	eaton-product-overview-for-machinery-catalogue-ca08103003zen-en-us.pdf SmartWire-DT Catalog Product Range Catalog Switching and protecting motors
CHARACTERISTIC CURVE	eaton-contactors-component-dilm-characteristic-curve-003.eps eaton-contactors-short-time-loading-dilm-characteristic-curve.eps eaton-contactors-switch-dilm-characteristic-curve.eps eaton-contactors-switch-dilm-characteristic-curve-002.eps
DECLARATIONS OF CONFORMITY	eaton-contactor-declaration-of-conformity-uk251227en.pdf eaton-contactor-declaration-of-conformity-eu250744en.pdf
DRAWINGS	eaton-contactors-dilm-dimensions-002.eps eaton-contactors-dilm-dimensions-012.eps eaton-contactors-mounting-dilm-dimensions-002.eps eaton-contactors-mounting-dilm-dimensions.eps eaton-general-ie-ready-dilm-contactor-standards.eps eaton-contactors-mounting-dilm-3d-drawing.eps eaton-contactors-dilm-3d-drawing-011.eps
ECAD MODEL	ETN.277908.edz
INSTALLATION INSTRUCTIONS	IL03407033Z

INSTALLATION VIDEOS	WIN-WIN with push-in technology
MCAD MODEL	eaton-iec-contactors-mcad-drawings-dil-m40-72.dwg DA-CS-dil_m40_72
PEP ECO-PASSPORT	eaton-iec-contactors-pep-eato-00028-v0101-en.pdf
SYSTEM OVERVIEW	eaton-contactors-dilm-contactor-system-overview.eps
WIRING DIAGRAMS	eaton-contactors-contact-dilm-wiring-diagram-003.eps

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

DATE:



Eaton Corporation plc Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2026 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

