


Specifications



Photo is representative



Eaton 278444

Eaton Moeller® series ZB Overload relay, ZB32, Ir= 0.24 - 0.4 A, 1 N/O, 1 N/C, Direct mounting, IP20

General specifications

PRODUCT NAME	Eaton Moeller® series ZB Thermal overload relay
---------------------	---

CATALOG NUMBER	278444
-----------------------	--------

MODEL CODE	ZB32-0,4
-------------------	----------

EAN	4015082784447
------------	---------------

PRODUCT LENGTH/DEPTH	96 mm
-----------------------------	-------

PRODUCT HEIGHT	67 mm
-----------------------	-------

PRODUCT WIDTH	45 mm
----------------------	-------

PRODUCT WEIGHT	0.141 kg
-----------------------	----------

CERTIFICATIONS

CSA-C22.2 No. 60947-4-1-14
IEC/EN 60947-4-1
IEC/EN 60947
CSA
CSA File No.: 012528
CSA Class No.: 3211-03
CE
UL Category Control No.: NKCR
UL
UL File No.: E29184
VDE 0660
UL 60947-4-1



Powering Business Worldwide

Contacts

**NUMBER OF AUXILIARY
CONTACTS (CHANGE-
OVER CONTACTS)** 0

**NUMBER OF AUXILIARY
CONTACTS (NORMALLY
CLOSED CONTACTS)** 1

**NUMBER OF AUXILIARY
CONTACTS (NORMALLY
OPEN CONTACTS)** 1

**NUMBER OF CONTACTS
(NORMALLY CLOSED
CONTACTS)** 1

**NUMBER OF CONTACTS
(NORMALLY OPEN
CONTACTS)** 1

Design verification

10.10 TEMPERATURE RISE

The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.

10.11 SHORT-CIRCUIT RATING

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

10.12 ELECTROMAGNETIC COMPATIBILITY

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

10.13 MECHANICAL FUNCTION

The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

10.2.2 CORROSION RESISTANCE

Meets the product standard's requirements.

10.2.3.1 VERIFICATION OF THERMAL STABILITY OF ENCLOSURES

Meets the product standard's requirements.

10.2.3.2 VERIFICATION OF RESISTANCE OF INSULATING MATERIALS TO NORMAL HEAT

Meets the product standard's requirements.

10.2.3.3 RESIST. OF INSUL. MAT. TO ABNORMAL HEAT/FIRE BY INTERNAL ELECT. EFFECTS

Meets the product standard's requirements.

10.2.4 RESISTANCE TO ULTRA-VIOLET (UV) RADIATION

Meets the product standard's requirements.

10.2.5 LIFTING

Does not apply, since the entire switchgear needs to be evaluated.

10.2.6 MECHANICAL IMPACT

Does not apply, since the entire switchgear needs to be evaluated.

10.2.7 INSCRIPTIONS

Meets the product standard's requirements.

10.3 DEGREE OF PROTECTION OF ASSEMBLIES

Does not apply, since the entire switchgear needs to be evaluated.

10.4 CLEARANCES AND CREEPAGE DISTANCES

Meets the product standard's requirements.

10.5 PROTECTION

Does not apply, since the

AGAINST ELECTRIC SHOCK	entire switchgear needs to be evaluated.
10.6 INCORPORATION OF SWITCHING DEVICES AND COMPONENTS	Does not apply, since the entire switchgear needs to be evaluated.
10.7 INTERNAL ELECTRICAL CIRCUITS AND CONNECTIONS	Is the panel builder's responsibility.
10.8 CONNECTIONS FOR EXTERNAL CONDUCTORS	Is the panel builder's responsibility.
10.9.2 POWER-FREQUENCY ELECTRIC STRENGTH	Is the panel builder's responsibility.
10.9.3 IMPULSE WITHSTAND VOLTAGE	Is the panel builder's responsibility.
10.9.4 TESTING OF ENCLOSURES MADE OF INSULATING MATERIAL	Is the panel builder's responsibility.
EQUIPMENT HEAT DISSIPATION, CURRENT-DEPENDENT PVID	5.4 W
HEAT DISSIPATION CAPACITY PDISS	0 W
HEAT DISSIPATION PER POLE, CURRENT-DEPENDENT PVID	1.8 W
RATED OPERATIONAL CURRENT FOR SPECIFIED HEAT DISSIPATION (IN)	0.4 A
STATIC HEAT DISSIPATION, NON-CURRENT-DEPENDENT PVS	0 W

Electrical rating

**CONVENTIONAL
THERMAL CURRENT ITH
OF AUXILIARY CONTACTS
(1-POLE, OPEN)** 6 A

**RATED OPERATIONAL
CURRENT (IE) AT AC-15,
120 V** 1.5 A

**RATED OPERATIONAL
CURRENT (IE) AT AC-15,
220 V, 230 V, 240 V** 1.5 A

**RATED OPERATIONAL
CURRENT (IE) AT AC-15,
380 V, 400 V, 415 V** 0.9 A

**RATED OPERATIONAL
CURRENT (IE) AT DC-13,
110 V** 0.4 A

**RATED OPERATIONAL
CURRENT (IE) AT DC-13,
220 V, 230 V** 0.2 A

**RATED OPERATIONAL
CURRENT (IE) AT DC-13,
24 V** 0.9 A

**RATED OPERATIONAL
CURRENT (IE) AT DC-13,
60 V** 0.75 A

**RATED OPERATIONAL
VOLTAGE (UE) - MAX** 690 V

SAFE ISOLATION 440 V AC, Between main
circuits, According to EN
61140
440 V, Between auxiliary
contacts and main
contacts, According to EN
61140
240 V AC, Between
auxiliary contacts,
According to EN 61140

**SWITCHING CAPACITY
(AUXILIARY CONTACTS,
PILOT DUTY)** B600 at opposite polarity,
AC operated (UL/CSA)
R300, DC operated
(UL/CSA)
B300 at opposite polarity,
AC operated (UL/CSA)

VOLTAGE RATING - MAX 600 VAC

Features & functions

FEATURES

Test/off button
Phase-failure sensitivity
(according to IEC/EN
60947, VDE 0660 Part 102)
Reset pushbutton
manual/auto
Trip-free release

General information

AMBIENT OPERATING TEMPERATURE - MAX	55 °C
AMBIENT OPERATING TEMPERATURE - MIN	-25 °C
AMBIENT OPERATING TEMPERATURE (ENCLOSED) - MAX	40 °C
AMBIENT OPERATING TEMPERATURE (ENCLOSED) - MIN	-25 °C
CLASS	CLASS 10 A / IEC 60947-4-1, 8.2.1.5.1.1. c) 4 min
CLIMATIC PROOFING	Damp heat, cyclic, to IEC 60068-2-30 Damp heat, constant, to IEC 60068-2-78
DEGREE OF PROTECTION	IP20 IP00
FRAME SIZE	ZB32
MOUNTING METHOD	Direct attachment Direct mounting
OVERLOAD RELEASE CURRENT SETTING - MAX	0.4 A
OVERLOAD RELEASE CURRENT SETTING - MIN	0.24 A
OVERVOLTAGE CATEGORY	III
POLLUTION DEGREE	3
PRODUCT CATEGORY	- Accessories - Overload relay ZB up to 150 A
PROTECTION	Finger and back-of-hand proof, Protection against direct contact when actuated from front (EN 50274)
RATED IMPULSE WITHSTAND VOLTAGE (UIMP)	6000 V AC 4000 V (auxiliary and control circuits)
SHOCK RESISTANCE	10 g, Mechanical, Sinusoidal, Shock duration 10 ms
SUITABLE FOR	Branch circuits, (UL/CSA)
TEMPERATURE COMPENSATION	≤ 0.25 %/K, residual error for T > 40° Continuous

Short-circuit rating

SHORT-CIRCUIT CURRENT RATING (HIGH FAULT AT 600 V)	1 A, Class J/CC, max. Fuse, SCCR (UL/CSA) 100 kA, Fuse, SCCR (UL/CSA)
SHORT-CIRCUIT PROTECTION RATING	25 A gG/gL, Fuse, Type "1" coordination Max. 6 A gG/gL, fuse, Without welding, Auxiliary and control circuits 2 A gG/gL, Fuse, Type "2" coordination Information on Type "1" and Type "2" coordination applies to 100 kA and 690 V

Terminal capacities

SCREW SIZE	M4, Terminal screw M3.5, Terminal screw, Control circuit cables
SCREWDRIVER SIZE	1 x 6 mm, Terminal screw, Standard screwdriver 2, Terminal screw, Pozidriv screwdriver
STRIPPING LENGTH (CONTROL CIRCUIT CABLE)	8 mm
STRIPPING LENGTH (MAIN CABLE)	10 mm
TERMINAL CAPACITY (FLEXIBLE WITH FERRULE)	1 x (1 - 4) mm ² , Main cables 2 x (1 - 4) mm ² , Main cables 1 x (0.75 - 2.5) mm ² , Control circuit cables 2 x (0.75 - 2.5) mm ² , Control circuit cables
TERMINAL CAPACITY (SOLID)	1 x (0.75 - 4) mm ² , Control circuit cables 2 x (1 - 6) mm ² , Main cables 2 x (0.75 - 4) mm ² , Control circuit cables 1 x (1 - 6) mm ² , Main cables
TERMINAL CAPACITY (SOLID/STRANDED AWG)	18 - 8, Main cables 2 x (18 - 14), Control circuit cables
TIGHTENING TORQUE	1.2 Nm, Screw terminals, Control circuit cables 1.8 Nm, Screw terminals, Main cables

Resources

CATALOGUES	eaton-product-overview-for-machinery-catalogue-ca08103003zen-en-us.pdf
CHARACTERISTIC CURVE	eaton-tripping-devices-overload-relay-zb-overload-relay-characteristic-curve-002.eps eaton-tripping-zb-overload-relay-characteristic-curve-002.eps
DECLARATIONS OF CONFORMITY	eaton-thermal-overload-relay-declaration-of-conformity-uk251269en.pdf eaton-thermal-overload-relay-declaration-of-conformity-eu250786en.pdf
DRAWINGS	eaton-tripping-devices-overload-relay-zb-overload-relay-dimensions.eps eaton-tripping-devices-overload-relay-zb-overload-relay-dimensions-004.eps eaton-tripping-devices-zb-overload-relay-dimensions-002.eps eaton-tripping-devices-overload-relay-zb-overload-relay-3d-drawing-002.eps
ECAD MODEL	DA-CE-ETN.ZB32-0,4
INSTALLATION INSTRUCTIONS	IL03407195Z eaton-overload-relays-zb12-zb32-il03407015z.pdf DA-CS-zb32
MCAD MODEL	eaton-thermal-overload-relays-mcad-drawings-zb32.dwg
PEP ECO-PASSPORT	eaton-thermal-overload-relays-pep-eato-00458-v0101-en.pdf

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

DATE:



Eaton Corporation plc Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2026 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

