

Specifications



Photo is representative



Eaton 278616

Eaton Moeller series xEffect - FAZ MCB.
Miniature circuit breaker (MCB), 40 A, 1p,
characteristic: S

General specifications

PRODUCT NAME	Eaton Moeller series xEffect - FAZ MCB
CATALOG NUMBER	278616
MODEL CODE	FAZ-S40/1
EAN	4015082786168
PRODUCT LENGTH/DEPTH	80 mm
PRODUCT HEIGHT	75.5 mm
PRODUCT WIDTH	17.7 mm
PRODUCT WEIGHT	0.116 kg
COMPLIANCES	UL CSA09 (with supplementary protector only) RoHS conform
CERTIFICATIONS	UL 1077 CSA (Class No. 3215-30) IEC/EN 60898 UL (Category Control Number QVNU2, QVNU8) IEC/EN 60947-2 UL (File No. E177451) CE marking CSA-C22.2 No. 235 CSA (File No. 204453) North America (UL recognized, CSA certified) EN45545-2 IEC 61373



Powering Business Worldwide

Additional information

CURRENT LIMITING CLASS

3

FEATURES

Additional equipment possible

SPECIAL FEATURES

Ambient temperature hint: a 1 °C increase results in a 0.5% linear reduction of current carrying capacity

USED WITH

Miniature circuit breaker FAZ

Delivery programme

AMPERAGE RATING

40 A

APPLICATION

- Branch circuits, not as BCPD
- Switchgear for industrial and advanced commercial applications
- xEffect - Switchgear for industrial and advanced commercial applications

NUMBER OF POLES

Single-pole

NUMBER OF POLES (PROTECTED)

1

NUMBER OF POLES (TOTAL)

1

RELEASE CHARACTERISTIC

Other

TRIPPING CHARACTERISTIC

S

TYPE

- FAZ
- Miniature circuit breaker

Design verification to IEC/EN 61439

10.10 TEMPERATURE RISE	The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.
10.11 SHORT-CIRCUIT RATING	Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.12 ELECTROMAGNETIC COMPATIBILITY	Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.13 MECHANICAL FUNCTION	The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.
10.2.2 CORROSION RESISTANCE	Meets the product standard's requirements.
10.2.3.1 VERIFICATION OF THERMAL STABILITY OF ENCLOSURES	Meets the product standard's requirements.
10.2.3.2 VERIFICATION OF RESISTANCE OF INSULATING MATERIALS TO NORMAL HEAT	Meets the product standard's requirements.
10.2.3.3 RESIST. OF INSUL. MAT. TO ABNORMAL HEAT/FIRE BY INTERNAL ELECT. EFFECTS	Meets the product standard's requirements.
10.2.4 RESISTANCE TO ULTRA-VIOLET (UV) RADIATION	Meets the product standard's requirements.
10.2.5 LIFTING	Does not apply, since the entire switchgear needs to be evaluated.
10.2.6 MECHANICAL IMPACT	Does not apply, since the entire switchgear needs to be evaluated.
10.2.7 INSCRIPTIONS	Meets the product standard's requirements.
10.3 DEGREE OF PROTECTION OF ASSEMBLIES	Does not apply, since the entire switchgear needs to be evaluated.
10.4 CLEARANCES AND CREEPAGE DISTANCES	Meets the product standard's requirements.
10.5 PROTECTION	Does not apply, since the

Design verification to IEC/EN 61439 - technical data

AMBIENT OPERATING TEMPERATURE - MAX	75 °C
AMBIENT OPERATING TEMPERATURE - MIN	-25 °C
EQUIPMENT HEAT DISSIPATION, CURRENT-DEPENDENT	3.9 W
HEAT DISSIPATION CAPACITY	0 W
HEAT DISSIPATION PER POLE, CURRENT-DEPENDENT	0 W
RATED OPERATIONAL CURRENT FOR SPECIFIED HEAT DISSIPATION (IN)	40 A
STATIC HEAT DISSIPATION, NON-CURRENT-DEPENDENT	0 W

AGAINST ELECTRIC SHOCK	entire switchgear needs to be evaluated.
10.6 INCORPORATION OF SWITCHING DEVICES AND COMPONENTS	Does not apply, since the entire switchgear needs to be evaluated.
10.7 INTERNAL ELECTRICAL CIRCUITS AND CONNECTIONS	Is the panel builder's responsibility.
10.8 CONNECTIONS FOR EXTERNAL CONDUCTORS	Is the panel builder's responsibility.
10.9.2 POWER-FREQUENCY ELECTRIC STRENGTH	Is the panel builder's responsibility.
10.9.3 IMPULSE WITHSTAND VOLTAGE	Is the panel builder's responsibility.
10.9.4 TESTING OF ENCLOSURES MADE OF INSULATING MATERIAL	Is the panel builder's responsibility.

Technical data - electrical

ADMISSIBLE BACK-UP FUSE - MAX	125 A gL/gG
DIRECTION OF INCOMING SUPPLY	As required
FREQUENCY RATING - MAX	60 Hz
FREQUENCY RATING - MIN	50 Hz
LIFESPAN, ELECTRICAL	10000 operations
OPERATIONAL SWITCHING CAPACITY	7.5 kA
OVERVOLTAGE CATEGORY	III
POLLUTION DEGREE	2
RATED IMPULSE WITHSTAND VOLTAGE (UIMP)	4 kV
RATED INSULATION VOLTAGE (UI)	440 V
RATED OPERATIONAL VOLTAGE (UE) - MAX	230 V
RATED SHORT-CIRCUIT BREAKING CAPACITY (IEC 60947-2)- ICU AT 230 V	10 kA
RATED SHORT-CIRCUIT BREAKING CAPACITY (IEC 60947-2)- ICU AT 400 V	10 kA
RATED SWITCHING CAPACITY (IEC/EN 60947-2)	10 kA
SELECTIVITY CLASS	3
VOLTAGE RATING	240 V AC / 415 V AC
VOLTAGE RATING (UL CSA 13)	277 V AC; 48 V DC
VOLTAGE RATING AT DC	60 V DC (per pole)
VOLTAGE TYPE	AC

Technical data - mechanical

BUILT-IN DEPTH	70.5 mm
BUSBAR MATERIAL THICKNESS	0.8 mm - 2 mm
CONNECTABLE CONDUCTOR CROSS SECTION (MULTI-WIRED) - MAX	25 mm ²
CONNECTABLE CONDUCTOR CROSS SECTION (MULTI-WIRED) - MIN	1 mm ²
CONNECTABLE CONDUCTOR CROSS SECTION (SOLID-CORE) - MAX	25 mm ²
CONNECTABLE CONDUCTOR CROSS SECTION (SOLID-CORE) - MIN	1 mm ²
DEGREE OF PROTECTION	IP20 UL/CSA Type: - IP40 (when fitted) IP20 (IEC)
ENCLOSURE WIDTH	80 mm
FRAME	45 mm
MOUNTING METHOD	Top-hat rail IEC/EN 60715
MOUNTING POSITION	As required
MOUNTING WIDTH	17.5 mm
MOUNTING WIDTH PER POLE	17.5 mm
TERMINAL CAPACITY (CONTROL CABLE)	25 mm ² (1x)
TERMINAL CAPACITY OF SCREW TERMINALS FOR MAIN CABLE	10 mm ² (2x)
TERMINAL PROTECTION	Finger and hand touch safe, DGUV VS3, EN 50274
TERMINALS (TOP AND BOTTOM)	Twin-purpose terminals
WIDTH IN NUMBER OF MODULAR SPACINGS	1

Resources

CATALOGUES

[eaton-xeffect-industrial-switchgear-range-catalog-ca003002en-en-us.pdf](#)

CHARACTERISTIC CURVE

[eaton-mcb-current-xeffect-faz-characteristic-curve.eps](#)

[eaton-mcb-current-xeffect-faz-characteristic-curve-002.eps](#)

[eaton-mcb-xeffect-faz-characteristic-curve-002.eps](#)

[eaton-xeffect-faz-mcb-characteristic-curve-004.jpg](#)

[eaton-mcb-characteristic-xeffect-faz-characteristic-curve-003.eps](#)

[eaton-xeffect-faz-mcb-characteristic-curve-003.jpg](#)

[eaton-mcb-characteristic-xeffect-faz-characteristic-curve-006.eps](#)

[eaton-mcb-tripping-characteristic-xeffect-faz-characteristic-curve.eps](#)

[eaton-mcb-tripping-characteristic-xeffect-faz-characteristic-curve-002.eps](#)

[eaton-mcb-xeffect-faz-characteristic-curve.eps](#)

DECLARATIONS OF CONFORMITY

[eaton-mcb-declaration-of-conformity-eu251404en.pdf](#)

[eaton-mcb-declaration-of-conformity-uk251434en.pdf](#)

DRAWINGS

[eaton-mcb-xeffect-faz-dimensions.eps](#)

[eaton-xeffect-faz-mcb-dimensions.jpg](#)

[eaton-xeffect-faz-mcb-3d-drawing-005.jpg](#)

[eaton-xeffect-faz-mcb-3d-drawing-014.jpg](#)

ECAD MODEL	DA-CE-ETN.FAZ-S40_1
INSTALLATION INSTRUCTIONS	eaton-mcb-rccb-rcbo-g9-il019140zu.pdf
MCAD MODEL	eaton-non-selective-universal-mcb-mcad-3d-models-faz-xxx-1p.stp
PEP ECO-PASSPORT	eaton-non-selective-universal-mcb-pep-eato-00047-v0101-en.pdf
WIRING DIAGRAMS	eaton-xpole-mmc4-6-m-mcb-wiring-diagram-002.jpg eaton-mcb-xeffect-faz-wiring-diagram.eps

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

DATE:



Eaton Corporation plc Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2026 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

